

Product Specification



LED Bollard Light
Walkway Standard Series



Dome



Flat

Product Features

- 15w
- Dome or Flat Options
- Dome: 4000K
Flat: 3 Colour Adjustable 3000K/4000K/5000K
- Aluminium post with PC Lens
- Dome: Ø120 x 1020mm
Flat: Ø120 x 990mm
- IP65, IK08 Housing
- Weight: 4.5kg

Specification Overview



Model	Watt	Type	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
BOL-W120D	15w	Dome	4000K	991lm	360°	Black	Ø120mm x 1020mm
BOL-W120F-3C	15w	Flat	3000K/4000K/5000K	991lm	360°	Black	Ø120mm x 990mm

Product Specification



LED Bollard Light
Walkway MAX Series



Dome Flat Pillar

Product Features

- 20w
- Dome, Flat or Pillar Options
- Dome/Pillar: 4000K
Flat: 3 Colour Adjustable 3000K/4000K/5000K
- Aluminium post with PC Lens
- Dome: Ø160 x 1015mm
Flat: Ø160 x 980mm
Pillar: Ø160 x 995mm
- IP65, IK08 Housing
- Weight: 8.25kg

Specification Overview



Model	Watt	Type	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
BOL-W160D	20w	Dome	4000K	1107lm	360°	Black	Ø160mm x 1015mm
BOL-W160F-3C	20w	Flat	3000K/4000K/5000K	1107lm	360°	Black	Ø160mm x 980mm
BOL-W160P	20w	Pillar	4000K	1107lm	360°	Black	Ø160mm x 995mm

Product Specification



LED Bollard Light
Walkway Louver MAX Series



Dome Flat Pillar

Product Features

- 20w
- Dome, Flat or Pillar Options
- 4000K
- Aluminium post with PC Lens
- Dome: Ø160 x 1000mm
- Flat: Ø160 x 1015mm
- Pillar: Ø160 x 980mm
- IP65, IK08 Housing
- Weight: 8.25kg

Specification Overview



Model	Watt	Type	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
BOL-L160D	20w	Dome	4000K	1107lm	360°	Black	Ø160mm x 1000mm
BOL-L160F-3C	20w	Flat	4000K	1107lm	360°	Black	Ø160mm x 1015mm
BOL-L160P	20w	Pillar	4000K	1107lm	360°	Black	Ø160mm x 980mm

LED Bollard Light

Walkway Series

Specification	Walkway		Walkway MAX			Louver MAX		
Model	BOL-W120		BOL-W160			BOL-L160		
Head Type	Dome	Flat	Dome	Flat	Pillar	Dome	Flat	Pillar
Colour Temperature	4000K	3CCT 3000K/4000K/5000K	4000K	3CCT 3000K/4000K/5000K	4000K	4000K		
Lumen (lm)	991lm		1107lm			1107lm		
Efficiency (lm/w)	>66lm/w		>55lm/w			>55lm/w		
Light Source	LED							
CRI (%)	≥80							
Beam Angle	360°							
Power Requirement	220~240VAC							
Power Consumption	15w		20w			20w		
Dimmable	No		No			No		
Housing	Aluminium with polycarbonate lens							
Lifespan	>50,000 hours							
Operation Temperature	-20°C~+60°C							
Product Dimension (Diameter)	Ø120mm		Ø160mm			Ø160mm		
Product Dimension (Height)	1020mm	990mm	1015mm	980mm	995mm	1000mm	1015mm	980mm
Impact Rating	IK08							
Weight	4.5kg		8.25kg			8.25kg		
Protection Rating	IP65							
Warranty	3 Years							