

100w LED Canopy Light (Small)

Product Features

- 100w
- CCT: 5000K
- Large range input 180~295VAC
- Easy connect junction box on rear with large terminal block
- Aluminium die cast housing
- Opal Polycarbonate Lens
- 120° Beam Angle
- 455 x 455 x 110mm
- IP65 Housing
- Weight:6kg











Specification Overview

Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SCL-100W-VS	100w	180~295VAC	5000K	8882lm	120°	White	455x455x110mm



100w LED Canopy Light (Small)



	116	A		
j		0.00		
1				
1			1.1.	
	-	3 .	10	

		\wedge	
n	672.7,27401x		341.98cm
n	168.2,685.01x		683.95cm
m	74.74,304.41x		1025.93cm
m	42.04,171.31x		1367.91cm
m	26.91,109.61x		1709.88cm
im	18.69,76.111x		2051.86cm
m	13.73,55.921x		2393.84cm
m	10.51,42.811x		2735.81cm
m	8.305,33.831x		3077.79cm
m	6.727,27.401x		3419.77cm
t	Eavg, Emax	Angle:119.36deg	Diameter

Specification	
Model	SCL-100W-VS
Colour Temperature (1CCT)	5000K
Lumen (lm)	8882lm
Efficiency (Im/w)	>89lm/w
Light Source	LED
CRI (%)	≥80
Beam Angle	120°
Power Requirement	180~295VAC
Power Consumption	98.79w
Dimmable	No
Housing	Diecast aluminium with PC Lens
Lifespan	>40,000 hours
Operation Temperature	-20°C~+80°C
Product Dimension	455 x 455 x 110mm
Impact Rating	IK10
Weight	6kg
Protection Rating	IP65
Warranty	5 Years
Spe	ecifications are subject to change without notice

Specifications are subject to change without notice

