

Product Features

- 3w, 12VDC operation
- 3 colour adjustable (3000K, 4000K, 5000K)
- Can be surface mounted or recess mounted
- Low Profile
- 120° Beam Angle
- Ø70 x 13.7mm
- 57mm cut-out
- 1.9m Fig-8 cable and plug included
- Driver sold separately
- Weight: 62g

Options:



CAB-PWR-6 Drives 1 – 6 lights Non-Dimmable



Specification Overview



| • | | | | | | | 5627 |
|------------------|-------|-------|-------------------|-----------|---------------|----------------|--------------|
| Model | Power | Input | Colour Temp | Lumens | Beam Angle | Trim Colour | Dimensions |
| CAD 0257 2C WILT | 2\\/ | 13VDC | 2000K/4000K/2000K | 190~250lm | 120° | \M/hito | Ø70 v 12 7mm |

Product Specification

LED Cabinet Light 3w Ø70mm




Switch to Excellence

| Model | Power | Lumens | ССТ | Cut-Out | Dimension (Dia x H) | Weight |
|-----------------|-------|-----------|-------------------|---------|------------------------|--------|
| CAB-0357-3C-WHT | 3W | 180~250lm | 3000K/4000K/5000K | 57mm | Ø70 x 13.7mm | 82g |


| Specification | 1 | | | Dimensions |
|----------------------|--------------------------|--------------------------|-----------------|------------------------|
| ССТ | 3000K/4000K/5000K | Housing | Aluminium | |
| Efficacy | >60lm/w | Lens | Polycarbonate | |
| CRI (%) | ≥80 | Housing Colour | White | 13.7mm |
| Beam Angle | 120° | Lifespan | >50,000 hours | → 70mm < |
| Power Input | 12VDC, constant voltage* | Operation Temperature | -20 °C to +45°C | ⊕ |
| Dimmable | No | | | → 65mm < |
| Impact Rating | IK08 | | | |
| Protection Rating | IP20 | Warranty | 3 Years | • |

Mounting Options

Recessed Mounting



Surface Mounting



* Cabinet lights can be wired in parallel avoiding the requirement of a Junction box. Junction box is supplied with optional CAB-PWR-6 driver and is not sold separately

Specifications are subject to change without notice

