

Product Specification




Low Glare Down Light
Reflector 10w Ø108mm



Product Features

- 10w
- 3 colour adjustable (3000K, 4000K, 5000K)
- Low Glare Design
- Available in White or Black trim
- 60° Beam Angle
- Ø108 x 90mm
- 90mm cut-out
- IP44 protection
- 0.6m Flex cable and plug included
- Weight: 260g

Specification Overview



Model	Power	Size	Colour Temp	Lumens	Beam Angle	Trim Colour	Power Requirement
DLU-1090R-3C-W	10w	Ø108 x 90mm	3000K/4000K/5000K	1000~1200lm	60°	White	220~240VAC
DLU-1090R-3C-B	10w	Ø108 x 90mm	3000K/4000K/5000K	1000~1200lm	60°	Black	220~240VAC

Low Glare Down Light
Reflector 10w Ø108mm

Model	Power	Lumens	CCT	Cut-Out	Dimension (Dia x H)	Weight
DLU-1090R-3C-W	10w	1000~1200lm	3000K/4000K/5000K	90mm	Ø108 x 90mm	260g
DLU-1090R-3C-W	10w	1000~1200lm	3000K/4000K/5000K	90mm	Ø108 x 90mm	260g

Specification				Dimensions	
CCT	3000K/4000K/5000K	Housing	Plastic Coated Aluminium		
Efficacy	>100lm/w	Lens	Polycarbonate		
CRI (%)	≥80	Housing Colour	White or Black options		
Beam Angle	60°	Lifespan	>40,000 hours		
Power Input	220~240VAC	Operation Temperature	-20 °C to +45°C		
Dimmable	Yes, (with LED, Universal or Trailing Edge Dimmers)				
Impact Rating	IK08				
Protection Rating	IP44	Warranty	3 Years		

Technical drawing of a spotlight showing dimensions: height 90, lens diameter 81, and base diameter 108.

