

Product Features

- 12w
- 3 colour adjustable (3000K, 4000K, 5000K)
- **Remote Driver**
- 110° Beam Angle
- Ø108 x 38mm
- 90mm cut-out
- Flex cable and plug included
- Weight: 350g





Specification Overview









Model	Power	Size	Colour Temp	Lumens	Beam Angle	Trim Colour	Power Requirement
PDL-1290-3C-WHT	12w	Ø108 x 38mm	3000K/4000K/5000K	950~1050lm	110°	White	220~240VAC

Product Specification

LED Down Light

PDL (Flat Trim) 12w Ø108



Switch to Excellence

Model	Power	Lumens	ССТ	Cut-Out	Dimension (Dia x H)	Weight
PDL-1290-3C-WHT	12w	950~1050lm	3000K/4000K/5000K	90mm	Ø108 x 38mm	350g

Specification			
ССТ	3000K/4000K/5000K	Housing	Aluminium
Efficacy	>80lm/w	Lens	Polycarbonate
CRI (%)	≥80	Housing Colour	White
Beam Angle	110°	Lifespan	>50,000 hours
Power Input	220~240VAC	Operation Temperature	-20 °C to +45°C
Dimmable	Yes, (with LED, Universal or Trailing Edge Dimmers)		
Impact Rating	IK08		
Protection Rating	IP44	Warranty	5 Years

