

Product Features

- 10w
- 4000K
- 36° Beam Angle
- Choice of black or white trim
- Dimmable
- Ø80 x 130mm
- Weight: 500g











Specification Overview

Model	Power	Size	Colour Temp	Lumens	Beam Angle	Trim Colour	Power Requirement
DLS-1080-T-B	10w	Ø80 x 130mm	4000K	1190lm	36°	Black	220~240VAC
DLS-1080-T-W	10w	Ø80 x 130mm	4000K	1190lm	36°	White	220~240VAC

Product Specification

Surface Mount Down Light

Round 10w Ø80mm



Switch to Excellence

Model	Power	Lumens	ССТ	Trim Colour	Dimension (Dia x H)	Weight
DLS-1080-T-B	10w	1190lm	4000K	Black	Ø80 x 130mm	500g
DLS-1080-T-W	10w	1190lm	4000K	White	Ø80 x 130mm	500g

Specification	1			Dimensions
ССТ	4000K	Housing	Aluminium	
Efficacy	>110lm/w	Lens	Polycarbonate	
CRI (%)	≥80	Housing Colour	Black or White options	Ø80m
Beam Angle	110°	Lifespan	>40,000 hours	
Power Input	220~240VAC	Operation Temperature	-20 °C to +45°C	
Dimmable	Yes, (with LED, Universal or Trailing Edge Dimmers)			130m
Impact Rating	IK08			m
Protection Rating	IP44 (front), IP20 (rear)	Warranty	3 Years	-