

Product Specification



Surface Mount Down Light
Square 16w 115x115mm



Product Features

- 16w
- High CRI: ≥90%
- 3 colour adjustable (3000K, 4000K, 5000K)
- 36° Beam Angle
- Adjustable lighting orientation with 350° horizontal and 25° vertical
- Choice of black or white trim
- Flicker Free Driver
- 115 x 115 x 122mm
- Weight: 900g



Specification Overview



COLOUR SELECT



DIMMABLE



FLICKER-FREE LIGHTING



5827



Model	Power	Size	Colour Temp	Lumens	Beam Angle	Trim Colour	Power Requirement
DLS-16SQ-3C-B	16w	115x115x122mm	3000K/4000K/5000K	1600~1840lm	36°	Black	220~240VAC
DLS-16SQ-3C-W	16w	115x115x122mm	3000K/4000K/5000K	1600~1840lm	36°	White	220~240VAC

Surface Mount Down Light

Square 16w 115x115mm

Model	Power	Lumens	CCT	Trim Colour	Dimension	Weight
DLS-16SQ-3C-B	16w	1600~1840lm	3000K/4000K/5000K	Black	115x115x122mm	900g
DLS-16SQ-3C-W	16w	1600~1840lm	3000K/4000K/5000K	White	115x115x122mm	900g

Specification				Dimensions	
CCT	3000K/4000K/5000K	Housing	Aluminium		
Efficacy	>100lm/w	Lens	Polycarbonate		
CRI (%)	≥90	Housing Colour	Black or White options		
Beam Angle	36°	Lifespan	>40,000 hours		
Power Input	220~240VAC, Flicker Free	Operation Temperature	-20 °C to +45°C		
Dimmable	Yes, (with LED, Universal or Trailing Edge Dimmers)				
Impact Rating	IK08				
Protection Rating	IP20	Warranty	3 Years		



A	115mm
B	115mm
C	122mm
D	80mm