

## LED Spitfire Emergency Light



### **Product Features**

- 5W
- Available in white or black housing
- Non-Maintained Emergency Mode
- 85mm with a 143mm adaptor plate
- Recessed Installation (surface mount boxes available)
- Complies with AS2293.3
- Classification C0:D63;C90:D63
- Ø85mm or Ø143 x 24mm



## **Specification Overview**







Model	Power	Power Requirement	Trim Colour	Dimensions
EM-SF	5w	110~240VAC	White	Ø85mm or Ø143 x 24mm
EM-SF-B	5w	110~240VAC	Black	Ø85mm or Ø143 x 24mm
EM-SMB-RD	Round Surface Mount Housing		White	
EM-SMB-RD-B	Round Surface Mount Housing		Black	
EM-SMB-RT	Rectangle Surface Mount Housing		White	
EM-SMB-RT-B	Rectangle Surface Mount Housing		Black	
EM-SMB-IP	IP65 Surface Mount Housing		White	



# **LED Spitfire Emergency Light**



### **Options**



Model: EM-SMB-RD
Round Surface Mount Housing – White

Model: EM-SMB-RD-B Round Surface Mount Housing - Black



Model: EM-SMB-RT
Rectangle Surface Mount Housing – White

Model: EM-SMB-RT-B Rectangle Surface Mount Housing – Black



Model: EM-SMB-IP
IP65 Surface Mount Housing

5	pe	CITI	ıca	tio	n

EM-SF	EM-SF-B		
White	Black		
LED			
110~240VAC			
5w			
> 3 hours			
< 16 hours			
Manual			
Li-ion: 3.7V / 2200mAH			
Flame retardant PC			
Recessed Ceiling or Surface Mount (requires optional housing)			
Ø85 x 24mm / Ø143 x 24mm (using adaptor)			
111 x 42 x 25mm			
80 x 35 x 23mm			
700g			
IP20			
C0:D63;C90:D63			
3 Years (Battery 1 year)			
	White  LED  110~240VAC  5w  > 3 hours  < 16 hours  Manual  Li-ion: 3.7V / 2200mAH  Flame retardant PC  Recessed Ceiling or Suroptional housing)  Ø85 x 24mm / Ø143 x 2  111 x 42 x 25mm  80 x 35 x 23mm  700g  IP20  C0:D63;C90:D63		

Specifications are subject to change without notice

