

Surface Mount Blade Exit Sign 24m

Product Features

- 4W
- **Polycarbonate Housing**
- Maintained Emergency Mode
- Complete with all pictograms
- Complies with AS2293.3
- Classification C0:E4.0;C90:D2.0
- 358 x 215 x 60mm



Specification Overview

Model	Power	Power Requirement	Viewing Distance	Trim Colour	Dimensions
EXIT-SBS	4w	110~240VAC	24m	White	358 x 215 x 60mm
EXIT-SBS-B	4w	110~240VAC	24m	Black	358 x 215 x 60mm
EXIT-RKIT	Recessed Kit, use together with EXIT-SBS to become a recessed fitting			White	457 x 100 x 70mm
EXIT-RKIT-B	Recessed Kit, use together with EXIT-SBS-B to become a recessed fitting			Black	457 x 100 x 70mm



www.s-tech.com.au

08 9330 8485

Product Specification


Surface Mount Blade Exit Sign 24m

.

Standard



358mm



Pictograms:



Options:



Í			N
	215mm		Т
			L
		60mm	Ρ
-			Ρ
2			S
2	215mm		С
		L	

100mm

Recessed Kit – White Model: EXIT-RKIT

Recessed Kit – Black Model: EXIT-RKIT-B

Specification		 	
5) UELUI I I UGI I I UDI I	Sin	COTI	on
		 L a L	UII

Specification				
Model	EXIT-SBS	EXIT-SBS-B		
Trim Colour	White	Black		
Light Source	LED			
Power Requirement	110~240VAC			
Power Consumption	4w			
Standby Time	> 3 hours			
Charging Time	< 16 hours			
Testing	Manual			
Indicator	Green and Red (Bi-Colour)			
Battery Capacity	LifePO4: 3.2V / 500mAH			
Housing	Body: PC Diffuser: PE Diffuser: PC with light diffuser			
Mounting	Ceiling, Wall or Recessed (requires kit)			
Cable Entry	Ø21mm			
Product Dimension	358 x 215 x 60mm			
Weight	1.1kg			
Protection Rating	IP20			
Classification	C0:E4.0;C90:D2.0			
Warranty	3 Years (Battery 1 year)			
Specifications are subject to change without notice				



www.s-tech.com.au

08 9330 8485

exit