

## Surface Mount JUMBO Exit Sign 40m

## **Product Features**

- 6W
- **Polycarbonate Housing**
- Maintained Emergency Mode
- Complete with all pictograms
- Complies with AS2293.3
- Classification C0:D0.32;C90:D10
- 630 x 320 x 100mm






Canning Vale WA 6155

Model	Power	Power Requirement	Viewing Distance	Trim Colour	Dimensions
EXIT-JUMBO	6w	110~240VAC	40m	White	630 x 320 x 100mm
-tech		www.s-tech.com	au 08.933	0 8485	S-Tech Holdings Pty Ltd 12 Mordaunt Circuit,



## **Product Specification**

## Surface Mount JUMBO Exit Sign 40m



Pictograms:



Specification				
Model	EXIT-JUMBO			
Light Source	LED			
Power Requirement	110~240VAC			
Power Consumption	6w			
Standby Time	> 3 hours			
Charging Time	< 16 hours			
Testing	Manual			
Indicator	Green and Red (Bi-Colour)			
Battery Capacity	LifePO4: 3.7V / 2200mAH			
Housing	Body: Steel Diffuser: PE			
Mounting	Wall, Ceiling or Suspended			
Cable Entry	Ø21mm			
Product Dimension	630 x 320 x 100mm			
Weight	1.1kg			
Protection Rating	IP20			
Classification	C0:D0.32;C90:D10			
Warranty	3 Years (Battery 1 year)			
	Specifications are subject to change without notice			



www.s-tech.com.au

08 9330 8485

exit