Product Specification












100w V24 Green Eyewash LED Flood Light

Product Features

- 100w
- Green LED's
- Suitable for Eye Wash Stations
- Full range power input 90~305VAC
- Aluminium die cast housing
- Tempered glass face
- 120° Symmetrical Beam Angle
- 309 x 312 x 53mm
- Rating: IP66
- Weight: 2.72kg











| Model | Watt | Size | ССТ | Lumens | Beam Angle | Trim Colour | Weight |
|------------|------|------------------|-------|----------|---------------|----------------|--------|
| FI_100S_GI | 100w | 200 v 212 v 52mm | Green | 13 000lm | 120° | Black | 2 72kg |

Rev. 1.0, 2025 www.s-tech.com.au | 08 9330 8485





Mounting Holes



Options:



Pole Mounted Head Frames Single Model: SL-HF-1 Double Model: SL-HF-2 Triple Model: SL-HF-3 Available in Galvanised or PC options



Mounting Poles
Contact for options
Available in Galvanised or PC options

Poles and head frames are available in galvanised or powder coated finishes

| Specification | | | | | |
|---------------------------|---|--|--|--|--|
| Model | FL-100S-GL | | | | |
| Colour Temperature (1CCT) | Green | | | | |
| Lumen (Im) | 13,000lm | | | | |
| Efficiency (lm/w) | >130lm/w | | | | |
| Light Source | LED | | | | |
| CRI (%) | ≥80 | | | | |
| Beam Angle | 120° | | | | |
| Power Requirement | 90~305VAC | | | | |
| Power Consumption | 100w | | | | |
| Dimmable | No | | | | |
| Housing | Diecast aluminium with toughened glass lens | | | | |
| Lifespan | >50,000 hours | | | | |
| Operation Temperature | -20°C~+60°C | | | | |
| Product Dimension | 309 x 312 x 53mm | | | | |
| Impact Rating | IK08 | | | | |
| Weight | 2.72kg | | | | |
| Protection Rating | IP66 | | | | |
| Warranty | 5 Years | | | | |

Specifications are subject to change without notice