

Please read these instructions carefully in full prior to carrying out the installation.

IMPORTANT SAFETY ISSUES

- This product must be installed by a qualified electrician according to AS/NZS 3000.
- Ensure that the AC power is disconnected at the switchboard and test to ensure that there is no power on the circuit prior to starting installation.
- This product is rated to IP20 (front) and is not suitable for damp environments.
- Modification of this product will void any warranty.
- When cleaning or replacing the light, please ensure the power is off and the light is completely cooled down. Cleaning can be done using a soft cloth and PH neutral detergent.

INSTALLATION INSTRUCTIONS

Step 1: Turn off the power supply

Step 2: This model has 2 power input options, option 1 is through the endcap, option 2 is through the centre.

Option 1 - Slide the endcap out (opposite end to the colour and power select switches) and reveal the terminal block, knock out or notch out the endcap to and terminate the power cable into the terminal block.

Option 2 - Slide both endcaps out and remove the diffuser from the front (fig. 3) to reveal the terminal block, pull through the power cable and terminate the power cable into the terminal block.

Step 3: Fix the light to the ceiling and either replace the cover or just the endcap (depending on power input option). If you installed as Option 2, ensure that the power cable is pushed flat to stop it pressing against the diffuser so it does not create shadows on the front of the lens.

Step 4: Adjust the LED Power and the Colour Temperature using the switches on endcap. The default setting is 40w and 4000K.

NOTE: Please do not adjust the Power or Colour Temperature when the light is ON as it will damage the driver

Step 5: Turn on the power supply and ensure the luminaire is working.

