



Remote Control



Wall Switch

Solar Shed Batten Series

Product Features

- 360mm or 600mm batten options
- Automatic night-time operation
- Built-in PIR motion sensor
- Supplied with remote control and wall switch
- Light can be used during the day or night
- Dedicated 5V USB charge port
- Cable Length: 5m (panel to light), 3m (light to wall switch)
- 120° Beam Angle
- Lamp Rating: IP65
- Lamp Impact Rating: IK06
- Weight: 2kg (360mm), 3kg (600mm)



Model	Watt	Size	CCT	Lumens	Beam Angle	Trim Colour	Weight
SSBL-12W	12w	Light: 360 x 60 x 80mm Panel: 350 x 170 x 17mm	6000K	1200lm	120°	White	2kg
SSBL-15W	16w	Light: 600 x 60 x 85mm Panel: 550 x 170 x 17mm	6000K	2500lm	120°	White	3kg

Solar Shed Batten Series



Wall Switch



Mount the wall switch within 3m of the light fitting near the door to allow you to switch on and off the light.
Operation as follows:

- 1st Push : 100% Brightness
- 2nd Push : 50% Brightness
- 3rd Push : 30% standby brightness, 100% when motion
- 4th Push : Light Off



Remote Control



- Switch light ON/OFF 100% Power (activates day mode)
- Automatic ON/OFF, dusk to dawn (activates night mode)
- Increase Brightness
- Decrease Brightness
- 0% Standby, 100% when motion
- 30% Standby, 100% when motion
- Works for 2hrs then off
- Works for 4hrs then off
- Works for 6hrs then off

Settings for night mode only

This product is designed for residential use and supplied with wall switches and a remote control. We recommend the SWP-2FT-12CM for commercial applications, however this will only operate at night (dusk to dawn).

* S-Tech solar products are designed for dusk to dawn operation with added allowance for winter conditions, however you must be aware that in winter months it is possible that some nights the light will not last all night due to inclement weather conditions limiting charging time. Solar is not recommended for any locations classed as critical lighting areas where lighting is required all night.

Specification

Model	SSBL-12W	SSBL-15W
Colour Temperature	6000K	
Lumen (lm)	1200lm	2400lm
Efficiency (lm/w)	>100lm/w	>160lm/w
Light Source	LED	
CRI (%)	≥80	
Beam Angle	120°	
Power Requirement	Solar Powered	
Power Consumption	12w	16w
Cable Length	5m (light to solar panel)	
Battery (Li(NiCoMn)O2)	45WH 3.7v	94WH 3.7v
Charging Time	~6 hours	
Operation Time	Dusk to dawn*	
Light Housing	Aluminium and Polycarbonate	
Lifespan	>40,000 hours	
Operation Temperature	-15°C~+45°C	
Product Dimension (Light)	360 x 65 x 80mm	600 x 60 x 85mm
Product Dimension (Solar Panel)	350 x 170 x 17mm	550 x 170 x 17mm
Impact Rating	IK05	
Weight	2kg	3kg
Protection Rating	IP65	
Warranty	2 Years	

Specifications are subject to change without notice