


Product Features

- 67w Halogen Equivalent
- 6000K
- Dusk to Dawn Operation
- Inbuilt PIR Motion Sensor
- Flexible mounting options
- 4 mode settings
- Automatic night-time operation
- 0-90° adjustable light head and solar panel
- Includes kit to remote mount solar panel (length: 2m)
- IP65 Housing
- IK06 Impact Rating
- Weight: 650g



Includes kit to remote mount the solar panel



Fully portable, includes table stand





Specification Overview

Model E	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
---------	------------	-------------	--------	---------------	----------------	------------

SML-MINI 67w Halogen 4000K 1,000lm 120° Dark Grey 190 x 146.5 x 26.5mm

Product Specification

Solar Flood Light MINI - 1,000lm






Switch to Excellence

Model	Power	Lumens	ССТ	Dimension (W x H x D)	Weight
SML-MINI	67w Equivalent (Halogen)	1,000lm	4000K	190 x 146.5 x 26.5mm	650g

Specification				Dimensions
ССТ	4000K	Housing	Polycarbonate	
Efficacy	>100lm/w	Lens	Polycarbonate	
CRI (%)	≥80	Housing Colour	Dark Grey	31.1
Beam Angle	120°	Operation Temperature	-10°C to +55°C	
Solar Panel	2.2w	Lifespan	>30,000 hours	
Battery	LifePO4, 3.7V 14.8WH	Remote Control	No	-212
Charging Time	~8 Hours (from 0-100%)	Motion Sensor	PIR	
Operation Time	Dusk to dawn*	Sensor Range	≤6m	
Impact Rating	IK06			_
Protection Rating	IP65	Warranty	1 Year	



Mode Settings Features



M1 = 10% then 100% when motion detected (60s)

M2 = 0% then 100% when motion detected

(60s)

M3 = 30% brightness (6H) then off M4 = 100% brghtness (2H) then off



PIR Sensor

Black sensor to eliminate false triggers by interference.

Max. detection: 5m

^{*} S-Tech solar products are designed for dusk to dawn operation with added allowance for winter conditions, however you must be aware that in winter months it is possible that some nights the light will not last all night due to inclement weather conditions limiting charging time. Solar is not recommended for any locations classed as critical lighting areas where lighting is required all night.

