

## 40w Solar Motion Flood Light



## **Product Features**

- ON/OFF with remote either day or night
- Inbuilt Motion Sensor 2 operation modes: 1)
   Dimmed brightness (30%) until motion activated, or 2) Light off (0%) until motion activated
- Auto setting for dusk to dawn lighting\*
- Remote control allows brightness, lighting time and sensor mode settings
- Automatic night time operation
- Separate solar panel with 5m lead
- 120° Beam Angle
- IP65 Housing
- Weight: 5kg













## **Specification Overview**

Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Post Colour	Dimensions
SFL-M40	40w	Solar	6000K	4000lm	120°	Black	Light: 305 x 235 x 52mm

Panel: 530 x 350 x 18mm





## 40w Solar Motion Flood Light


4.0775m

6.1163m

8.1551m







Specification					
Mc	odel	SFL-M40			
Col	lour Temperature	6000K			
Lur	men (Im)	4000lm			
Eff	iciency (Im/w)	>100lm/w			
Lig	ht Source	LED			
CR	I (%)	≥80			
Bea	am Angle	120°			
Pov	wer Requirement	Solar Powered			
Bat	ttery	LifePO4, 6.4V 18AH			
Cha	arging Time	~8 Hours (from 0-100%)			
Ор	eration Time	Dusk to dawn* 3hrs 100% > 4hrs 50% > 5hrs 30%			
Но	using	Aluminium			
Rei	mote Control	2.4G (up-to 25m)			
Ser	nsor	Microwave (up-to 15m)			
Life	espan	>40,000 hours			
Ор	eration Temperature	-10°C~+40°C			
Pro	oduct Dimension (light)	305 x 235 x 52mm			
Pro	oduct Dimension (solar panel)	530 x 350 x 18mm			
We	eight	5kg			

Specifications are subject to change without notice



areas where lighting is required all night

195.43lx

86.86lx

48.86lx

Warranty

**Protection Rating** 

IP65

2 Years