

Product Specification



Outdoor Wall Light  
12w AURA Wall Wash



Product Features

- 12w
- Choice of 3000K or 5000K colour temperature
- Adjustable face section (340°) for different wall wash effect
- 110° Beam Angle
- Aluminium housing
- Choice of Black or White trim
- 140 x 140 x 48mm
- IP54 Housing
- IK08 Impact Rating
- Weight: 870g



Specification Overview



| Model         | Power | Input      | Colour Temp | Lumens | Beam Angle | Trim Colour | Dimensions   |
|---------------|-------|------------|-------------|--------|------------|-------------|--------------|
| WL-AURA12-R-B | 12w   | 220~240VAC | 3000K       | 600lm  | 110°       | Black       | 140X140X48mm |
| WL-AURA12-R-W | 12w   | 220~240VAC | 3000K       | 600lm  | 110°       | White       | 140X140X48mm |
| WL-AURA12-V-B | 12w   | 220~240VAC | 5000K       | 760lm  | 110°       | Black       | 140X140X48mm |
| WL-AURA12-V-W | 12w   | 220~240VAC | 5000K       | 760lm  | 110°       | White       | 140X140X48mm |

Outdoor Wall Light  
12w AURA Wall Wash

| Model         | Trim Colour | Power | Lumens    | CCT   | Dimension        | Weight |
|---------------|-------------|-------|-----------|-------|------------------|--------|
| WL-AURA12-R-B | Black       | 12w   | 600~760lm | 3000K | 140 x 140 x 48mm | 870g   |
| WL-AURA12-R-W | White       | 12w   | 600~760lm | 3000K | 140 x 140 x 48mm | 870g   |
| WL-AURA12-V-B | Black       | 12w   | 600~760lm | 5000K | 140 x 140 x 48mm | 870g   |
| WL-AURA12-V-W | White       | 12w   | 600~760lm | 5000K | 140 x 140 x 48mm | 870g   |

| Specification     |                |                       |                        | Dimensions |  |
|-------------------|----------------|-----------------------|------------------------|------------|--|
| CCT               | 3000K or 5000K | Housing               | Aluminium              |            |  |
| Efficacy          | >50lm/w        | Diffuser              | Polycarbonate          |            |  |
| CRI (%)           | ≥80            | Housing Colour        | Black or White options |            |  |
| Beam Angle        | 110°           | Lifespan              | >50,000 hours          |            |  |
| Power Input       | 220~240VAC     | Operation Temperature | -20 °C to +65°C        |            |  |
| Dimmable          | No             |                       |                        |            |  |
| Impact Rating     | IK08           |                       |                        |            |  |
| Protection Rating | IP54           | Warranty              | 3 Years                |            |  |



