


Product Features

- 10w/20w Watt Select
- 2 colour selectable Amber (Turtle Friendly/Bug Free*) and Green (Eye wash)
- 120° Beam Angle
- Aluminium die cast housing
- Ø275 x 80mm
- **IP65 Housing**
- **IK10 Impact Rating**
- Weight: 1.25kg









Grille Cover

















Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-BH20-TLG-B	10/20w	200~240VAC	Amber / Green	2000 ~ 2200lm	120°	Black	Ø275x80mm

Product Specification

Outdoor Wall Light

Turtle Safe / Bug Free / Eyewash



Switch to Excellence

Model	Trim Colour	Power	Lumens	ССТ	Dimension	Weight
WL-BH20-TLG-B	Black	10/20w	2000lm ~ 2200lm	Amber / Green	Ø275 x 80mm	1.25kg

Specification				Dimensions
ССТ	Amber / Green	Housing	Diecast aluminium	
Efficacy	>100lm/w	Diffuser	Polycarbonate	
CRI (%)	≥80	Housing Colour	Black	
Beam Angle	110°	Lifespan	>50,000 hours	
Power Input	220~240VAC	Operation Temperature	-25 °C to +45°C	0 0
Dimmable	No			80
Impact Rating	IK10			* Whilst our testing using an amber light source has found it will attract
Protection Rating	IP65			approximately 90% less bugs than alternate light sources, there is still a risk of some
		Warranty	5 Years	 bugs being attracted to our bug free lighting products.

Options



Eyelid Cover Model: WL-BH20-ELC-B



Microwave Sensor Add in sensor option Model: WL-BH-MMS2



Grille Cover Model: WL-BH20-GC-B



Photocell
Add in sensor option
Turns on at dusk and off
and dawn
Model: WL-BH-PE



Emergency Fitting Model: WL-BH20-TLG-B-E

Specifications are subject to change without notice



Product Specification

Outdoor Wall Light

Turtle Safe / Bug Free / Eyewash Emergency





Switch to Excellence

Model	Trim Colour	Power	Lumens	ССТ	Dimension	Weight
WL-BH20-TLG-B-E	Black	10/20w	2000lm ~ 2200lm	Amber / Green	Ø275 x 80mm	1.6kg

Specification				Dimensions	
ССТ	Amber / Green	Housing	Diecast aluminium		
Efficacy	>100lm/w	Diffuser	Polycarbonate		
CRI (%)	≥80	Housing Colour	Black		
Beam Angle	110°	Lifespan	>50,000 hours		
Power Input	220~240VAC	Operation Temperature	-25 °C to +45°C		
Dimmable	No	Emergency power	2w	80	
Impact Rating	IK10	Emergency Run-Time	180 minutes	* Whilst our testing using an amber light - source has found it will attract	
Protection Rating	IP65	Battery	LifePO4 6.4v 1500mAH	approximately 90% less bugs than alternate light sources, there is still a risk of	
		Warranty	5 Years 3 Years Battery	some bugs being attracted to our bug free lighting products.	

Options



Eyelid Cover Model: WL-BH20-ELC-B



Microwave Sensor Add in sensor option Model: WL-BH-MMS2



Grille Cover Model: WL-BH20-GC-B



Photocell
Add in sensor option
Turns on at dusk and off
and dawn
Model: WL-BH-PE



Standard Fitting Model: WL-BH20-TLG-B

Specifications are subject to change without notice

