



3w LED Star Lights

Product Features

- 3w
- Available in 3000K, 4000K or 5000K
- Choice of White or Brushed Chrome Trim
- 45° Beam Angle
- Ø42 x 37mm
- 30mm cut-out
- IP20 protection
- 1.9m Fig-8 cable and plug included
- Weight: 62g



Options:




STAR-PWR-2
Drives 1 – 2 lights
Non-Dimmable



STAR-PWR-6
Drives 3 – 6 lights
Dimmable



Specification Overview




Model	Power	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
STAR-0329CD-WHT	3w	5000K	300lm	45°	White	Ø42 x 37mm
STAR-0329ND-WHT	3w	4000K	290lm	45°	White	Ø42 x 37mm
STAR-0329WD-WHT	3w	3000K	270lm	45°	White	Ø42 x 37mm
STAR-0329CD-BC	3w	5000K	300lm	45°	Brushed Chrome	Ø42 x 37mm
STAR-0329ND-BC	3w	4000K	290lm	45°	Brushed Chrome	Ø42 x 37mm
STAR-0329WD-BC	3w	3000K	270lm	45°	Brushed Chrome	Ø42 x 37mm

Product Specification



3w LED Star Lights



Star light drivers are sold separately

Please select the correct driver as follows to suit your requirements.

Note: All ports must be filled in the junction box with either a light or supplied jumper. The STAR-PWR-6 driver will only correctly operate with at least 3 star lights attached to the junction box.

Options:



STAR-PWR-2
Drives 1 – 2 lights
Non-Dimmable



STAR-PWR-6
Drives 3 – 6 lights
Dimmable



Specification

Model	STAR-0329WD-BC STAR-0329WD-WHT	STAR-0329ND-BC STAR-0329ND-WHT	STAR-0329CD-BC STAR-0329CD-WHT
Colour Temperature (1CCT)	3000K	4000K	5000K
Lumen (lm)	270lm	290lm	300lm
Efficiency (lm/w)	>90 lm/w	>96 lm/w	>100 lm/w
Light Source	LED		
CRI (%)	≥80		
Beam Angle	45°		
Power Requirement	220~240VAC with optional driver		
Power Consumption	3w		
Dimmable	Yes, Triac dimmable with PWR-6 Driver		
Housing	Aluminium		
Trim Colour	Brushed Chrome (BC) or White (WHT)		
Lifespan	>50,000 hours		
Operation Temperature	-20°C~+45°C		
Product Dimension	Ø42 x 37mm		
Cut-Out	30mm		
Weight	62g		
Protection Rating	IP20		
Warranty	5 Years		

Specifications are subject to change without notice