

## 100w LED Canopy Light (Small)

## **Product Features**

- 100w
- CCT: 5000K
- Large range input 180~295VAC
- Easy connect junction box on rear with large terminal block
- Aluminium die cast housing
- Opal Polycarbonate Lens
- 120° Beam Angle
- 455 x 455 x 110mm
- IP65 Housing
- Weight:6kg











## **Specification Overview**

Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SCL-100W-VS	100w	180~295VAC	5000K	8882lm	120°	White	455x455x110mm





## 100w LED Canopy Light (Small)



	1
	7

F	Flux out:6340 lm		
	BIO. N.Y. O. D. BOOK OF THE STATE OF THE STA	Λ	
		$\triangle$	
	672.7,27401x	/ \	341.98cm
	168.2,685.01x		683.95cm
	74.74,304.41x	+	1025.93cm
	42.04,171.31x		1367.91cm
	42.04,171.31X	/	1367.91Cm
l	26.91,109.61x		1709.88cm
	18.69,76.111x	1	2051.86cm
	13.73,55.921x		2393.84cm
	10.51,42.811x		2735.81cm
	8.305,33.831x		3077.79cm
			1
	6.727,27.401x		3419.77cm

Specification	
Model	SCL-100W-VS
Colour Temperature (1CCT)	5000K
Lumen (Im)	8882lm
Efficiency (lm/w)	>89lm/w
Light Source	LED
CRI (%)	≥80
Beam Angle	120°
Power Requirement	180~295VAC
Power Consumption	98.79w
Dimmable	No
Housing	Diecast aluminium with PC Lens
Lifespan	>40,000 hours
Operation Temperature	-20°C~+80°C
Product Dimension	455 x 455 x 110mm
Impact Rating	IK10
Weight	6kg
Protection Rating	IP65
Warranty	5 Years
Spe	ecifications are subject to change without notice

Specifications are subject to change without notice

