






Please read these instructions carefully in full prior to carrying out the installation.

IMPORTANT SAFETY ISSUES

- This product must be installed by a qualified electrician according to AS/NZS 3000.
- Ensure that the AC power is disconnected at the switchboard and test to ensure that there is no power on the circuit prior to starting installation.
- This product is rated to IP44 (front) and is not suitable for damp environments.
- Modification of this product will void any warranty.
- When cleaning or replacing the light, please ensure the power is off and the light is completely cooled down. Cleaning can be done using a soft cloth and PH neutral detergent.

INSTALLATION INSTRUCTIONS

<p>warning:</p> <p>Turn off and isolate the electrical supply before connecting this fitting to the building wires. Must be installed or connected by licenced electrician This product is indoor use only</p>	<p>Step 1: Slide the end caps and remove the LED diffuser from the base housing</p> 
<p>Step 2: Mount the fitting onto ceiling with screws (surface mounted)</p> 	<p>Step 2: Secure the mounting bracket to the steel cable (suspended mounted)</p> 
<p>Step 3: Wire the cable in to the terminal block through the cable entry hole, and insert connector between the base and diffuser Assemble the diffuser back to the base and also the two caps</p> 	<p>Step 5: Turn on the power supply to ensure the luminaire is working properly.</p> 

Note: This product is colour switching, please remember to select the correct colour prior to the final assembly of the light. WW: 3000K, NW: 4000K, CW: 5000K

SMD-4FT-40-3C-MR - Refer to remote control packaging for the microwave sensor settings