



200w V19E Slimline LED Flood Light

Product Features

- 200w
- Quality Driver
- Full range power input 90~305VAC
- Aluminium die cast housing
- Tempered glass face
- 120° Beam Angle
- 445 x 392 x 56mm
- IP66 Housing
- Weight: 5.4kg




Specification Overview

Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
FLA-SC200W-V19E	200w	90~305VAC	5000K	23,676lm	120°	Black	445x392x56mm


Product Specification



200w V19E Slimline LED Flood Light



Specification	
Model	FLA-SC200W-V19E
Colour Temperature (1CCT)	5000K
Lumen (lm)	23,676lm
Efficiency (lm/w)	>118lm/w
Light Source	LED
CRI (%)	≥80
Beam Angle	120°
Power Requirement	90~305VAC
Power Consumption	199.2w
Dimmable	No
Housing	Diecast aluminium with toughened glass lens
Lifespan	>50,000 hours
Operation Temperature	-20°C~+45°C
Product Dimension	445 x 392 x 56mm
Impact Rating	IK08
Weight	5.4kg
Protection Rating	IP66
Warranty	5 Years



Specifications are subject to change without notice