



## 500w V19E Slimline LED Flood Light

### Product Features

- 500w
- Quality Driver
- Full range power input 90~305VAC
- Aluminium die cast housing
- Tempered glass face
- 60° Round Beam Angle or 150x80° asymmetric (forward throw) Beam Angle available
- 672 x 534 x 188mm
- IP66 Housing
- Weight: 15kg



Options:



Cut-off Hood



### Specification Overview



Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
FLA-SC500W-RV	500w	90~305VAC	5000K	55,931lm	60°	Black	672x534x188mm
FLA-SC500W-AV	500w	90~305VAC	5000K	56,109lm	150°x80°	Black	672x534x188mm

# Product Specification




## 500w V19E Slimline LED Flood Light




Image shown with fitted with optional cut-off hood fitted (Model: FLA-SC500-CH)

### Lens Options:

Round Beam



Asymmetric Forward Throw



### 60° Round Beam

1m	32727,547741x	106,94cm
2m	8182,136931x	213,89cm
3m	3636,60861x	320,83cm
4m	2045,34231x	427,77cm
5m	1309,21911x	534,72cm
6m	909,1,15211x	641,66cm
7m	667,9,11181x	748,60cm
8m	511,4,855,81x	855,55cm
9m	404,0,676,21x	962,49cm
10m	327,3,547,71x	1069,43cm

Height      Eavg, Emax      Angle: 56.27deg      Diameter

### Specification

Model	FLA-SC500W-RV	FLA-SC500W-AV
Colour Temperature (1CCT)	5000K	
Lumen (lm)	56,109lm	55,931lm
Efficiency (lm/w)	>123lm/w	
Light Source	LED	
CRI (%)	≥80	
Beam Angle	60°	150x80°
Power Requirement	90~305VAC	
Power Consumption	453.7w	
Dimmable	No	
Housing	Diecast aluminium with toughened glass lens	
Lifespan	>50,000 hours	
Operation Temperature	-20°C~+60°C	
Product Dimension	672 x 534 x 188mm	
Impact Rating	IK08	
Weight	15kg	
Protection Rating	IP66	
Warranty	5 Years	

Specifications are subject to change without notice