

150w LED Canopy Light (Small)

Product Features

- 150w
- CCT: 5000K
- Large range input 180~295VAC
- Easy connect junction box on rear with large terminal block
- Aluminium die cast housing
- Opal Polycarbonate Lens
- 120° Beam Angle
- 455 x 455 x 110mm
- IP65 Housing
- Weight:6.1kg











Specification Overview

Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SCL-150W-VSS	150w	180~295VAC	5000K	13350lm	120°	White	455x455x110mm



150w LED Canopy Light (Small)



	F = 1	Fol 1	. 1	
		1-10	F I	
T			1	
		100	M I	
			H	1
0	,	1 1.1	. 1	-
		3		

		\
1m	1129,46041x	338.31cm
2m	282.2,11511x	676.62cm
3m	125.4,511.61x	1014.92cm
4m	70.54,287.81x	1353.23cm
5m	45.15,184.21x	1691.54cm
6m	31.35,127.91x	2029.85cm
7m	23.03,93.961x	2368.16cm
8m	17.63,71.941x	2706.46cm
9m	13.93,56.841x	3044.77cm
Om	11.29,46.041x	3383.08cm

Specification	
Model	SCL-150W-VSS
Colour Temperature (1CCT)	5000K
Lumen (lm)	13350lm
Efficiency (lm/w)	>89lm/w
Light Source	LED
CRI (%)	≥80
Beam Angle	120°
Power Requirement	180~295VAC
Power Consumption	150w
Dimmable	No
Housing	Diecast aluminium with PC Lens
Lifespan	>40,000 hours
Operation Temperature	-20°C~+80°C
Product Dimension	455 x 455 x 110mm
Impact Rating	IK10
Weight	6.1kg
Protection Rating	IP65
Warranty	5 Years
Spe	ecifications are subject to change without notice

Specifications are subject to change without notice

