



100w ECO-FL LED Flood Light

Product Features

- 100w
- 3 colours in one: 3000K, 4000K, 5000K (switch select)
- Full range power input 100~240VAC
- Aluminium die cast housing
- Tempered glass face
- 120° Beam Angle
- 347 x 300 x 68mm
- IP65 Housing
- Weight:3kg



3 Colour Adjustable



Specification Overview

Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
ECO-FL-100W	100w	100~240VAC	3000-4000-5000K	8640~9000 lm	120°	Black	347x300x68mm

Product Specification



100w ECO-FL LED Flood Light

Specification

Model	ECO-FL-100W
Colour Temperature (3CCT)	3000K / 4000K / 5000K
Lumen (lm)	8640 ~ 9000lm
Efficiency (lm/w)	>90lm/w
Light Source	LED
CRI (%)	≥80
Beam Angle	120°
Power Requirement	100~240VAC
Power Consumption	100w
Dimmable	No
Housing	Diecast aluminium with toughened glass lens
Lifespan	>40,000 hours
Operation Temperature	-20°C~+45°C
Product Dimension	347 x 300 x 68mm
Impact Rating	IK08
Weight	3kg
Protection Rating	IP65
Warranty	3 Years

Specifications are subject to change without notice