


150w ECO-HB UFO LED High Bay Light

Product Features

- 150w
- Quality 0-10V Dimmable Driver
- Full range power input 100~305VAC
- Aluminium die cast housing
- Polycarbonate Lens
- 120° Beam Angle
- Supplied with 1.8m flex and plug
- Ø320 x 210mm
- IP65 Housing
- Weight: 4.4kg














Specification Overview

Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
FCO-HB150W-V	150w	100~305VAC	5000K	22 544lm	120°	Black	Ø320x210mm





150w ECO-HB UFO LED High Bay Light



Accessory options



Merrytek Microwave Motion Sensor Kit Model: FLA-SHV18S-1-MMS



Bracket for floodlight or low bay fitting Model: FLA-SHV18S-1-FB

	iliuminano	ce-Distance Curve		
1.0	8120.34		4264.258	2.572
2.0	2030.09		1066.064	5.144
3.0	902.26		473.806	7.716
ight (n)	Center E(1x)	Average: 104.3	ge E(lx)	Diameter(m

Specification				
Model	ECO-HB150W-V			
Colour Temperature (1CCT)	5000K			
Lumen (lm)	22,544lm			
Efficiency (Im/w)	>150lm/w			
Light Source	LED			
CRI (%)	≥80			
Beam Angle	120°			
Power Requirement	100~305VAC			
Power Consumption	149.40w			
Dimmable	Yes, 0-10V			
Housing	Diecast aluminium with Polycarbonate lens cover			
Lifespan	>50,000 hours			
Operation Temperature	-40°C~+50°C			
Product Dimension	Ø320 x 210mm			
Impact Rating	IK08			
Weight	4.4kg			
Protection Rating	IP65			
Warranty	5 Years			

Specifications are subject to change without notice

