

10w LED Panel Down Light with Motion Sensor

Product Features

- 10w
- 3 colours in one: 3000K, 4000K, 5000K (switch select)
- PIR Sensor
- Built in light sensor so light will only activate when it is dark
- Ø115 x 73mm
- 90mm cut-out
- 0.6m Flex cable and plug included
- Weight: 200g

the form the

Specification Overview

3 Colour Adjustable

| Model | Power | Power Requirement | Colour Temp | Lumens | Beam Angle | Trim Colour | Dimensions |
|-------------|-------|----------------------|-----------------|-----------|---------------|-------------|-------------|
| RDL-1090-MS | 10w | 220~240VAC | 3000-4000-5000K | 760~880lm | 100° | White | Ø115 x 73mm |




www.s-tech.com.au

08 9330 8485

S-Tech Holdings Pty Ltd 12 Mordaunt Circuit, Canning Vale WA 6155



10w LED Panel Down Light with Motion Sensor



| Sensor Specification | | | | | |
|------------------------|-----------------------|--|--|--|--|
| Sensor Distance | ≥ 5m / 25° (front) | | | | |
| Light On Time | 30 Sec (±5S) | | | | |
| Light Sensor ON/OFF | 8-20 Lux | | | | |

Options:



| ec (±55) | Housing |
|----------|----------------|
|) Lux | Lifespan |
| | Operation Ten |
| | Product Dime |
| Trim | Cut-Out |
| RIM-BLK | Weight |
| | Protection Rat |

Warrar

Specification Model **RDL-1090-MS Colour Temperature** 3CCT: 3000K / 4000K / 5000K Lumen (Im) 760~880lm Efficiency (Im/w) >76 lm/w **Light Source** LED CRI (%) ≥80 **Beam Angle** 100° **Power Requirement** 220~240VAC **Power Consumption** 10w Dimmable No Plastic coated aluminium >40,000 hours -20°C~+45°C nperature nsion Ø115 x 73mm 90mm 200g **IP40** Rating 3 Years Warranty

Specifications are subject to change without notice



www.s-tech.com.au

08 9330 8485