

LED Lighting Catalogue



-tech
LED Lighting

Switch to Excellence

About Us



S-Tech Lighting is one of Australia's leading innovators in LED lighting and LED Technology, with a reputation built on quality, reliability, and over 25 years of industry expertise.

Founded in Western Australia, S-Tech has grown from a specialist local manufacturer into a national presence with offices now in Adelaide, Sydney, Melbourne, and our Head Office in Perth. This expansion enables us to deliver industry-leading products and service across the country, while continuing to support projects worldwide.

Our team has played an active role in shaping LED technology standards in Australia, with management contributing to Australian Standards Committees and driving the adoption of energy-efficient lighting across multiple sectors. Since 2000, we have been designing, manufacturing, and supplying advanced LED lighting systems to meet the demanding requirements of industries such as mining, commercial, residential, and public infrastructure.

S-Tech products are Australian designed, tested, and certified to meet both local and international electrical safety standards. By partnering with world-class component manufacturers and investing heavily in research and development, we ensure our customers receive products that combine cutting-edge LED chip technology with superior thermal management for unmatched performance and longevity.

Today, S-Tech offers a portfolio of over 600 product lines and growing, from:

- Commercial high bays, flood lights, and streetlights
- Residential downlights
- Solar-powered lighting
- Specialised mining and safety lighting

Our products are trusted across Australia and installed globally through our international agent network in Canada, India, Indonesia, Philippines, Singapore, UK, and Europe.

As the LED lighting industry continues to evolve, S-Tech remains committed to delivering energy-efficient, sustainable, and future-ready solutions that help businesses and households reduce energy consumption while enjoying high-quality illumination built to last 50,000+ hours.

With a proven track record, national reach, and global outlook, S-Tech Lighting is your partner for smarter, greener lighting.

Contents

Products	Page
Product Index	4
S-Wear Range – Clothing and Accessories	6
S-Trade Range – Plug bases and Tools	10
Sensors	14
Torches and Headlamps	21
Dimmers	24
Wireless Switches and Receivers	29
Cabinet and Strip Lighting	37
Downlights	41
Surface Mount Downlights	57
Indoor Wall Lights	60
Oyster Lights	63
Deck and Garden Lights	66
Outdoor Wall Lights	69
Outdoor Wall Pack Lights	93
Bollard Lights	100
S-Exit Signs and Emergency Lights	105
Shop Lights	113
T-Bar Panel Lights	116
T-Bar Panel Accessories	121
Linear Lights	130
Batten Lights	134
High Bay Lights	150
Flood Lights	159
Canopy Lights	174
Streetlights	177
Street and Park Lanterns	181
Solar Powered Lights	188
Poles and Accessories	207

**Product
Index**
S-Wear**S-Trade****Sensors****Torches and
Headlamps****Dimmers**

6

**Wireless
Switches**

10

Cabinet Lights

14

Downlights

21

**Surface Mount
Downlights**

24

**Indoor Wall
Lights**

29

Oyster Lights

37

**Garden and
Deck Lights**

41

**Outdoor Wall
Lights**

57

**Outdoor Wall
Pack Lights**

60

Bollard Lights

63

**Exit and
Emergency**

66

Shop Lights

69

**T-Bar Panel
Lights**

93

**T-Bar Panel
Accessories**

100

Linear Lights

105



113



116



121



130

**Product
Index**
Indoor Battens**Weatherproof
Battens****High Bay Lights****Floodlights****Specialised
Floodlights**

134



142



150



159



165

**Sports
Floodlights****Canopy Lights****Streetlights****Street Lanterns****Solar Powered
Lighting**

170



174



177



181



188

**Poles and
Accessories**

207

S-WEAR RANGE





Hi-Vis Singlet

SW-HVSS

Sizes: M, L, XL, XXL



Hi-Vis T-Shirts

Plain: SW-HVTP

With Black Stripes SW-HVTS

Sizes: M, L, XL, XXL



Hi-Vis Polo

Plain: SW-HVPS

With Black Stripes SW-HVTS

Sizes: M, L, XL, XXL



Hi-Vis Fleece Hoody

Plain: SW-HVH

Sizes: M, L, XL, XXL

Model	Style	Available Sizes
SW-HVSS	Hi-Vis Singlet with Black Side Panels	M, L, XL, XXL
SW-HVTP	Hi-Vis T-Shirt – Plain	M, L, XL, XXL
SW-HVTS	Hi-Vis T-Shirt with Black Side Panels	M, L, XL, XXL
SW-HVPS	Hi-Vis Polo Shirt with Black Side Panels	M, L, XL, XXL
SW-HVH	Hi-Vis Fleece Hoody	M, L, XL, XXL



Travel Mug

- 360ml
- Anti-Spill Lid
- Keep your coffee hot in the morning



Guzzler Drink Bottles

- 1000ml
- Supplied with both Straw and Guzze Caps
- Dual Sidewalls to keep your drink of choice icy cold
- Available in Black, White or Turquoise Blue



Model	Type	Capacity	Colour
SW-TM-B	Travel Mug	360ml	Black
SW-WB-1L-B	Guzzler Drink Bottle	1000ml	Black
SW-WB-1L-TB	Guzzler Drink Bottle	1000ml	Turquoise Blue
SW-WB-1L-W	Guzzler Drink Bottle	1000ml	White



Straw Surf Hat

The S-wear straw surf hat is broad rimmed to keep the sun off you, whether you are at the beach with the family or working in the sun, it's got you covered.



Backpack / Laptop Bag

The S-wear Backpack is built tough! Complete with 3 zipped sections, 2 side pockets and a padded laptop section internally it's ready to hit the road with you



Model	Type
SW-HAT-STRAW	Broad Rim Straw Surf Hat
SW-BP	Backpack / Laptop Bag





Product Features

- Rechargeable
- 6.35mm quick release chuck
- Forward, reverse and manual modes
- Dual front LED work lights
- Non-slip rubber grip
- Supplied with USB charging cable and PH2 Phillips bit


 Dual front
LED work lights


USB charge port


 USB cable and
PH2 Phillips bit included



Technical Specification

Model	Battery	Speed (no load)	Torque	Charging Time	Operation Time	USB Charging Input	Dimensions	Body Colour
ST-RSD	3.6v li-ion	2800RPM	1.5 N.m (electric) 10 N.m (manual)	~60 mins	~200 mins	USB Micro B (≤5v 1A)	Ø37.8mm x 154mm	Black

Plug Base
 Surface Mount Socket

Product Features

- Easy snap off tabs to allow the socket to fit in a Ø70mm cut-out
- Australian approved 3-pin, 10A 250V socket
- Transparent base plate
- Multiple fixing points
- Screw heads allow Flat or Phillips head screwdrivers to be used
- Pack Size: 10pcs
- Carton Size: 200pcs


Technical Specification

Model	Type	Input	Material	Dimensions	Body Colour
ST-SMS2	S-trade Surface Mount Socket – 10A	250VAC, 10A	Polycarbonate	Ø65.2mm x 54.7mm	White




E-trade

S-tech
LED Lighting

Plug Base
Rapid Connect Socket

VIPER



Product Features

- No need to remove the outer insulation
- Insulation-Displacement Connector Technology
- Suitable for 1.5mm² and 2.5mm² Multi-Strand Flat Cables
- Rating: 250VAC / 10A
- Transparent Base plate
- Fits through in a 70mm cut-out
- Rating: 250VAC / 10A
- Pack Size: 10pcs
- Carton Size: 200pcs



Specification Overview



Model	Type	Input	Material	Dimensions	Body Colour
ST-RCS	S-trade VIPER Rapid Connect Socket - 10A	240VAC, 10A	Polycarbonate	70 x 44 x 30mm	White



SENSORS

AuraGuard
 Sensor Series


Model	SEN-IRID16	SEN-IROD12	SEN-IROD182	SEN-IROD183
IP Rating	IP44	IP65	IP66	IP66
Max. Load (LED & CFL)	1000w	300w	500w	1000w
Max. Load (Incandescent)	2000w	1200w	1000w	2000w
Detection Distance	6 ~ 16m	12m	6 ~ 18m	6 ~ 18m
Time Delay	10s ~ 30mins	10s ~ 15mins	10s ~ 30mins	10s ~ 30mins
Light Sensor	2 ~ 2000lux	3 ~ 2000lux	3 ~ 2000lux	3 ~ 2000lux
Manual Override	✓	✗	✗	✓
Adjustable Time Delay	✓	✓	✓	✓
Adjustable Light Sensor	✓	✓	✓	✓
Adjustable Sensitivity	✓	✗	✓	✓
2-Wire Connection	✗	✗	✓	✗
3-Wire Connection	✓	✓	✓	✓
Warranty	5 Years	5 Years	5 Years	5 Years

Indoor PIR Sensor
AuraGuard 16


Product Features



- Surface or Recessed Mount
- Manual Override
- Sensor Shield Included
- Adjustable Time Delay, Lux and Sensitivity settings



Specification

Dimensions

Model	SEN-IRID16
Sensor Type	PIR
Maximum Load	1000w (LED, CFL), 2000w (Incandescent)
Installation Height	2.2m~4m
Detection Distance	6m~16m
Detection Angle	360°
Time Delay	10s ~ 30mins
Light Sensor	2~2000lux
Power Requirement	220~240VAC
Housing	Polycarbonate
Product Dimension	Ø106mm x 61mm (Surface Mount) Ø106mm x 58.5mm (Recessed)
Weight	204g
Protection Rating	IP44
Warranty	5 Years



Outdoor PIR Sensor
AuraGuard 12



Product Features

- IP65 Weatherproof
- No Manual Override
- Adjustable Time Delay and Lux settings



5627

Specification	Dimensions
Model	SEN-IROD12
Sensor Type	PIR
Maximum Load	300w (LED, CFL), 1200w (Incandescent)
Installation Height	1.8m~2.5m
Detection Distance	12m
Detection Angle	180°
Time Delay	10s ~ 15mins
Light Sensor	3~2000lux
Power Requirement	220~240VAC
Housing	Polycarbonate
Product Dimension	119.5 x 80 x 51.5mm
Weight	158g
Protection Rating	IP65
Warranty	5 Years



Ourdoor PIR Sensor

AuraGuard 182



Product Features

2
 WIRE


- IP66 Weatherproof
- 2-Wire or 3-Wire connection
- No Manual Override
- Adjustable Time Delay, Lux and Sensitivity settings

Specification
Dimensions

Model	SEN-IROD182
Sensor Type	PIR
Maximum Load	500w (LED, CFL), 1000w (Incandescent)
Installation Height	1.8m~2.5m
Detection Distance	6~18m
Detection Angle	180°
Time Delay	10s ~ 30mins
Light Sensor	3~2000lux
Power Requirement	220~240VAC
Housing	Polycarbonate
Product Dimension	135 x 73 x 115mm
Weight	204g
Protection Rating	IP66
Warranty	5 Years



Outdoor PIR Sensor
AuraGuard 183


Product Features

- IP66 Weatherproof
- 3-Wire connection
- Manual Override
- Adjustable Time Delay, Lux and Sensitivity settings




5627

Specification

Dimensions

Model	SEN-IROD183
Sensor Type	PIR
Maximum Load	1000w (LED, CFL), 2000w (Incandescent)
Installation Height	1.8m~2.5m
Detection Distance	6~18m
Detection Angle	180°
Time Delay	10s ~ 30mins
Light Sensor	3~2000lux
Power Requirement	220~240VAC
Housing	Polycarbonate
Product Dimension	135 x 73 x 115mm
Weight	204g
Protection Rating	IP66
Warranty	5 Years



Sunset Switch

Programmable



Product Features




- IP66 Weatherproof
- Adjustable Time Delay and Lux settings
- Multiple Conduit Entries



Specification

Dimensions

Model	SEN-SUNSW
Sensor Type	Photo Electric
Maximum Load	16A
Time Delay Settings	1, 2, 3, 4, 5, 6, 7, 8, 9 Hours or Dusk to Dawn
Light Sensor	3~500lux
Power Requirement	220~240VAC
Housing	Polycarbonate
Product Dimension	82 x 82.4 x 55.5mm
Weight	200g
Protection Rating	IP66
Warranty	5 Years



HEADLAMPS AND TORCHES



Torch Light Series


Product Features

- Adjustable Headlamp
- Multifunction Headlamp
- Inspection Light
- Multifunctional Flashlight
- Weatherproof Dive Torch



Specification Overview



Model	Type	Lumen	Run Time	Charge Time	Modes	Rating	Weight	Dimensions
THL-02	Headlamp	200lm	4H	1H	High-Low-Strobe-SOS-Red strobe	IP44	50g	65x32x39mm
THL-07	Headlamp	700lm	4H-6H	2.5H	STRIP: High-Low SPOT: High-Low	IPX4	70g	300x33x20mm
THL-08	Torch/ Headlamp	800lm	3H	2H	STRIP: High-Red-Red Strobe SPOT: High-Low	IP42	104g	140x21x21mm
THL-40	Torch	4000lm	7H	8H	FRONT: Low-Med-High-Strobe TAIL: Low	IP34	400g	Ø52x140mm
THL-15-IP68	Torch (Dive)	1500lm	2H	1.5H	Single Light Mode	IP68	212g	151x26x37mm

Premium Headlamp

3,800lm



Product Features

- 3,800lm
- Beam Zoom
- ABS and aluminium construction
- Type C charging port
- Presented in a protective box
- Weight: 240g



Specification Overview

Model	Type	Lumen	Run Time	Charge Time	Modes	Rating	Weight	Dimensions
THL-38	Premium Headlamp	3800lm	9H*	5H	Low-Med-High-Strobe	IP44	240g	Lamp: Ø45x69mm Package: 190x154x112mm

* Run-Time is based on strobe setting



5627

DIMMERS



Dimmer Series
Rotary Dimmer Switch



Product Features

- Rotary Dimmer with push ON/OFF
- Soft Start
- Fits most standard wall plates (excludes Clipsal Iconic)
- No Neutral Required
- Load: Min 5w / Max 350w
- Adjustable Min/Max dimming levels
- Multi-way switching compatible
- Refer to below for dimmer configuration

Options:


Black Knob

Load Correction Device

Single-way and Multi-way switching diagram	Function	Setup
	Disable Push Button	Short press the dimmer rotary knob 7 times
	Enable Push Button (default)	Short press the dimmer rotary knob 5 times
	Brightness adjustment – Minimum	Use the left hand adjusting trim pot on the body of the dimmer to adjust the desired minimum brightness level
	Brightness adjustment – Maximum	Use the right hand adjusting trim pot on the body of the dimmer to adjust the desired maximum brightness level





Specification Overview

Model	Type	Dimming Mode	Size	Max Load	Min Load	Comments
DIM-R	Rotary	Trailing Edge	56.1 x 23 x 23.1mm	350w	5w	<u>Not</u> suitable for multi-way dimming
DIM-R-BK		Matt Black Knob to suit DIM-R Dimmer				
DIM-LCD		Load Correction Device				Used to reduce dimming issues/flickering

Dimmer Series
Multi-Way Dimmer Switch


Product Features

- Multi-Function dimmer
- Available in Rotary or Push Button
- Suitable for multi-way dimming
- Dimmer with push ON/OFF switch
- Soft Start
- Fits most standard wall plates (excludes Clipsal Iconic)
- No Neutral Required
- Load: Min 5w / Max 300w
- Numerous programmable features (refer to following page)

Options:



Specification Overview

Model	Type	Dimming Mode	Size	Max Load	Min Load	Comments
DIM-MW-R	Rotary	Trailing Edge	54.9 x 23.5 x 23.5mm	300w	5w	<u>Allows</u> for multi-way dimming
DIM-MW-P	Push	Trailing Edge	43.5 x 23.5 x 23.5mm	300w	5w	<u>Allows</u> for multi-way dimming
DIM-MW-R-BK	Matt Black Knob to suit DIM-MW-R Dimmer					
DIM-LCD	Load Correction Device					Used to reduce dimming issues/flickering

Dimmer Series
SMART WiFi Dimmer Switch


Product Features

- Both manual and Wi-Fi Controlled dimmer
- Available in Rotary or Push Button
- Dimmer with push ON/OFF switch
- S-mart lighting control powered by TUYA
- Works with 2.4GHz enabled Wi-Fi router
- Compatible with Alexa and Google Home
- Soft Start
- Fits most standard wall plates (excludes Clipsal Iconic)
- No Neutral Required
- Load: Min 5w / Max 250w
- Programmable Min/Max dimming levels



Specification Overview

Model	Type	Dimming Mode	Size	Max Load	Min Load	Comments
DIM-SMART-R	Rotary	Trailing Edge	59.1 x 22.5 x 40mm	250w	5w	Wi-Fi and wall-controlled dimming
DIM-SMART-P	Push	Trailing Edge	47.2 x 22.5 x 40mm	250w	5w	Wi-Fi and wall-controlled dimming
DIM-SMART-R-BK	Matt Black Knob to suit DIM-SMART-R Dimmer					
DIM-LCD	Load Correction Device					Used to reduce dimming issues/flickering

Dimmer Series
Rotary Dimmer Switch


Product Features

- The load correction device (L.C.D) is used together with a dimmer to solve several issues related with LED lighting
- The L.C.D can in most cases solve problems such as glowing lights, flicker and can even reduce minimum dimming levels
- Maximum Power Consumption: 1w



Specification Overview

Model	Type	Size	Max Load	Comments
DIM-LCD	Load Correction Device	46 x 186 x 11.5mm	1w	Used to reduce dimming issues / flickering

WIRELESS KINETIC SWITCH

Wireless Kinetic Switch
Aussie Mech Wall Switch

 Regd. Australian Design
 Patent: 202513715

Product Features

- Wireless Push Button
- NO power or batteries required
- Fits most standard wall plates (excludes Clipsal Iconic)
- Add a switch anywhere (no chasing walls, no cabling required)
- Pair Multiple Switches with the one receiver for multi-way switching and dimming
- Works together with the S-Tech range of Kinetic Wireless Receivers
- Range: ≤30m Indoor, ≤80m Outdoor



Specification Overview

Model	Type	Dimensions	Comments
KIN-SW-AU	Aussie Mech Wall Switch	45 x 23 x 23mm	Fits most standard wall plates (excludes Clipsal Iconic)

Wireless Kinetic Switch
Wall Switch


Product Features

- Wireless Push Button
- NO power or batteries required
- Add a switch anywhere (no chasing walls, no cabling required)
- Mount the switch wherever you want
- Can be screwed or attached to the wall with double sided tape
- Pair Multiple Switches with the one receiver for multi-way switching
- Dimming available in the Wide Model only
- Works together with the S-Tech range of Kinetic Wireless Receivers or Doorbell
- Range: ≤30m Indoor, ≤80m Outdoor

Narrow Wall Switch

- Join multiple switches together to create additional switches in one bank
- Not suitable for dimming

Wide Wall Switch

- Suitable for dimming



Specification Overview



Model	Type	Dimensions	Comments
KIN-SW-N-W	Narrow Wall Switch – 1 Gang	86 x 29 x 16mm	Mount anywhere, not suitable for dimming
KIN-SW-W-W	Wide Wall Switch – 1 Gang	86 x 86 x 16mm	Mount anywhere, suitable for dimming

Wireless Kinetic Switch
Key Fob Switch


Product Features

- Wireless Key Fob
- NO power or batteries required
- Pair Multiple Switches or Key Fobs with the one receiver for multi-way switching
- Not suitable for Dimming
- Works together with the S-Tech range of Kinetic Wireless Receivers
- Range: ≤30m Indoor, ≤80m Outdoor



Specification Overview



Model	Type	Dimensions	Comments
KIN-SW-K1-B	Key Fob Switch – 1 Gang	48 x 21 x 18mm	Not suitable for dimming

Wireless Kinetic Switch
Receiver Options


Product Features

- Dimming and Non-Dimming options
- Works with the S-Tech Range of Wireless Switches and Key Fobs
- Wi-Fi Control (powered by Tuya)
- Works with a 2.4GHz enabled Wi-Fi Router
- Compatible with Google Home and Alexa
- NO power or batteries required
- Pair Multiple Switches with the one receiver for multi-way switching and dimming
- Pair one switch with up-to 5 receivers for combined switching or dimming of circuits
- Range: ≤30m Indoor, ≤80m Outdoor



Standard – 1 or 2 Channel

- Turns circuits ON/OFF, Multiple uses, not only for lighting

Dimmable – 1 Channel

- Suitable for dimming, Dims most triac dimmable lights

Contact Relay – 1 Channel

- Provides latched volt free closed contact for 2 seconds
- Ideal for garage doors, gates, door access, commercial doorbells or remote switching of devices

Specification Overview




Model	Type	Dimensions	Comments
KIN-R1-STD	Standard Receiver – 1 Channel	82 x 52 x 24mm	Max Load: 1000w, Not suitable for dimming.
KIN-R2-STD	Standard Receiver – 2 Channel	82 x 52 x 24mm	Max Load: 1000w/channel, Not suitable for dimming.
KIN-R1-DIM	Dimmable Receiver – 1 Channel	82 x 52 x 24mm	Max Load: 1000w, Suitable for dimming
KIN-R1-CR	Contact Relay (2 sec) – 1 Channel	82 x 52 x 24mm	Max Load: 5A

Wireless Kinetic Switch
Smart Socket


Product Features

- Plugs into your wall socket allowing you to control devices connected to the Wireless Smart Socket using the S-Tech Range of Wireless Switches and Key Fobs
- Ideal for table lamps, remote switching of devices, or anywhere you want to be able to turn on/off devices wirelessly
- Wi-Fi Control (powered by Tuya)
- Works with a 2.4GHz enabled Wi-Fi Router
- Compatible with Google Home and Alexa
- Pair Multiple Switches with the one receiver for multi-way switching and dimming
- Pair one switch with up-to 5 receivers for combined switching or dimming of circuits
- Range: ≤30m Indoor, ≤80m Outdoor

Options:



Wireless Kinetic Switch or Key Fob



Specification Overview

Model	Type	Dimensions	Comments
KIN-R-SOC	Wireless Smart Socket	50 x 50 x 38mm	Max Load: 1000w, Not suitable for dimming.



Wireless Kinetic Switch

3-in-1 Bathroom Switch



Product Features

- Bathroom Kit for Light, Fan and Heat switching
- Simple solution when only 1 cable was chased in the wall for the light switch in the bathroom
- NO power or batteries required for the switch
- Add a switch anywhere (no chasing walls, no cabling required)
- Mount the switch wherever you want, can be screwed or attached to the wall with double sided tape
- Supplied with 2 x Wireless Receivers and 1 Wireless 3 Gang Wall Switch
- This product is not suitable for dimming
- Range: ≤30m Indoor, ≤80m Outdoor



Specification Overview



Model	Type	Dimensions	Rating
KIN-LFH-KIT	Bathroom Kit – 2 x Receivers and 1 x 3-Gang Wall Switch	Switch: 86 x 86 x 16mm Receivers: 82 x 52 x 24mm	Receiver (Light) – 300w LED Receiver (Fan/Heat) – 1500w Resistive




Wireless Kinetic Switch

Doorbell Kit



Options:



Wireless Kinetic
Switch or Key Fob

Product Features

- Wireless push button doorbell
- NO power, batteries or cabling required for the push button
- Receiver plugs into a standard wall socket
- Pair up-to 10 switches with one doorbell for multiple access points
- Pair one switch to up-to 5 doorbell receivers for multiple chime locations
- Add one of the IP65 S-Tech Wireless Kinetic Switches with the receiver for gates or door locations that are in the weather
- Range: ≤30m Indoor, ≤80m Outdoor



Specification Overview

Model	Type	Dimensions
KIN-DBK	Wireless Kinetic Doorbell Kit	82 x 52 x 24mm




5827



CABINET LIGHTS

LED Cabinet Light

3w Ø70mm



Product Features

- 3w, 12VDC operation
- 3 colour adjustable (3000K, 4000K, 5000K)
- Can be surface mounted or recess mounted
- Low Profile
- 120° Beam Angle
- Ø70 x 13.7mm
- 57mm cut-out
- 1.9m Fig-8 cable and plug included
- Driver sold separately
- Weight: 62g

Options:


CAB-PWR-6
 Drives 1 – 6 lights
 Non-Dimmable



Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
CAB-0357-3C-WHT	3W	12VDC	3000K/4000K/5000K	180~250lm	120°	White	Ø70 x 13.7mm





EasyLink

Connectable Strip Light




Product Features

- Slim profile connectable light strip
- Fast link and shadow free
- 4 length options - 84mm, 260mm, 500mm and 1000mm
- Multiple connection options and controllers
- Maximum run length: 5m
- 3000K/4000K/5000K selectable
- 120° Beam Angle
- Aluminium base with PC Lens
- 16.5mm wide x 12.5mm high
- IP20 Housing



| Options:



See Accessory
options overleaf



Specification Overview



EasyLink
Accessories

EL-FX
 Input power cable

- 1m long
- Wire to wall switch to turn ON/OFF
- Fixed Colour selection


EL-SW
 Input switch cable

- Push switch to turn on and to cycle colours
- Hold switch to dim light (retains dimming setting)


EL-SEN
 Input Hand Gesture cable

- Wave hand once for ON/OFF
- Wave hand twice for CCT change
- Hold hand under sensor to dim light (retains dimming setting)


EL-EXT1

Driver Extension Cable

- 1m long


EL-EXT1

Splitter Cable

- 250mm long
- 1 to 4 feeds


EL-CLIP-45

45° Install Clips

- Use when you want to mount the EasyLink strip at a 45° angle


EL-CNR

Rotatable Connector

- Adjustable joiner from 80° to 280°
- Fully illuminated (1w)
- 84mm long


EL-LINK1


Light Link Cable

- 90° Corner for when mounting vertically
- Fully illuminated (1w)
- 42 x 42mm long


EL-LINK1

Light Link Cable

- 1m Long
- Use to extend to another area



DOWN LIGHTS



LED Star Lights

3w Ø42mm



Product Features


- 3w
- Available in 3000K, 4000K or 5000K
- Choice of White, Black or Brushed Chrome Trim
- 45° Beam Angle
- Ø42 x 37mm
- 30mm cut-out
- IP20 protection
- 1.9m Fig-8 cable and plug included
- Weight: 62g

Options:

	STAR-PWR-2 Drives 1 – 2 lights Non-Dimmable	
	STAR-PWR-6 Drives 3 – 6 lights Dimmable	



Specification Overview



Model	Power	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
STAR-0329CD-BLK	3w	5000K	300lm	45°	Black	Ø42x37mm
STAR-0329ND-BLK	3w	4000K	290lm	45°	Black	Ø42x37mm
STAR-0329WD-BLK	3w	3000K	270lm	45°	Black	Ø42x37mm
STAR-0329CD-WHT	3w	5000K	300lm	45°	White	Ø42x37mm
STAR-0329ND-WHT	3w	4000K	290lm	45°	White	Ø42x37mm
STAR-0329WD-WHT	3w	3000K	270lm	45°	White	Ø42x37mm
STAR-0329CD-BC	3w	5000K	300lm	45°	Brushed Chrome	Ø42x37mm
STAR-0329ND-BC	3w	4000K	290lm	45°	Brushed Chrome	Ø42x37mm
STAR-0329WD-BC	3w	3000K	27Plm	45°	Brushed Chrome	Ø42x37mm

LED Star Lights
Driver Options


Model	Power Requirement	Dimmable	
STAR-PWR-2	220~240VAC	No	Drives 1 to 2pcs of S-Tech STAR-0329 Star Lights
STAR-PWR-6	220~240VAC	Yes	Drives 3 to 6pcs of S-Tech STAR-0329 Star Lights

Specification STAR-PWR-2

Model	STAR-PWR-2
Number of Lights	1 to 2pcs
Power Requirement	220~240VAC
Junction Box	2 way
Power Consumption	3~6w
Dimmable	No
Operation Temperature	-20°C~+45°C
Warranty	5 Years

Specification STAR-PWR-6

Model	STAR-PWR-6
Number of Lights	3 to 6pcs
Power Requirement	220~240VAC
Junction Box	6 way
Power Consumption	9~18w
Dimmable	Yes, (with LED, Universal or Trailing Edge Dimmers)
Operation Temperature	-20°C~+45°C
Warranty	5 Years

Specifications are subject to change without notice

Note: All ports must be filled in the junction box with either a light or supplied jumper. The STAR-PWR-6 driver will only correctly operate with at least 3 star lights attached to the junction box.


This product is provided with an easy connect junction box for use with S-Tech LED Star Lights. Do not remove the junction box or re-wire or the warranty will be void.

Low Glare Down Light

Smooth


Product Features

- 6w or 10w options
- 3 colour adjustable (3000K/4000K/5000K)
- Low Glare Design
- Smooth White Reflector
- 60° Beam Angle
- Ø85 or Ø103mm size options available
- IP44
- 0.6m Flex cable and plug included



Specification Overview

Model	Power	Cut-Out	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
DLU-0670-3C-W	6w	Ø70mm	3000K/4000K/5000K	500~700lm	60°	White	Ø85 x 84mm
DLU-1090-3C-W	10w	Ø90mm	3000K/4000K/5000K	1000~1200lm	60°	White	Ø103 x 86mm

Low Glare Down Light
 Reflector 10w Ø108mm


Product Features

- 10w
- 3 colour adjustable (3000K, 4000K, 5000K)
- Low Glare Design
- Available in White or Black trim
- 60° Beam Angle
- Ø108 x 90mm
- 90mm cut-out
- IP44 protection
- 0.6m Flex cable and plug included
- Weight: 260g



Specification Overview

Model	Power	Cut-Out	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
DLU-1090R-3C-W	10w	Ø90mm	3000K/4000K/5000K	1000~1200lm	60°	White	Ø108 x 90mm
DLU-1090R-3C-B	10w	Ø90mm	3000K/4000K/5000K	1000~1200lm	60°	Black	Ø108 x 90mm



Low Glare Downlight

UGR<19 25w Ø240mm



Product Features

- 25w
- 3 Colour Adjustable (3000K/4000K/5000K)
- Low Glare Design (UGR<19)
- 60° Beam Angle
- Ø240 x 142mm
- 195 – 230mm cut-out
- IP44
- 0.6m Flex cable and plug included
- Weight: 930g



Specification Overview

Model	Power	Cut-Out	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
DLU-20200-3C-W	25w	Ø195~230mm	3000K/4000K/5000K	2100~2700lm	60°	White	Ø240 x 142mm


LED Down Light

Trade Pack 15


15 PACK


Product Features

- Trade Pack with Surface Mount Socket
- 15pcs per pack
- 9w
- 3 colour adjustable (3000K/4000K/5000K)
- 110° Beam Angle
- Ø115 x 60mm
- 90mm cut-out
- IP44 (front only) protection
- 0.6m Flex cable and plug included
- Weight: 250g



Specification Overview

Model	Power	Cut-Out	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
DL-TRADE15	9w	Ø90mm	3000K/4000K/5000K	700~900lm	110°	White	Ø115 x 60mm




Builders Choice Down Light

9w Ø111mm


4 PACK


Product Features

- 4pcs per pack
- 9w
- 3 colour adjustable (3000K, 4000K, 5700K)
- Supplied with 0.6m flex and plug
- 110° Beam Angle
- Ø111 x 32mm
- 90~95mm cut-out
- Rating: IP44 (front)
- Weight: 250g



Specification Overview

Model	Power	Cut-Out	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
DL-BC9-4	9w	Ø90mm	3000K/4000K/5000K	900~1100lm	110°	White	Ø111 x 32mm


LED Down Light
RDL Integral Driver Series


Product Features

- Integral Driver
- 3 Colour Adjustable (3000K/4000K/5000K)
- Ø85, Ø115, Ø145, Ø170, Ø190 and Ø225mm size options available
- Dimmable
- IP54 (front only)
- 0.6m Flex cable and plug included

Options:

Black Trim
(In some models)

Brushed Chrome Trim
(In some models)



Specification Overview

Model	Power	Cut-Out	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
RDL-0770-3C-W	7W	Ø70~80mm	3000K/4000K/5000K	560~650lm	90°	White	Ø97 x 54mm
RDL-1090-3C-W	10W	Ø90~95mm	3000K/4000K/5000K	971~1139lm	100°	White	Ø115 x 58mm
RDL-13125-3C-W	13W	Ø120~130mm	3000K/4000K/5000K	1050~1320lm	100°	White	Ø145 x 62.5mm
RDL-16145-3C-W	16W	Ø140~160mm	3000K/4000K/5000K	1536~1728lm	100°	White	Ø170 x 66mm
RDL-20165-3C-W	20W	Ø160~170mm	3000K/4000K/5000K	1917~2129lm	100°	White	Ø190 x 75.5mm
RDL-20200-3C-W	20W	Ø200~210mm	3000K/4000K/5000K	2102~2434lm	100°	White	Ø225 x 84mm




Product Features

- Suits RDL-0770-3C-W
- Available in Brushed Chrome or Black options
- Fold down tabs to secure onto downlight
- Ø98 x 3.9mm




Specification

Model	RDL-70-TBC	RDL-70-TBLK
Colour	Brushed Chrome	Black
Mounting	Fold down tabs	
Material	Steel	
Dimension	Ø98x 3.9mm	
Warranty	3 Years	

Down Light Accessories
Decorative Trim


Product Features

- Suits RDL-1090-3C-W and DL-TRADE15 models
- Available in Brushed Chrome or Black options
- Clip-On Trim
- Ø116 x 4mm



Specification

Model	RDL-TRIM	RDL-TRIM-BLK
Colour	Brushed Chrome	Black
Mounting	Clip-on	
Material	Stainless Steel	Steel
Dimension	Ø116 x 4mm	
Warranty	3 Years	

Specifications are subject to change without notice

Sensor Downlight

PIR 9w Ø111mm



Product Features

- 9w
- 3 Colour Adjustable (3000K/4000K/5000K)
- Supplied with Multi-Function Remote Control
- Works in any ambient light conditions
- 100° Beam Angle
- Ø111 x 32mm
- 90 – 95mm cut-out
- IP20
- 0.6m Flex cable and plug included
- Weight: 250g


WITH SENSOR


Remote Control Features

- Turn Light On or Off
- Change Colour Temperature and Adjust Brightness
- Turn PIR On or Off
- Adjust Hold Time, Ambient Brightness and Sensor Sensitivity



Specification Overview

Model	Power	Cut-Out	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
DL-PIR	9w	Ø90mm	3000K/4000K/5000K	800~900lm	100°	White	Ø111 x 32mm



Adjustable Gimbal Down Light

9w Ø108mm En Vogue



Product Features

- 9w
- 3 colour adjustable (3000K, 4000K, 5000K)
- 360° rotatable gimbal
- 90° tilt
- 60° Beam Angle
- Ø108 x 36mm
- 90mm cut-out
- IP44 Housing
- Weight: 370g


Options:



DALI Dimmable Driver



Specification Overview



Model	Power	Cut-Out	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
DL-EV9-3C-W	9w	Ø90mm	3000K/4000K/5000K	810~900lm	60°	White	Ø108 x 36mm



tech
LED Lighting

Adjustable Gimbal Down Light

LED Panel 10w Ø104




Product Features

- 10w
- 3 colour adjustable (3000K, 4000K, 5000K)
- Remote driver with flex and plug
- White, Black or Brushed Chrome Trim options
- 25° tilt
- 100° Beam Angle
- Ø104 x 30mm
- 90mm cut-out
- IP20 Housing
- Weight: 326g

Options:



Dali Dimmable Driver




Specification Overview

LED Down Light
PDL (Flat Trim) 12w Ø108


Product Features

- 12w
- 3 colour adjustable (3000K, 4000K, 5000K)
- Remote Driver
- 110° Beam Angle
- Ø108 x 38mm
- 90mm cut-out
- Flex cable and plug included
- Weight: 350g


 2-Core cable
between driver
and light


Specification Overview

Model	Power	Cut-Out	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
PDL-1290-3C-WHT	12w	Ø90mm	3000K/4000K/5000K	950~1050lm	110°	White	Ø108 x 38mm





LED Down Light
 PDL Recessed Trim Series


Product Features

- Remote Driver
- 3 colour adjustable (3000K, 4000K, 5000K)
- Ø190, Ø225 and Ø300mm size options available
- Dimmable
- IP44
- 0.6m Flex cable and plug included

Options:

Adaptor Plates
(In some models)

Specification Overview

Model	Power	Cut-Out	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
PDL-22165-3C-WHT	22w	Ø160~170mm	3000K/4000K/5000K	2000~2200lm	100°	White	Ø190 x 45mm
PDL-22190-3C-WHT	22w	Ø200~210mm	3000K/4000K/5000K	2000~2200lm	100°	White	Ø228 x 45mm
PDL-35260-3C-WHT	35w	Ø230~260mm	3000K/4000K/5000K	3150~4680lm	100°	White	Ø280 x 52mm



SURFACE MOUNT DOWN LIGHTS




Surface Mount Down Light

Round 10w Ø80mm


Product Features

- 10w
- 4000K
- 36° Beam Angle
- Choice of black or white trim
- Dimmable
- Ø80 x 130mm
- Weight: 500g


Specification Overview

Model	Power	Size	Colour Temp	Lumens	Beam Angle	Trim Colour	Power Requirement
DLS-1080-T-B	10w	Ø80 x 130mm	4000K	1190lm	36°	Black	220~240VAC
DLS-1080-T-W	10w	Ø80 x 130mm	4000K	1190lm	36°	White	220~240VAC

Surface Mount Down Light

Square 16w 115x115mm



Product Features


- 16w
- High CRI: ≥90%
- 3 colour adjustable (3000K, 4000K, 5000K)
- 36° Beam Angle
- Adjustable lighting orientation with 350° horizontal and 25° vertical
- Choice of black or white trim
- Flicker Free Driver
- 115 x 115 x 122mm
- Weight: 900g



Specification Overview

Model	Power	Size	Colour Temp	Lumens	Beam Angle	Trim Colour	Power Requirement
DLS-16SQ-3C-B	16w	115x115x122mm	3000K/4000K/5000K	1600~1840lm	36°	Black	220~240VAC
DLS-16SQ-3C-W	16w	115x115x122mm	3000K/4000K/5000K	1600~1840lm	36°	White	220~240VAC





INDOOR WALL LIGHTS

Indoor Wall Light

10w TACO



Product Features

- 10w
- 3 colour adjustable (3000K, 4000K, 5000K)
- 120° Beam Angle
- Aluminium housing
- Architectural design
- Dimmable
- Flicker Free
- 205 x 103 x 75mm
- IP20 Housing
- Weight: 380g



COLOUR SELECT



DIMMABLE



FICKER-FREE

LIGHTING

Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-TACO-T-W	10w	220~240VAC	3000K/4000K/5000K	675~750lm	120°	White	205x103x75mm



5627

Indoor Wall Light
8w LEAF


Product Features

- 8w
- 4000K
- 160° Beam Angle
- Aluminium housing
- Architectural design
- Dimmable
- Flicker Free
- 145 x 135 x 80mm
- IP20 Housing
- Weight: 360g




Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-LEAF-T-W	8w	220~240VAC	4000K	730lm	160°	White	145x135x80mm



OYSTER LIGHTS



LED Ceiling Light
Oyster Light Series


Product Features

- 200mm, 300mm or 400mm Standard Options
- 300mm available in Standard, Sensor or RGB Halo Options
- 3 colour adjustable (3000K, 4000K, 5000K)
- Slimline housing
- Twist to remove light head
- Easy installation
- Double Insulated
- Includes Loop Terminal
- 120° Beam Angle
- IP54 Housing

300mm Options:



Standard



Sensor Version



Smart HALO Version



COLOUR SELECT




DIMMABLE



Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
OY-20012-3C	12w	Ø200 x 48mm	3000K/4000K/5000K	1200~1440lm	120°	White	450g
OY-30018-3C	18w	Ø300 x 48mm	3000K/4000K/5000K	1800~2160lm	120°	White	850g
OY-30018-MMS	18w	Ø300 x 48mm	3000K/4000K/5000K	1800~2160lm	120°	White	850g
OY-300-HALO	24w	Ø300 x 48mm	2700~6500K + RGB	1800~2160lm	120°	White	850g
OY-40024-3C	24w	Ø386 x 50mm	3000K/4000K/5000K	2400~2800lm	120°	White	1.4kg

Builders Choice
 Ø350mm Oyster Light


Product Features

- Ø350mm
- 3 Wattage Selectable (18w/24w/36w)
- 3 colour adjustable (3000K, 4000K, 5700K)
- Slimline housing with deep cable entry
- Twist to remove light head
- Extra Large Terminal Block with Loop Terminal
- Double Insulated
- 120° Beam Angle
- IP54 (front)



Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
OY-BCWS	18w/24w/36w	Ø350 x 48mm	3000K/4000K/5700K	3600~4200lm	120°	White	1.5kg

GARDEN AND DECK LIGHTS



Garden and Deck Lights
Deck Light Series


Remote control supplied with RGB kit only



Product Features

- Ø30mm or 45mm Options
- Warm White or RGB Options
- 6 pack of LED deck lights including 12v power supply
- RGB version supplied with IR remote control to manage colours
- Stainless steel trim with PC lens
- 90° Beam Angle
- 21mm or 32mm cut-out Options
- Walk over pressure 100kg
- Plug and play design
- IP67 Housing

Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
DECK30-WW	0.6w	Ø30 x 26mm	3000K	60lm	90°	Stainless Steel	60g
DECK30-RGB	0.6w	Ø30 x 26mm	RGB	60lm	90°	Stainless Steel	60g
DECK45-WW	1w	Ø45 x 26mm	3000K	90lm	90°	Stainless Steel	86g
DECK45-RGB	1w	Ø45 x 26mm	RGB	90lm	90°	Stainless Steel	86g



Garden and Deck Lights
3w Spike

Product Features

- 3w
- 12V AC/DC Operation
- Aluminium die cast housing
- Tempered glass face
- 30° Beam Angle
- Ø42 x 75mm (excluding spike)
- IP65 Housing
- IK08 Impact Rating
- Weight: 450g


Specification Overview


5627

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
GS-0330-WW	3w	Ø42 x 75mm	3000K	400lm	30°	Black	450g

OUTDOOR WALL LIGHTS



Builders Choice

Up/Down Wall Light



Product Features

- 10w
- 3 Colour Adjustable (3000K/4000K/5700K)
- Available in Black or White trim options
- Rustproof Polycarbonate Housing
- Double Insulated
- 90° Beam Angle
- IP65 Housing
- IK08 Impact Rating
- Weight: 500g



Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-BCUD-B	10w	200~240VAC	3000K/4000K/5700K	800~900lm	90°	Black	Ø85 x 170mm
WL-BCUD-W	10w	200~240VAC	3000K/4000K/5700K	800~900lm	90°	White	Ø85 x 170mm

Outdoor Wall Light

13w SWIVEL Up/Down



Product Features

- 13w
- Choice of 3000K or 5000K colour temperature
- 90° Beam Angle
- Aluminium housing
- Adjustable top and bottom sections (340°) to direct light where you require
- Choice of Black or White trim
- Ø65 x 220 x 94mm
- IP54 Housing
- IK08 Impact Rating
- Weight: 990g



Specification Overview



Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-SWIVEL13-R-B	13w	220~240VAC	3000K	700lm	90°	Black	Ø65x220x94mm
WL-SWIVEL13-R-W	13w	220~240VAC	3000K	700lm	90°	White	Ø65x220x94mm
WL-SWIVEL13-V-B	13w	220~240VAC	5000K	800lm	90°	Black	Ø65x220x94mm
WL-SWIVEL13-V-W	13w	220~240VAC	5000K	800lm	90°	White	Ø65x220x94mm

Outdoor Wall Light

10w EDGE Up/Down



Product Features

- 10w
- 3 colour adjustable (3000K, 4000K, 5000K)
- 8° Polarised Lens (29°x77°)
- Aluminium housing
- Choice of Black or White trim
- Compact and stylish fitting
- 175 x 90 x 30.5mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 570g



Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-EDGE10-3C-B	10w	220~240VAC	3000K/4000K/5000K	1060~1166lm	29x77°	Black	175x90x30.5mm
WL-EDGE10-3C-W	10w	220~240VAC	3000K/4000K/5000K	1060~1166lm	29x77°	White	175x90x30.5mm

Outdoor Wall Light

10w CUBE Up/Down



Product Features

- 10w
- Choice of 3000K or 5000K colour temperature
- 15° to 120° Adjustable Beam Angle
- Aluminium housing
- Choice of Black or White trim
- 120 x 97 x 100mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 590g



Specification Overview



Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-CUBE10-R-B	10w	220~240VAC	3000K	750lm	15~120°	Black	120x97x100mm
WL-CUBE10-R-W	10w	220~240VAC	3000K	750lm	15~120°	White	120x97x100mm
WL-CUBE10-V-B	10w	220~240VAC	5000K	900lm	15~120°	Black	120x97x100mm
WL-CUBE10-V-W	10w	220~240VAC	5000K	900lm	15~120°	White	120x97x100mm

Outdoor Wall Light

20w CUBE Up/Down



Product Features

- 20w
- Choice of 3000K or 5000K colour temperature
- 15° to 120° Adjustable beam angle
- Aluminium housing
- Choice of Black or White trim
- Polycarbonate face
- 242 x 98 x 100mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 1.1kg



Specification Overview



Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-CUBE20-R-B	18w	220~240VAC	3000K	1150lm	15~120°	Black	242x98x100mm
WL-CUBE20-R-W	18w	220~240VAC	3000K	1150lm	15~120°	White	242x98x100mm
WL-CUBE20-V-B	18w	220~240VAC	5000K	1350lm	15~120°	Black	242x98x100mm
WL-CUBE20-V-W	18w	220~240VAC	5000K	1350lm	15~120°	White	242x98x100mm

Outdoor Wall Light

10w CUBE2 Up/Down



Product Features

- 10w
- 3 colour adjustable (3000K, 4000K, 5000K)
- Settings for light output can be UP/DOWN, DOWN only or UP only
- Asymmetric Beam
- Aluminium housing
- Choice of Black or White trim
- 200 x 100 x 60mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 710g



Specification Overview



Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-CUBE2-3C-B	10w	220~240VAC	3000K/4000K/5000K	600~750lm	40x110°	Black	200x100x60mm
WL-CUBE2-3C-W	10w	220~240VAC	3000K/4000K/5000K	600~750lm	40x110°	White	200x100x60mm

Outdoor Wall Light

8w TOCO



Product Features

- 8w
- 3 colour adjustable (3000K, 4000K, 5000K)
- Use as an UP lighter or DOWN lighter
- 45° Beam Angle
- Aluminium die cast housing
- Available in Black or White Trim
- 202 x 121 x 95mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 500g



Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-TOCO8-3C-B	8w	220~240VAC	3000K/4000K/5000K	680~760lm	45°	Black	202x121x85mm
WL-TOCO8-3C-W	8w	220~240VAC	3000K/4000K/5000K	680~760lm	45°	White	202x121x85mm

Outdoor Wall Light
20w Twin Spot Light


Product Features

- 20w (2x10w)
- 3 colour adjustable (3000K, 4000K, 5000K)
- Option WITH or WITHOUT motion sensor
- Motion Sensor Version: PIR Sensor with Lux and Time Control
- 100° Beam Angle
- Aluminium die cast housing
- Adjustable Light Heads
- 240 x 168 x 181mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 500g



Specification Overview

Model	Type	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-TFL20-3C-B-NS	No Sensor	20w	220~240VAC	3000K/4000K/5000K	1700~1800lm	100°	Black	240x168x181mm
WL-TFL20-3C-B	With Sensor	20w	220~240VAC	3000K/4000K/5000K	1700~1800lm	100°	Black	240x168x181mm

Outdoor Wall Light

12w AURA Wall Wash



Product Features

- 12w
- Choice of 3000K or 5000K colour temperature
- Adjustable face section (340°) for different wall wash effect
- 110° Beam Angle
- Aluminium housing
- Choice of Black or White trim
- 140 x 140 x 48mm
- IP54 Housing
- IK08 Impact Rating
- Weight: 870g



Specification Overview



Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-AURA12-R-B	12w	220~240VAC	3000K	600lm	110°	Black	140X140X48mm
WL-AURA12-R-W	12w	220~240VAC	3000K	600lm	110°	White	140X140X48mm
WL-AURA12-V-B	12w	220~240VAC	5000K	760lm	110°	Black	140X140X48mm
WL-AURA12-V-W	12w	220~240VAC	5000K	760lm	110°	White	140X140X48mm

Outdoor Wall Light
10w Oval Bunker


Product Features

- 10w
- 3 colour adjustable (3000K, 4000K, 5000K)
- 120° Beam Angle
- Aluminium die cast housing
- Polycarbonate face
- 215 x 135 x 50mm
- IP65 Housing
- IK10 Impact Rating
- Weight: 500g

Options:



Eyelid Cover



Grille Cover


Vandal Resistance
IK10


Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-BH10-3C-B	10w	220~240VAC	3000K/4000K/5000K	900~1000lm	120°	Black	215x135x50mm
WL-BH10-3C-W	10w	220~240VAC	3000K/4000K/5000K	900~1000lm	120°	White	215x135x50mm

10w Oval Bunker

Cover Options



Product Features

- Use together with the S-Tech 10w Oval Bunker Range
- Remove existing cover and replace with either the Eyelid or the Grille.
- Available in both Black and White finish

WL-BH10-ELC-B

Eyelid Cover Plate to suit 10w Oval Bunker Light – Black

WL-BH10-ELC-W

Eyelid Cover Plate to suit 10w Oval Bunker Light – White



WL-BH10-GC-B

Grille Cover Plate to suit 10w Oval Bunker Light – Black

WL-BH10-GC-W

Grille Cover Plate to suit 10w Oval Bunker Light – White



Outdoor Wall Light
16w Large Oval Bunker


Product Features

- 16w
- 3 colour adjustable (3000K, 4000K, 5000K)
- 120° Beam Angle
- Aluminium die cast housing
- Polycarbonate face
- 280 x 185 x 100mm
- IP65 Housing
- IK10 Impact Rating
- Weight: 1.15kg

Options:


Cover Options



Microwave Sensor



Dusk-to-dawn sensor

Specification Overview


COLOUR SELECT

Vandal Resistance
IK10


Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-BH16-3C-B	16w	220~240VAC	3000K/4000K/5000K	1208~1366lm	120°	Black	280x185x100mm
WL-BH16-3C-W	16w	220~240VAC	3000K/4000K/5000K	1208~1366lm	120°	White	280x185x100mm

16w Oval Bunker
Cover Options


Product Features

- Use together with the S-Tech 16w Large Oval Bunker Range
- Remove existing cover and replace with either the Eyelid or the Grille.
- Available in both Black and White finish

WL-BH16-ELC-B

Eyelid Cover Plate to suit 16w Large Oval Bunker Light – Black



WL-BH16-ELC-W

Eyelid Cover Plate to suit 16w Large Oval Bunker Light – White



WL-BH16-GC-B

Grille Cover Plate to suit 16w Large Oval Bunker Light – Black


WL-BH16-GC-W

Grille Cover Plate to suit 16w Large Oval Bunker Light – White

Builders Choice
Ø230mm PC Round Bunker


Product Features

- 10w/15w Watt Select
- 3 Colour Adjustable (3000K/4000K/5700K)
- Available in Black or White trim options
- Rustproof Polycarbonate Housing
- Double Insulated
- 100° Beam Angle
- Ø230mm x 50mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 800g




Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-BCBH-B	10w/15w	200~240VAC	3000K/4000K/5700K	1000~1500lm	100°	Black	Ø230 x 50mm
WL-BCBH-W	10w/15w	200~240VAC	3000K/4000K/5700K	1000~1500lm	100°	White	Ø230 x 50mm

Outdoor Wall Light
Ø300mm PC Round Bunker


Product Features

- 10w/16w Watt Select
- 3 colour adjustable (3000K, 4000K, 5000K)
- Available in Black or White housing
- Double Insulated
- 120° Beam Angle
- Robust polycarbonate housing
- Ø300mm x 95mm
- IP65 Housing
- IK10 Impact Rating
- Weight: 1.05kg

Options:


Specification Overview


 Vandal Resistance
IK10


Model	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
WL-BHPC-B	10w/16w	Ø300mm x 95mm	3000K/4000K/5000K	1010-1770lm	120°	Black	1.05kg
WL-BHPC-W	10w/16w	Ø300mm x 95mm	3000K/4000K/5000K	1010-1770lm	120°	White	1.05kg

Outdoor Wall Light
20w Round Bunker


Product Features

- 10w/20w Watt Select
- 3 colour adjustable (3000K, 4000K, 5000K)
- Available in Black or White housing
- Available in Standard or Emergency fitting
- 120° Beam Angle
- Aluminium die cast housing
- Polycarbonate face
- Ø275 x 80mm
- IP65 Housing
- IK10 Impact Rating

Options:

-  Eyelid or Grille Cover
-  Emergency Fitting
-  Microwave Sensor
-  Dusk-to-dawn sensor



IK10

Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-BH20-3C-B	10w/20w	220~240VAC	3000K/4000K/5000K	1800~2000lm	120°	Black	Ø275x80mm
WL-BH20-3C-W	10w/20w	220~240VAC	3000K/4000K/5000K	1800~2000lm	120°	White	Ø275x80mm
WL-BH20-3C-B-E	10w/20w	220~240VAC	3000K/4000K/5000K	1513~1896lm	120°	Black	Ø275x80mm
WL-BH20-3C-W-E	10w/20w	220~240VAC	3000K/4000K/5000K	1513~1896lm	120°	White	Ø275x80mm

Outdoor Wall Light

Turtle Safe / Bug Free / Eyewash Bunker



Product Features

- 10w/20w Watt Select
- 2 colour selectable
Amber (Turtle Friendly/Bug Free*)
and Green (Eye wash)
- 120° Beam Angle
- Aluminium die cast housing
- Ø275 x 80mm
- IP65 Housing
- IK10 Impact Rating
- Weight: 1.25kg

Options:



Standard



Emergency



Microwave Sensor


 Dusk-to-dawn
Sensor


 Eyelid or
Grille Cover

TURTLE SAFE

BUG FREE

EYEWASH LIGHT

Specification Overview


 Vandal Resistance
IK10


Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-BH20-TLG-B	10/20w	200~240VAC	Amber / Green	2000 ~ 2200lm	120°	Black	Ø275x80mm

20w Round Bunker Light
Cover Options


Product Features

- Use together with the S-Tech 20w Round Bunker Range
- Remove existing cover and replace with either the Eyelid or the Grille.
- Available in both Black and White finish

WL-BH20-ELC-B

Eyelid Cover Plate to suit 20w Round Bunker Light – Black


WL-BH20-ELC-W

Eyelid Cover Plate to suit 20w Round Bunker Light – White

WL-BH20-GC-B

Grille Cover Plate to suit 20w Round Bunker Light – Black


WL-BH20-GC-W

Grille Cover Plate to suit 20w Round Bunker Light – White

Outdoor Wall Light

30w Round Large Bunker



Product Features

- 30w
- 3 colour adjustable (3000K, 4000K, 5000K)
- Available in Black or White housing
- 120° Beam Angle
- Aluminium die cast housing
- Polycarbonate face
- Ø350 x 100mm
- IP65 Housing
- IK10 Impact Rating
- Weight: 2.7kg

Options:

	Eyelid Cover
	Emergency Pack
	Microwave Sensor
	Dusk-to-dawn sensor



IK10




Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-BH30-3C-B	30w	220~240VAC	3000K/4000K/5000K	2463~2722lm	120°	Black	Ø350x100mm
WL-BH30-3C-W	30w	220~240VAC	3000K/4000K/5000K	2463~2722lm	120°	White	Ø350x100mm

Outdoor Wall Light
30w Bunker Emergency Pack


Product Features

- Suits WL-BH30-3C-B or WL-BH30-3C-W
- Complete swap out LED board with Emergency Pack assembled
- Includes test switch and indicator light
- Optional Motion Sensor or Dusk-to-dawn PE cell can be installed

Options:

 Microwave Sensor
Model: WL-BH-MMS2

 Dusk-to-dawn sensor
Model: WL-BH-PE


Model	Power	Lumens	CCT	Dimension	Weight
-------	-------	--------	-----	-----------	--------

WL-BH30-EP	30w	2463~2722lm	3000K/4000K/5000K	Ø285 x 30mm	550g
------------	-----	-------------	-------------------	-------------	------

Specification			
CCT	3000K/4000K/5000K	Lifespan	>40,000 hours
Efficacy	>82lm/w	Operation Temperature	-25 °C to +45°C
CRI (%)	≥80	Emergency Power	4w
Beam Angle	120°	Emergency Run-Time	180 minutes
Power Input	220~240VAC	Battery	LifePO4 6.4v 1500mAH
Dimmable	No	Warranty	5 Years 3 Years Battery

Specifications are subject to change without notice



30w Large Bunker Light

Cover Options



Product Features

- Use together with the S-Tech 30w Large Round Bunker Range
- Remove existing cover and replace with either the Eyelid or the Grille.
- Available in both Black and White finish

WL-BH30-ELC-B

Eyelid Cover Plate to suit 30w Large Round Bunker Light – Black

WL-BH30-ELC-W

Eyelid Cover Plate to suit 30w Large Round Bunker Light – White



Bunker Light Accessories
PE Photocell Sensor


Product Features

- Dusk-to-Dawn switching
- Can be installed in the sensor cut-out area of the approved list below (requires minimal re-wiring)
- Multiple lux level settings
- Sensor distinguishes between artificial and natural light



Suitable for Installation in

WL-BH16-3C Series Bunker Lights
 WL-BH20-3C Series Bunker Lights
 WL-BH30-3C Series Bunker Lights
 WL-WP50-3C Wall Pack Light

Specification Overview

Model	Standby Power	Power Requirement	Fits Models	Dimensions
WL-BH20-PE	<0.5w	220~240VAC	WL-BH16, WL-BH20, WL-BH30, WL-WP50	55.5 x 36 x 22mm





Bunker Light Accessories
Microwave Motion Sensor



Product Features

- 5.8G Microwave Motion Sensor
- 2-Step Sensor (ON-OFF)
- Can be installed in the sensor cut-out area of the approved list below (requires minimal re-wiring)
- Dip switch settings for distance, time and daylight sensor.
- Override function to disable microwave sensor



Suitable for Installation in

WL-BH16-3C Series Bunker Lights
WL-BH20-3C Series Bunker Lights
WL-BH30-3C Series Bunker Lights
WL-WP50-3C Wall Pack Light

Specification Overview

Model	Standby Power	Power Requirement	Fits Models	Dimensions
WL-BH20-MMS2	<0.5w	220~240VAC	WL-BH16, WL-BH20, WL-BH30, WL-WP50	72 x 36 x 24.5mm





Apollo Wall Pack

30w/35w/45w/50w Watt Select



Product Features

- Wattage Adjustable (30w/35w/45w/50w)
- 3 Colour Adjustable (3000K/4000K/5000K)
- Flicker Free Driver
- Aluminium Die Cast Housing
- UV Stabilised Opal Polycarbonate Lens
- 120° Beam Angle
- IP65 Housing
- IK10 Impact Rating
- Weight: 3.05kg

Options:


Microwave Sensor Options



Dusk-to-dawn Sensor

Specification Overview



Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
-------	-------	-------	-------------	--------	------------	-------------	------------

WL-WP50-3C	30/35/45/50w	185~265VAC	3000K/4000K/5000K	3150~5460lm	120°	Black	265x300x180mm
------------	--------------	------------	-------------------	-------------	------	-------	---------------

WL-BH-MMS2	Microwave Sensor Kit (ON-OFF) – Dip Switch Setting
WL-WP-MMS	Microwave Sensor Kit (3-Step ON-DIM-OFF) – Requires Remote for set-up
WL-WP-RC	RF Remote Control (simplified) to suit WL-WP-MMS or WP70 Titan Wall Packs
SMD-MR-REMOTE	RF Remote Control (complex) to suit WL-WP-MMS, WP70 Titan Wall Packs and SMD-MR G2 Sensor Battens
WL-BH-PE	PE Cell kit for dusk-to-dawn switching – compatible with WP50, BH16, BH20, BH30 & BHPC wall light models only

Titan Wall Pack

70w/120w Watt Select




Product Features

- Wattage Adjustable (70w/120w)
- 3 Colour Adjustable (3000K/4000K/5000K)
- Built-in Microwave Sensor (can be de-activated)
- Flicker Free Driver
- Aluminium Die Cast Housing
- UV Stabilised Polycarbonate Lens
- 120° Beam Angle
- IP65 Housing
- IK10 Impact Rating
- Weight: 4.52kg

Options:



Remote Control for Sensor set-up



Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WL-WP70-3C	70/120w	185~265VAC	3000K/4000K/5000K	7350~12600lm	120°	Bronze	385x247x195mm
WL-WP-RC	RF Remote Control (simplified) to suit WL-WP-MMS or WP70 Titan Wall Packs						
SMD-MR-REMOTE	RF Remote Control (complex) to suit WL-WP-MMS, WP70 Titan Wall Packs and SMD-MR G2 Sensor Battens						

Wall Pack Accessories

PE Photocell Sensor



Product Features

- Dusk-to-Dawn switching
- Can be installed in the sensor cut-out area of the approved list below (requires minimal re-wiring)
- Multiple lux level settings
- Sensor distinguishes between artificial and natural light



Suitable for Installation in
WL-BH16-3C Series Bunker Lights
WL-BH20-3C Series Bunker Lights
WL-BH30-3C Series Bunker Lights
WL-WP50-3C Wall Pack Light

Specification Overview

Model	Standby Power	Power Requirement	Fits Models	Dimensions
WL-BH20-PE	<0.5w	220~240VAC	WL-BH16, WL-BH20, WL-BH30, WL-WP50	55.5 x 36 x 22mm



Wall Pack Accessories
Microwave Motion Sensor


Product Features

- 5.8G Microwave Motion Sensor
- 3-Step Sensor – ON-DIM-OFF
- Can be installed in the sensor location on the WL-WP50-3C with 2 screws and plug into the driver (requires no re-wiring)
- Adjustable Detection Area, Hold Time, Stand-by Period and Dim level, Lux Sensor (Requires the optional remote control to change the settings.)

**Suitable for Installation in
WL-WP50-3C Wall Pack Light**

Options:



Remote Control for Sensor Settings




Function	Default Setting
Stand-by Dim Level	30%
Hold Time	30s
Detection Area	100%
Stand-by Period	∞ (infinity)
Daylight Threshold	Disabled



Specification Overview

Model	Standby Power	Power Requirement	Fits Model	Dimensions
WL-WP-MMS	<0.5w	220~240VAC	WL-WP50-3C	60 x 25.5 x 27.2mm
WL-WP-RC	RF Remote Control (simplified) to suit WL-WP-MMS or WP70 Titan Wall Packs			
SMD-MR-REMOTE	RF Remote Control (complex) to suit WL-WP-MMS, WP70 Titan Wall Packs and SMD-MR G2 Sensor Battens			



Product Features

- Suitable for use with WL-WP-MMS and WL-WP70-3C
- Use to adjust Microwave Sensor Settings

Button	Function	Description
ON/OFF	Normal ON/OFF	Press the ON/OFF button, sensing function is canceled and the light will remain ON/OFF. Sensor has power-off memory function, that is: Power on again under the "ON" mode of the load lamp, the load lamp enters "ON" mode. Power on again under the "OFF" mode of the load lamp, the load lamp enter the normally "OFF" mode after on for 2s.
Sensor	Recover sensing	Press this button to recover sensing function.
Dim+	Increasing Brightness	Press this button continuously, the brightness will increase. When adjusting the brightness at full brightness, ON/OFF mode is still available.
Dim-	Reducing Brightness	Press this button continuously, the brightness will reduce. When adjusting the brightness at full brightness, ON/OFF mode is still available.
Stand-by Dim Level	Low Brightness	10%, 30%
Hold Time	100% Brightness	30s, 1min, 5min, 10min
Detection Area	Detection Area	100% ↔, 75% ↔, 50% ↔, 25% ↔
Stand-by Period	Stand-by Time	0s, 3min, 10min, +∞
Test	TEST Button	Press this button, the light will turn off after 2 seconds. Restore to last sensing setting after power off.
Daylight Threshold	Threshold	15lux ☽, 50lux ☀, Disable

Specification Overview

Model	Power Requirement	Suits Models	Dimensions
WL-WP-RC	2 x AAA Batteries	WL-WP-MMS, WL-WP70-3C	45 x 120 x 17mm



Wall Pack Accessories
MMS Full Programming Remote


Product Features

- Suitable for use with Models: WL-WP-MMS, WL-WP70-3C and the SMD-MR G2 Sensor Battens
- Use to adjust Microwave Sensor Settings
- Unique IR setting to set remote control distance

Press the "ON/OFF" button, the light goes to constant on/off mode, sensor is disabled. Press "Reset" "Auto Mode" button to quit from this mode and the sensor starts to work. No memory for ON-OFF setting after power off. Sensor mode will auto recover after restart power supply.

Press "Reset" button, all parameters are same as setting of DIP switch or factory settings.

Press "Sensor Motion" button, the light quits from the constant on/off mode, and the sensor starts to work (The latest setting stays in validity).

Press "DIM Test" button, the 1-10V dimming works to test whether the 1-10V DC dimming ports are connected properly. After 2s, it returns to the latest setting automatically.

Long press 3s, Daylight priority mode will be switched to daylight threshold mode, lux value will go back to previous one.

DIM+ / DIM- Short press "Dim+/Dim-" button to set the output lumen lever, each press will $\pm 2\%$ light level.

DH Mode Long press >3s, sensor will be switched to daylight priority mode, if preset daylight value is Disable, press DH Mode can not start daylight priority mode.

QS1	Scene Options	Detection Area	Hold Time	Stand-by Period	Stand-by Dim Level	Daylight Sensor	Induction Mode
QS1	100%	5min	10min	10%	30Lux	HS	
QS2	100%	10min	30min	10%	Disable	HS	
QS3	100%	20min	30min	10%	Disable	HS	

Note: Detection area/Hold time/Stand-by period/Stand-by dim level/Daylight sensor can be adjusted by pressing the corresponding button. The latest setting will stay valid.

Press the "TEST 2S" button can enter the test mode any time. At the mode, the sensor parameters as below: Detection Area is 100%, Hold Time is 5s, Stand-by Dim Level is 10%, Stand-by Period is 0s, daylight sensor disable. This function only for testing. Quit the mode by pressing "Reset" or any other function buttons.

HS / LS Press "HS" button to set the detection area to be high sensitive. Press "LS" button to set the detection area to be low sensitive. The adjustment bases on the "Detection Area" parameter you set.

 Daylight Sensor Set up daylight threshold: 5Lux/15Lux/30Lux/100Lux/150Lux/Disable.

 Stand-by Period Set up stand-by time: 0s/10s/1min/3min/5min/10min/30min/+∞.

 Hold Time Set up hold time: 5s/30s/1min/3min/5min/10min/20min/30min.

 Stand-by Dim Level Set up stand-by dim level: 10%/20%/30%/50%.

 Detection Area Set up detection area: 25%/50%/75%/100%.

 Remote Distance Toggle button can set the distance of remote control and sensor.



Specification Overview


Model	Power Requirement	Suits Models	Dimensions
SMD-MR-REMOTE	2 x AAA Batteries	WL-WP-MMS, WP70 Titan Wall Packs and SMD-MR G2 Sensor Battens	55 x 174 x 22mm

BOLLARD LIGHTS



LED Bollard Light

Walkway Standard Series



Dome Flat

Product Features

- 15w
- 4000K
- Dome or Flat top options
- Aluminium post with PC Lens
- Dome: Ø120mm x 1020mm
- Flat: Ø120mm x 990mm
- IP65, IK08 Housing
- Weight: 4.5kg

Specification Overview

Model	Watt	Type	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
BOL-W120D	15w	Dome	4000K	991lm	360°	Black	Ø120mm x 1020mm
BOL-W120F	15w	Flat	4000K	991lm	360°	Black	Ø120mm x 990mm





Product Features

- 20w
- 4000K
- Dome, Flat or Pillar top options
- Aluminium post with PC Lens
- Dome: Ø160mm x 1015mm
- Flat: Ø160mm x 980mm
- Pillar: Ø160mm x 995mm
- IP65, IK08 Housing
- Weight: 8.25kg

Specification Overview



5627



Model	Watt	Type	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
BOL-W160D	20w	Dome	4000K	1107lm	360°	Black	Ø160mm x 1015mm
BOL-W160F	20w	Flat	4000K	1107lm	360°	Black	Ø160mm x 980mm
BOL-W160P	20w	Pillar	4000K	1107lm	360°	Black	Ø160mm x 995mm

LED Bollard Light

Walkway Louver MAX Series



Product Features

- 20w
- 4000K
- Dome, Flat or Pillar top options
- Aluminium post with PC Lens
- Dome: Ø160mm x 1015mm
- Flat: Ø160mm x 995mm
- Pillar: Ø160mm x 1000mm
- IP65, IK08 Housing
- Weight: 8.25kg



Specification Overview

Model	Watt	Type	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
BOL-L160D	20w	Dome	4000K	1107lm	360°	Black	Ø160mm x 1015mm
BOL-L160F	20w	Flat	4000K	1107lm	360°	Black	Ø160mm x 980mm
BOL-L160P	20w	Pillar	4000K	1107lm	360°	Black	Ø160mm x 995mm



Options:



DALI Dimmable Model

Product Features

- 12w
- 2 Colour Adjustable 3000K/4000K
- 600mm or 900mm Height Options
- Low Glare Design
- Optional DALI Dimmable model available (special order)
- Aluminium post with PC Lens
- Ø100 x 600mm or Ø100 x 900mm
- IP65, IK08 Housing
- Weight: 3.1kg (600mm), 4.3kg (900mm)

Specification Overview



Model	Watt	Type	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
BOL-W1006-2C	12w	Low Glare	3000K/4000K	630/735lm	120°	Black	Ø100mm x 600mm
BOL-W1006-2C-D			Dali Dimmable Version (special order)				
BOL-W1009-2C	12w	Low Glare	3000K/4000K	630/735lm	120°	Black	Ø100mm x 900mm
BOL-W1009-2C-D			Dali Dimmable Version (special order)				

EXIT AND EMERGENCY LIGHTS





Product Features

- 5w
- Available in White or Black housing
- Non-Maintained Emergency Mode
- 85mm with a 143mm adaptor plate
- Recessed Installation
(surface mount boxes available)
- Complies with AS2293.3
- Classification C0:D63;C90:D63
- Ø85mm or Ø143 x 24mm
- IP20
- Weight: 700g

Options:

- Model: EM-SMB-RD
Round Surface Mount Housing – White
- Model: EM-SMB-RT
Square Surface Mount Housing – White
- Model: EM-SMB-IP
IP65 Surface Mount Housing



Specification Overview



Model	Power	Input	Trim Colour	Dimensions
EM-SF	5w	110~240VAC	White	Ø85 / Ø143 x 24mm
EM-SF-B	5w	110~240VAC	Black	Ø85 / Ø143 x 24mm
EM-SMB-RD		Round Surface Mount Housing	White	Ø175 x 55mm
EM-SMB-RT		Square Surface Mount Housing	White	74 x 74 x 55mm
EM-SMB-IP		IP65 Surface Mount Housing	White	200 x 120 x 75mm

Emergency and Exit
Twin Flood Light


S-exit

Product Features

- 6w (2 x 3w)
- Non-Maintained Emergency Mode
- 2 x Adjustable Light Heads
- Replaceable LED Globes
- Slimline Design
- Fast Installation
- Complies with AS2293.3
- 266 x 220 x 50mm
- IP20
- Weight: 1.35kg



Specification Overview




Model	Power	Input	Trim Colour	Dimensions
EM-TWIN	6w (2x3w)	110~240VAC	White	266 x 220 x 50mm

Emergency and Exit
 Surface Mount Exit Sign


Product Features

- 4w
- Polycarbonate Housing
- Maintained Emergency Mode
- Complete with all pictograms
- Complies with AS2293.3
- Classification C0:E4.0;C90:D2.0
- 358 x 211 x 62.5mm
- IP20
- Weight: 800g

Options:



Recessed Kit



Specification Overview



Model	Power	Input	Viewing Distance	Trim Colour	Dimensions
EXIT-SM	4w	110~240VAC	24m	White	358 x 211 x 62.5mm
EXIT-RKIT		Recessed Kit, use together with EXIT-SM to become a recessed fitting		White	457 x 100 x 70mm

Emergency and Exit
Blade Exit Sign


Product Features

- 4w
- Polycarbonate Housing
- Maintained Emergency Mode
- Complete with all pictograms
- Complies with AS2293.3
- Classification C0:E4.0;C90:D2.0
- 358 x 215 x 60mm
- IP20
- Weight: 1.1kg

Options:


Black Fitting



Recessed Kit



Specification Overview



Model	Power	Input	Viewing Distance	Trim Colour	Dimensions
EXIT-SBS	4w	110~240VAC	24m	White	358 x 215 x 60mm
EXIT-SBS-B	4w	110~240VAC	24m	Black	358 x 215 x 60mm
EXIT-RKIT	Recessed Kit, use together with EXIT-SBS to become a recessed fitting			White	457 x 100 x 70mm
EXIT-RKIT-B	Recessed Kit, use together with EXIT-SBS-B to become a recessed fitting			Black	457 x 100 x 70mm



Product Features

- For use with EXIT-SM and EXIT-SBS Exit Sign models
- Polycarbonate housing
- Stainless steel spring clips
- Plug and play connection
- Cut-out: 410 x 75mm
- 457 x 100 x 70mm



Specification Overview

Model	Description	Trim Colour	Cut-Out	Dimensions
EXIT-RKIT	Recessed Kit, use together with EXIT-SM or EXIT-SBS to become a recessed fitting	White	410 x 75mm	457 x 100 x 70mm
EXIT-RKIT-B	Recessed Kit, use together with EXIT-SBS to become a recessed fitting	Black	410 x 75mm	457 x 100 x 70mm

Emergency and Exit
Wall Mount Exit Sign


Product Features

- 3w
- Polycarbonate Housing
- Maintained & Non-maintained Emergency Mode
- Complete with all pictograms
- Complies with AS2293.3
- Classification C0:E4.0;C90:D2.0
- 378 x 160 x 73.5mm
- IP20
- Weight: 1.05kg



Specification Overview



5627

Model	Power	Input	Viewing Distance	Trim Colour	Dimensions
EXIT-WM	3w	110~240VAC	24m	White	378 x 160 x 73.5mm

Emergency and Exit
 Surface Mount JUMBO Exit Sign


S-exit

Product Features

- 6w
- Steel Housing
- Maintained Emergency Mode
- Complete with all pictograms
- Complies with AS2293.3
- Classification C0:D0.32;C90:D10
- 630 x 320 x 100mm
- IP20
- Weight: 1.1kg



Specification Overview



5627

Model	Power	Input	Viewing Distance	Trim Colour	Dimensions
EXIT-JUMBO	6w	110~240VAC	40m	White	630 x 320 x 100mm

SHOPLIGHTS



LED Shop Light

45w Round



Product Features

- 45w
- 5000K
- Low Glare Design
- 60° Beam Angle
- 165mm cut-out
- IP20 Housing
- Weight: 1.2kg



Specification Overview

Model	Power	Size	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
CSL-45165CB	45w	Ø180 x 129mm	5000K	5,080lm	60°	White	1.2kg

LED Shop Light

42w Rectangle



Product Features

- 42w
- 3 colour adjustable (3000K, 4000K, 5000K)
- 120° Beam Angle
- 90° tilt
- 220 x 130mm cut-out
- IP20 Housing
- Weight: 1.8g



Specification Overview

Model	Power	Size	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
CSL-042-3C-W	42w	235 x 145 x 117mm	3000K/4000K/5000K	4500~5000lm	120°	White	1.8kg







T-BAR PANEL LIGHTS

T-Bar Panel Light

300 x 600


Options:
Surface Mount
Frame KitRecessed Ceiling
Frame Kit

Dimmable Driver

Product Features

- 18w
- 3 colour adjustable: 3000K/4000K/5000K
- Backlit design ensuring long life and performance
- Flicker Free Driver
- Low Glare UGR<22
- 120° Beam Angle
- 295 x 595 x 25mm
- IP50 Housing
- Weight: 1.2g

Looking for T-Bar Accessories?

Have a look in the next section to see the accessories available for T-Bar Panels

Specification Overview



COLOUR SELECT



Low Glare

FLICKER-FREE
LIGHTING

Model	Watt	Size	CCT	Lumens	Beam Angle	Trim Colour	Weight
PL-3060-3C	18w	295x595x25mm	3000K/4000K/5000K	1,975~2,291lm	120°	White	1.2kg

T-Bar Panel Light


600 x 600



Options:



Surface Mount Frame Kit



Recessed Ceiling Frame Kit



Dimmable Driver Options



Emergency Pack

Looking for T-Bar Accessories?

Have a look in the next section to see the accessories available for T-Bar Panels

Product Features

- 33w
- 3 colour adjustable: 3000K/4000K/5000K
- Backlit design ensuring long life and performance
- Flicker Free Driver
- Low Glare UGR<22
- 120° Beam Angle
- 595 x 595 x 25mm
- IP50 Housing
- Weight: 1.6kg



Specification Overview

Model	Watt	Size	CCT	Lumens	Beam Angle	Trim Colour	Weight
PL-6060-3C	33w	595x595x25mm	3000K/4000K/5000K	3620~4200lm	120°	White	1.6kg

T-Bar Panel Light

300 x 1200




Product Features

- 33w
- Standard, UGR<19 or Medical Grade Options
- Backlit design ensuring long life and performance
- 3 colour adjustable: 3000K/4000K/5000K (standard and UGR), 4000K for COI panels
- Flicker Free Driver
- Low Glare UGR<22 (standard) or UGR<19 (optional)
- 120° Beam Angle (standard), 90° Beam Angle (UGR<19)
- 295 x 1195 x 25mm
- Rating: IP50
- Weight: 1.6kg

Options:


Surface Mount Frame Kit



Recessed Ceiling Frame Kit



Dimmable Driver Options



Emergency Pack

Looking for T-Bar Accessories?

Have a look in the next section to see the accessories available for T-Bar Panels



COLOUR SELECT



Low Glare



FLICKER-FREE LIGHTING



Specification Overview


Model	Watt	Size	CCT	Lumens	Beam Angle	Trim Colour	Weight
PL-30120-3C	33w	295x1195x25mm	3000K/4000K/5000K	3620~4200lm	120°	White	1.6kg
PL-30120-3C-UGR	33w	295x1195x25mm	3000K/4000K/5000K	Low Glare UGR<19	T-Bar Panel with prismatic diffuser		
PL-312-COI	33w	295x1195x25mm	4000K	Medical Grade	T-Bar Panel (COI Compliant)		

LED T-Bar Panel


600 x 1200




Options:



Surface Mount Frame Kit



Recessed Ceiling Frame Kit



Dimmable Driver Options

Product Features

- 50w
- Backlit design ensuring long life and performance
- 3 Colour Adjustable (3000K/4000K/5000K)
- Flicker Free Driver
- Low Glare UGR<22
- 120° Beam Angle
- White Trim
- 595 x 1195 x 25mm
- Rating: IP50
- Weight: 3.3kg

Looking for T-Bar Accessories?

Have a look in the next section to see the accessories available for T-Bar Panels

Specification Overview



Model	Watt	Size	CCT	Lumens	Beam Angle	Trim Colour	Weight
PL-60120-3C	50w	595x1195x25mm	3000K/4000K/5000K	5467~6217lm	120°	White	3.3kg

T-BAR PANEL ACCESSORIES



T-Bar Panel
Emergency Pack

Product Features

- Maintained emergency back-up pack to suit 33V4 T-Bar panels
- ≥ 180 minutes run time
- Latest Li-Ion battery technology
- Simple installation


Specification
Dimensions

Model	PL-EP-33V4
Suits T-Bar Panel Models	PL-6060-33V4 PL-30120-33V4
Power Requirement	85~265VAC
Emergency Type	Maintained
Emergency Power	4w ± 0.5w
Emergency Duration	≥ 180 minutes
Battery	Li-Ion 8.4V / 2.2Ah
Operation Temperature	0°C~+55°C
Protection Rating	IP20
Approvals	SAA, RCM, CE
Warranty	3 years
Warranty (Battery)	1 year



T-Bar Panel
Power Supply Options

Specification Overview
Image
Model **PL-PWR-36**
Description NON-Dimmable Driver to suit PL-3060-3C

Input Voltage 200-240VAC, 50Hz

Warranty 3 Years

Model **PL-PWR-312/66**
Description NON-Dimmable Driver to suit PL-30120-3C / PL-6060-3C

Input Voltage 200-240VAC, 50Hz

Warranty 3 Years

Model **PL-PWR-612**
Description NON-Dimmable Driver to suit PL-60120-3C

Input Voltage 200-240VAC, 50Hz

Warranty 3 Years

Model **PL-DPS-312/66**
Description Dimmable Driver to suit PL-30120-3C / PL-6060-3C

Input Voltage 200-240VAC, 50Hz

Dimmable Yes (with LED, Universal or Trailing Edge Dimmers)

Warranty 3 Years

Model **PL-DPS-60V5**
Description Dimmable Driver to suit PL-60120-3C

Input Voltage 200-240VAC, 50Hz

Dimmable Yes (with LED, Universal or Trailing Edge Dimmers)


Warranty 3 Years


T-Bar Panel
DALI Dimmable Power Supply

Product Features

Specification
Dimensions

Model	PL-DPS-36W-DALI
Input Voltage	200-240VAC, 50Hz
Power Factor	0.9
Total Harmonic Distortion (THD)	<20% @ 230V
Inrush Current (Typ.)	16A/214uS
Leakage Current	<0.5mA/240V
No Load Wattage	<0.5W @ 230V
Output Voltage Range	30-40V
Rated Output Current	600~1050mA
Open Circuit Voltage	50V
Safety/EMC	IEC/EN61347-1, IEC/EN61347-2-13, IEC/EN62384, IEC/EN55015, IEC/EN61000-3-2
Dimension	144x80x32mm
Weight	200g
Warranty	3 Years



T-Bar Panel Light
 Wire Suspension Kits


Product Features

- Wire Suspension Hanging Kit with accessories
- 1m Length
- Suits models PL-30120-3C and PL-6060-3C



Model	Suits S-Tech T-Bar Panel	Wire Length	Weight
PL-SHC	PL-30120 and PL-6060 Series	1m	220g

Specification

Wire	Stainless Steel	Kit Includes	4 x Clips, 4 x Wire Suspension Cables and Accessories
Finish	Raw	Warranty	3 Years

T-Bar Panel Light
 Surface Mount Frame Kits


Product Features

- Assemble yourself frames
- Powder coated white to match T-Bar Panels
- Available to suit 300x600, 600x600, 300x1200, 600x1200 T-Bar Panels



Model	Suits S-Tech T-Bar Panel	Dimension	Weight
PL-SMFK-3060	PL-3060 Series	300mm x 600mm x 70mm	650g
PL-SMFK-30120	PL-30120 Series	300mm x 1200mm x 70mm	950g
PL-SMFK-6060	PL-6060 Series	600mm x 600mm x 70mm	860g
PL-SMFK-60120	PL-60120 Series	600mm x 1200 x 70mm	1.43kg

Specification

Housing	Aluminium	Kit Includes	2 x Extrusion, 2 x End Plates and 8 x Screws
Finish	Powder Coated		
Trim Colour	White	Warranty	5 Years

Specifications are subject to change without notice

T-Bar Panel Light

Quickfit Surface Mount Frame Kits



Product Features

- Available to suit PL-30120
- Provided in kit form, easy to assemble
- Clip together frames
- Powder Coated White



Model	Suits S-Tech T-Bar Panel	Dimension	Weight
PL-SMFK-312	PL-30120 Series	298mm x 1198mm x 65mm	720g

Specification

Housing	Aluminium	Kit Includes	4 x Clips, 4 x Frame Sections
Finish	Powder Coated		
Trim Colour	White	Warranty	5 Years

Specifications are subject to change without notice

T-Bar Panel Light
 Recessed Ceiling Frame


Product Features

- Designed to be used with S-Tech LED T-Bar Panels
- Powder coated white
- Available to suit 300x1200 or 600x600 T-Bar Panels
- Sold in bulk packs of 10pcs



Model	Suits S-Tech T-Bar Panel	Cut-Out	Dimension	Weight
PL-RCF-30120	PL-30120 Series	310 x 1210mm	1225 x 325 x 40mm	7kg
PL-RCF-6060	PL-6060 Series	610 x 610mm	625 x 625 x 40mm	7kg

Specification

Housing	Aluminium	Kit Includes	10 Pieces of Frames and Brackets
Finish	Powder Coated		
Trim Colour	White	Warranty	5 Years

Specifications are subject to change without notice

T-Bar Panel Light
Recessed Ceiling Frame Kits


Product Features

- Available to suit PL-3060, PL-30120, PL-6060 or PL-60120 options
- Provided in kit form, easy to assemble
- Clip together frames with Stainless Steel Clips
- Powder Coated White



Model	Suits S-Tech T-Bar Panel	Cut-Out	Dimension	Weight
PL-RCFK-36	PL-3060 Series	327mm x 627mm	335mm x 635mm	590g
PL-RCFK-312	PL-30120 Series	327mm x 1227mm	335mm x 1235mm	720g
PL-RCFK-66	PL-6060 Series	627mm x 627mm	635mm x 635mm	720g
PL-RCFK-612	PL-60120 Series	627mm x 1227mm	635mm x 1235mm	1.08kg

Specification

Housing	Aluminium	Kit Includes	4 x Clips, 4 x Frame Sections
Finish	Powder Coated		
Trim Colour	White	Warranty	5 Years

A photograph of a modern gym interior. The ceiling is a light beige color with recessed lighting and long, thin linear light strips. The floor is made of light-colored wood planks. In the background, there are various pieces of gym equipment, including weight machines and a large mirror. In the foreground, a person is using a piece of equipment. The image is split vertically by a large, semi-transparent graphic element. The left side of the graphic is a light gray gradient, and the right side is a white gradient. The word "LINEAR LIGHTS" is written vertically in large, bold, black capital letters, positioned in the center of the graphic.


LINEAR LIGHTS



Product Features



- Designed as individual lighting lengths or can be spliced together with seamless connections with optional accessories
- Multiple Installation: Pendant, Surface Mounted, Wall Mounted
- Available in 602mm, 1212mm & 1512mm lengths
- 3 colours in one: 3000K, 4000K, 5000K (switch select)
- Flicker Free Driver
- Supplied as standard for surface mounting together with a splicing kit to join additional sections
- Aluminium base with PC diffuser
- 110° Beam Angle
- IP20 Housing
- Weight: 1.7kg (602mm), 2.7kg (1212mm), 3.5kg (1512mm)

Options:




Model	Watt	Size	CCT	Lumens	Beam Angle	Trim Colour	Weight
LL-0.6-3C-B	17w	602 x 57 x 76mm	3000-4000-5000K	1500~1650lm	110°	Black	1.7kg
LL-0.6-3C-W	17w	602 x 57 x 76mm	3000-4000-5000K	1500~1650lm	110°	White	1.7kg
LL-1.2-3C-B	36w	1212 x 57 x 76mm	3000-4000-5000K	4000~4700lm	110°	Black	2.7kg
LL-1.2-3C-W	36w	1212 x 57 x 76mm	3000-4000-5000K	4000~4700lm	110°	White	2.7kg
LL-1.5-3C-B	45w	1512 x 57 x 76mm	3000-4000-5000K	5000~5800lm	110°	Black	2.7kg
LL-1.2-3C-W	45w	1512 x 57 x 76mm	3000-4000-5000K	5000~5800lm	110°	White	2.7kg


Refer to the following page for optional accessories

Linear Light Series
 Connection Accessories

Blank Spacer Section


Model	Size	Trim Colour	Weight
LL-BSS-0.3-B	300 x 57 x 76mm	Black	450g
LL-BSS-0.3-W	602 x 57 x 76mm	White	450g


"X" Connector


Model	Size	Trim Colour	Weight
LL-CON-X-B	343 x 343 x 76mm	Black	1.2kg
LL-CON-X-W	343 x 343 x 76mm	White	1.2kg


"L" Connector

Model	Size	Trim Colour	Weight
LL-CON-L-B	200 x 200 x 76mm	Black	800g
LL-CON-L-W	200 x 200 x 76mm	White	800g


"T" Connector

Model	Size	Trim Colour	Weight
LL-CON-T-B	343 x 200 x 76mm	Black	1kg
LL-CON-T-W	343 x 200 x 76mm	White	1kg



"Y" Connector

Model	Size	Trim Colour	Weight
LL-CON-Y-B	326 x 282 x 76mm	Black	1.2kg
LL-CON-Y-W	326 x 282 x 76mm	White	1.2kg

Linear Light Series
Mounting Accessories

Wall Mounting Kit

Model	Trim Colour	Requirement
LL-WMK-B	Black	1 kit per section
LL-WMK-W	White	1 kit per section


Suspension Kit with Ceiling Plate

Model	Trim Colour	Requirement
LL-CP-1.5-B	Black	1 per main section, then suspension kits only for additional sections
LL-CP-1.5-W	White	


Suspension Kit (excludes Ceiling Plate)

Model	Requirement
LL-SK-1.5	1 kit required per section


Linear Light Diffuser Roll

Model	Size
LL-COVER-5	5m length
LL-COVER-10	10m Length
LL-COVER-15	15m Length




BATTEN LIGHTS



LED Switch Batten
2FT 10w


Product Features

- ON/OFF Power Switch on endcap
- 606mm
- 10w
- 3 Colour Adjustable (3000K/4000K/5000K)
- Dimmable
- Double Insulated
- 210° Beam Angle
- Polycarbonate Base and Lens
- 606 x 50 x 85mm
- IP54 Housing
- IK06 Impact Rating
- Weight: 460g



Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SMD-2FTSW-3C	10w	220~240VAC	3000K/4000K/ 5000K	1,300~1,400lm	210°	White	606 x 50 x 85mm

LED Slimline Batten
ECOBAT-SB


Product Features

- 600mm or 1200w Options
- 20w (600mm) or 36w (1200mm)
- 3 Colour Adjustable (3000K/4000K/5000K)
- Slimline Batten
- Large Terminal Block
- 120° Beam Angle
- Aluminium Base with PC Lens
- 600 x 80 x 34mm or 1200 x 80 x 34mm
- IP20 Housing
- IK08 Impact Rating
- Weight: 600g (600mm), 1.12kg (1200mm)



Specification Overview




Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
ECO-SB-2FT-3C	20w	200~240VAC	3000K/4000K/ 5000K	2,100~2,800lm	120°	White	600 x 80 x 34mm
ECO-SB-4FT-3C	36w	200~240VAC	3000K/4000K/ 5000K	3,300~4,100lm	120°	White	1200 x 80 x 34mm

Builders Choice Batten
 Slimline


Product Features

- 1200mm
- 3 Wattage Selectable (20w/30w/40w)
- 4 Colour Adjustable (3000K/4000K/5000K/5700K)
- Aluminium Base with PC Lens
- 20mm Rear Mounting Hole
- Power Terminal Block in both Centre and Endcap for easy termination
- 120° Beam Angle
- IP40 Housing
- IK08 Impact Rating
- Weight: 500g



Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SMD-BCSL	20w/30w/40w	220~240VAC	3000K/4000K/ 5000K/5700K	2,200~4,800lm	120°	White	1200 x 32 x 83mm



G2 Surface Mount Batten


2ft Options

Product Features

- 18w
- Steel Base with PC Lens
- 120° Beam Angle
- IP20 Housing
- IK08 Impact Rating

Standard Batten

- 4 Colour Adjustable (3000K/4000K/5000K/6000K)
- Sensor Ready*



Emergency Batten

- Maintained Emergency Fitting
- 3 Colour Adjustable (4000K/5000K/6000K)



Sensor & Emergency Batten

- Maintained Emergency Fitting
- 3 Colour Adjustable (4000K/5000K/6000K)
- Integral Microwave Sensor (change via DIP switch)



Specification Overview

* Plug-in Microwave Sensor can be installed in Sensor Ready Battens from batch numbers >E06



G2 Surface Mount Batten

4ft Options

Product Features

- Steel Base with PC Lens
- 120° Beam Angle
- IP20 Housing
- IK08 Impact Rating

Standard Batten

- 20w/30w/36w Watt Select
- 4 Colour Adjustable (3000K/4000K/5000K/6000K)
- Sensor Ready*

Dimmable Batten

- 36w
- 3 Colour Adjustable (4000K/5000K/6000K)
- Dimmable with Trailing, LED and Universal Dimmers

Emergency Batten


- Maintained Emergency Fitting
- 20w/30w/36w Watt Select
- 3 Colour Adjustable (4000K/5000K/6000K)

Sensor Batten

- 4 Colour Adjustable (3000K/4000K/5000K/6000K)
- Integral Microwave Sensor (change via DIP switch)

Sensor & Emergency Batten

- Maintained Emergency Fitting
- 4 Colour Adjustable (3000K/4000K/5000K/6000K)
- Integral Microwave Sensor (change via DIP switch)



Options:

Plug-in Microwave Sensor*

Specification Overview

* Plug-in Microwave Sensor can be installed in Sensor Ready Battens from batch numbers >E06

G2 Surface Mount Batten

Low Glare UGR<19




Product Features

- 1183mm (4ft)
- 3 Wattage Selectable (20w/30w/40w)
- 3 Colour Adjustable (4000K/5000K/6000K)
- Steel Base with PC Lens
- 80° Beam Angle
- Low Glare UGR<19
- IP20 Housing
- IK08 Impact Rating
- Weight: 1.1kg

Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SMD-4FT-UGR	20w/30w/40w	220~240VAC	4000K/5000K/6000K	3724~3800lm	80°	White	1183x67x73mm



Surface Mount Batten
Wide Body Batten


Product Features

- 300 x 1200mm Wide Body Batten
- 36w
- 3 Colour Adjustable (3000K/4000K/5000K)
- Steel Base with PC Lens
- 1200 x 300 x 40mm
- 120° Beam Angle
- IP20 Housing
- IK06 Impact Rating
- Weight: 2.8kg



Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SMD-4FTWB-3C	36w	220~240VAC	3000K/4000K/ 5000K	3620~4200lm	120°	White	1200x300x50mm

G3 Weatherproof Batten
 Turtle Safe/Bug Free/Eyewash


Product Features

- Available in Standard and Emergency Models
- 10w / 20w Dual Power Selectable
- 600mm
- 2 colour adjustable (Amber/Green)
- Amber = Turtle Friendly/Bug Free* / Green = Eye wash
- Ø20mm Conduit Entry
- 110° Beam Angle
- PC Base and Lens
- 600 x 95 x 80mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 820g



TURTLE SAFE




BUG FREE



EYEWASH LIGHT

* Whilst our testing using an amber light source has found it will attract approximately 90% less bugs than alternate light sources, there is still a risk of some bugs being attracted to our bug free lighting products.



Specification Overview

Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WP-2FTG3-TLG	10/20w	200~240VAC	Amber / Green	2000 ~ 2200lm	110°	Grey	600x95x80mm
WP-2FTG3-TLG-E		Emergency Version					
WP-G3-PB			Pole brackets to suit G3 battens – set of 2pcs – Fits 26~42mm OD pole – PC Black				

G3 Weatherproof Batten

4ft Options



Product Features

- Available in Standard and Emergency/Sensor Models
- Standard model now Sensor Ready*
- 20w / 40w Dual Power Selectable
- 1200mm
- 3 Colour Adjustable (4000K/5000K/6000K)
- Ø20mm Conduit Entry
- 110° Beam Angle
- PC Base and Lens
- 1200 x 95 x 80mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 1.28kg

Options:

 Plug-in
 Microwave
 Sensor*


Pole Bracket


 Turtle Safe /
 Bug Free /
 Eyewash
 Model

* Plug-in Microwave Sensor can be installed in Sensor Ready Battens from batch numbers >E08


COLOUR SELECT



WATT SELECT



Specification Overview

Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WP-4FTG3-3C	20/40w	200~240VAC	4000-5000-6000K	4000~4800lm/ 2000~2400lm	110°	Grey/Opal	1200x95x80mm
WP-4FTG3-3C-ME	20/40w		Microwave Motion and Emergency Version (motion sensor can be deactivated for standard emergency operation)				
SMD-MMS			Microwave Motion Sensor for SMD/WP Battens (Batches >E08)				
WP-G3-PB			Pole brackets to suit G3 battens – set of 2pcs – Fits 26~42mm OD pole – PC Black				

G3 Weatherproof Batten
 Turtle Safe/Bug Free/Eyewash


Product Features


- Available in Standard and Emergency Models
- 20w / 40w Dual Power Selectable
- 1200mm
- 2 colour adjustable (Amber/Green)
- Amber = Turtle Friendly/Bug Free* / Green = Eye wash
- Ø20mm Conduit Entry
- 110° Beam Angle
- PC Base and Lens
- 1200 x 95 x 80mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 1.28kg


TURTLE SAFE

BUG FREE

EYEWASH LIGHT

* Whilst our testing using an amber light source has found it will attract approximately 90% less bugs than alternate light sources, there is still a risk of some bugs being attracted to our bug free lighting products.



Specification Overview

Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WP-4FTG3-TLG	20/40w	200~240VAC	Amber / Green	4000 ~ 4400lm	110°	Grey	1200x95x80mm
WP-4FTG3-TLG-E		Emergency Version					
WP-G3-PB			Pole brackets to suit G3 battens – set of 2pcs – Fits 26~42mm OD pole – PC Black				



Sensor Setting Options

Detection Area	Hold Time	Daylight Sensor	Standby DIM Level	Standby Period
100%	5 s	Disabled	0%	∞
50%	60 s	On	20%	15 mins
	3 mins			
	10 mins			

Microwave Motion Sensor

Product Features


- Suitable for models SMD-2FT-4C and SMD-4FT-4CWS (batch date >E06), and WP-4FTG3-3C (batch date >E08)
- 3-Step Dimming Function ON-DIM-OFF
- Adjust Stand-by Period and dimming levels. Daylight Threshold, Hold-time and detection area all via the dipswitches on the sensor



Specification

Model	SMD-MMS
Suits Models	SMD-2FT-4C and SMD-4FT-4CWS (Batches >E06) WP-4FTG3-3C (Batches >E08)
Kit Includes	1 x Sensor and Instructions
Microwave Frequency	5.8GHz
Microwave Power	<0.3mW
Operating Current	<30mA
Size	52 x 16 x 16mm
Warranty	3 Years

Specifications are subject to change without notice



Pole Bracket to suit G3 WP Batten

Product Features

- Suitable for G3 WP Batten Series (2ft or 4ft)
- Fits Ø26~42mm pole
- Suitable for round posts only
- Connects to WP Batten mounting brackets



WP-G3-PB Pole Bracket Kit



Specification

Model	WP-G3-PB
Suits Floodlight Models	G3 WP Battens (2ft or 4ft)
Kit Includes	2 x Pole Clamps 2 x Locking Bolts
Colour	Black
Fits Pole Size	Ø26~42mm OD
Finish	Powder Coated
Warranty	2 Years

Weatherproof Batten
STRONG Series


Product Features

- Vandal Proof Security Batten
- 10w / 20w Dual Power Selectable
- 3 Colour Adjustable (3000K/4000K/ 5000K)
- Flicker Free Driver
- Aluminium base with PC diffuser (AU) or Polycarbonate base and diffuser (PC)
- 120° Beam Angle
- IP66, IK10 Housing
- Weight: 1.5kg (AU), 1.3kg (PC)

Specification Overview


IK10


Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
WP-STR2FT-AU	10/20w	200~240VAC	4000K/5000K/6000K	1150~2600lm	120°	Grey	600x70x90mm
WP-STR2FT-PC	10/20w	200~240VAC	4000K/5000K/6000K	1150~2600lm	120°	Grey	675x96x116mm




SECURE WP Series



Product Features

- Vandal Proof Security Batten
- Available in 2FT or 4FT
- 2FT: 28w/32w/36w/40w Power Selectable
- 4FT: 48w/52w/56w/60w Power Selectable
- 3 Colour Adjustable (3000K/4000K/5000K)
- Flicker Free Driver
- Aluminium base with PC diffuser
- 120° Beam Angle
- IP66, IK10 Housing
- Weight: 1.9kg (2FT), 3.4kg (4FT)

Options:



Specification Overview

Model	Watt	Size	CCT	Lumens	Beam Angle	Trim Colour	Weight
WP-SEC2FT-3C	28/32/36/40w	650 x 110 x 97mm	3000-4000-5000K	3220~4800lm	120°	Grey	1.9kg
WP-SEC2FT-EM	2FT Emergency Pack (requires installation into fitting)						
WP-SEC4FT-3C	48/52/56/60w	1170 x 110 x 97mm	3000-4000-5000K	5520~7200lm	120°	Grey	3.4kg
WP-SEC4FT-EM	4FT Emergency Pack (requires installation into fitting)						
WP-SECPWR-28	Driver Pack 28w/32w/36w/40w (requires installation into fitting)						

150

HIGHBAY LIGHTS





LED High Bay

Product Features

- 200w, 150w or 100w Options
- 5000K
- Power input 120~277VAC
- Aluminium die cast housing
- Polycarbonate Lens
- 120° Beam Angle
- Supplied with 1.8m flex and plug
- Optional plug and play microwave motion sensor
- Ø280 x 146mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 2.4kg

Options:



Plug-In Microwave motion sensor



Specification Overview



Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
HB-STELLARO-V	100/150/200w	Ø280x146mm	5000K	16,538~29,898lm	120°	Black	2.4kg

LED High Bay

ASTRA Watt Select UFO



Product Features

- Watt Select 200w-150w-100w
- 3 colour adjustable (3000K, 4000K, 5000K)
- Quality 0-10V Dimmable Driver
- DALI compatible (with optional converter)
- Full range power input 100~305VAC
- Aluminium die cast housing
- Polycarbonate Lens
- 120° Beam Angle
- Supplied with 1.8m flex and plug
- Ø320 x 210mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 4.6kg

Options:


Plug-in Microwave motion sensor




DALI to 0-10V converter



Anti-Glare Lens




Specification Overview



Model	Power	Dimension	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
HB-AS2	100/150/200w	Ø310x150mm	3000K/4000K/5000K	16,007~32,268lm	120°	Black	4.6kg
HB-AS2-LMW	Anti-Glare Lens to suit						

LED High Bay
ASTRA XL Watt Select UFO

Options:


Plug-in Microwave motion sensor



DALI to 0-10V converter

Product Features

- Watt Select 320w-250w-210w
- 3 colour adjustable (3000K, 4000K, 5000K)
- Quality 0-10V Dimmable Driver
- DALI compatible (with optional converter)
- Full range power input 90~305VAC
- Aluminium die cast housing
- Polycarbonate Lens
- 90° Beam Angle
- Supplied with 1.8m flex and plug
- IP65 Housing
- IK10 Impact Rating



Specification Overview




Model	Power	Dimension	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
HB-AS3	210/250/320w	Ø360 x 200mm	3000K/4000K/5000K	33,600~51,628lm	90°	Black	6.7kg


LED High Bay Accessories
Plug and Play MW Sensor <12m

Model	Hardware Requirement	Transmission Power	Dimension (Dia x H)
-------	----------------------	--------------------	---------------------

HB-MMS-ANT54T	S-Tech ASTRA or STELLARO LED Highbay	<0.2mW	Ø51 x 41.3mm
---------------	--------------------------------------	--------	--------------

Specification		Sensor Coverage	
Input Voltage	12-24VDC	Mounting Height	Max. 12m
Transmission Power	<0.2mW	Detection Angle	120° (ceiling mount)
Hold Time	10s, 1min, 5min, 10min, 15min, 20min, 30min, 60min	Product Dimension	Ø51 x 41.3mm
Stand-By DIM Level	0%, 10%, 30%, 50%		
Stand-by Period	1min, 30min, 60min, +∞		
Sensitivity	20%, 50%, 75%, 100%		
Daylight Sensor	10lux, 30lux, 50lux, 100lux, 300lux, 500lux, Disable (ambient light detection) – No Daylight Harvesting Mode		
Protection Rating	IP65	Warranty	5 Years

Installation Diagram


Options	Default factory setting
---------	-------------------------



Remote Control for set-up of HB-MMS-ANT54T
 Model: HB-RC100


Sensitivity: 100%
 Hold Time: 5min
 Daylight Sensor: Disabled
 Stand-By DIM Level: 30%
 Stand By Period: 60min


LED High Bay Accessories
Plug and Play PIR Sensor <15m

Model	Hardware Requirement	Transmission Power	Dimension (Dia x H)
-------	----------------------	--------------------	---------------------

HB-MMS-ANT64T	S-Tech ASTRA or STELLARO LED Highbay	<0.2mW	Ø54.5 x 58.8mm
---------------	--------------------------------------	--------	----------------

Specification		Sensor Coverage	
Input Voltage	12-24VDC	Mounting Height	Max. 15m
Transmission Power	<0.2mW	Detection Angle	120° (ceiling mount)
Hold Time	10s, 1min, 5min, 10min, 15min, 20min, 30min, 60min	Product Dimension	Ø54.5 x 58.8mm
Stand-By DIM Level	0%, 10%, 30%, 50%		
Stand-by Period	1min, 30min, 60min, +∞		
Daylight Sensor	10lux, 30lux, 50lux, Disable		
Protection Rating	IP65	Warranty	5 Years


Installation Diagram


Options	Default factory setting
---------	-------------------------


Remote Control for set-up of HB-MMS-ANT54T
Model: HB-RC100


Sensitivity: 100%
Hold Time: 5min
Daylight Sensor: Disabled
Stand-By DIM Level: 30%
Stand By Period: 60min


LED High Bay Accessories
MW Sensor Remote Control

Model	Hardware Requirement	Dimension (Dia x H)
-------	----------------------	------------------------

HB-RC100	S-Tech LED Highbay fitted with optional Microwave Sensor (HB-MMS-ANT54T or HB-MMS-ANT564T)	Ø30 x 111mm
----------	---	-------------

Specification	Dimensions		
Input Voltage	12-24VDC	Mounting Height	Max. 12m
Transmission Power	<0.2mW	Detection Angle	120° (ceiling mount)
Hold Time	10s, 1min, 5min, 10min, 15min, 20min, 30min, 60min	Product Dimension	Ø30 x 111mm
Stand-By DIM Level	0%, 10%, 30%, 50%		
Stand-by Period	1min, 30min, 60min, +∞		
Sensitivity	20%, 50%, 75%, 100%		
Daylight Sensor	10lux, 30lux, 50lux, 100lux, 300lux, 500lux, Disable (ambient light detection) – No Daylight Harvesting Mode		
Protection Rating	IP65	Warranty	5 Years


Default factory setting

Sensitivity: 100%
 Hold Time: 5min
 Daylight Sensor: Disabled
 Stand-By DIM Level: 30%
 Stand By Period: 60min


High Bay

DALI to 0-10V Converter



Product Features

- Converts DALI signal to 0-10V output
- Compatible with S-Tech LED high bays with 3-wire 0-10V dimming cables
- Dimming range 10%-100%
- Compatible with DALI push button interface
- Ø30 x 111mm
- IP65 Housing
- Weight: 70g



Specification Overview

Model	Power Requirement	Input Signal	Output Signal	Dim Range	Colour	Dimensions
HB-SCD010B	12VDC	DALI	0-10V	10-100%	Black	Ø30x111mm

LED High Bay

600w BLAYZ



Product Features

- 600w
- 4000K
- AC Input Range: 180~305VAC
- Aluminium die cast housing
- Polycarbonate Lens
- 60° Beam Angle
- Supplied with 2.4m flex and plug
- Suspended or fixed mounting options
- Ø565 x 352mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 16.9kg



Specification Overview



Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
HB-BL6-T	600w	Ø565 x 352mm	4000K	78,000lm	60°	Black	16.9kg



FLOODLIGHTS

LED Flood Light
SparX Series


Options:


Product Features

- Watt Select (30w/60w/100w)
- 3 colour adjustable (3000K/4000K/5000K)
- Aluminium die cast housing
- Tempered glass face
- 120° Beam Angle
- Dimmable Version: Dimmable with LED, Universal or Trailing Edge Dimmers
- 250 x 167 x 42mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 950g

Looking for Poles and Accessories?


Have a look at the poles section towards the back of the book


Specification Overview


Model	Type	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
FL-SPARX	Standard	30w/60w/100w	250 x 167 x 42mm	3000/4000 /5000K	2850lm (30w) 5700lm (60w) 9000lm (100w)	120°	Black	950g
FL-SPARX-DIM	Dimmable	100w	250 x 167 x 42mm	3000/4000 /5000K	9000lm	120°	Black	950g

LED Flood Light
SparX-XL Watt Select


Options:


Pole Mounted
Head Frames

Mounting Poles

Product Features

- Watt Select (120w/150w/200w)
- 3 colour adjustable (3000K/4000K/5000K)
- Aluminium die cast housing
- Tempered glass face
- 120° Beam Angle
- 420 x 350 x 55mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 3.7kg

Looking for Poles and Accessories?
Have a look at the poles section towards the back of the book



Specification Overview

Model	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
FL-SPX-XL	120w/150w/200w	420 x 350 x 55mm	3000/4000/5000K	13,200-22,000lm	120°	Black	3.7g

LED Flood Light
 V24 Commercial Series

Options:

 Pole Mounted
Head Frames


Mounting Poles

Product Features

- Available in 50w, 100w, 150w, 200w, 300w or 400w
- Full range power input 90~305VAC
- -20°C~+60°C Operation Temperature
- Aluminium die cast housing
- Tempered glass face
- Symmetrical or Asymmetrical Beam Options
- IP66 Housing
- IK08 Impact Rating

**Looking for Poles
and Accessories?**

 Have a look at the
poles section towards
the back of the book


Specification Overview



Model	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
FL-050S-V	50w	207 x 312 x 53mm	5000K	8,300lm	120°	Black	1.82kg
FL-050A-V	50w	278 x 369 x 52mm	5000K	6,467lm	130/60° Asymmetrical	Black	3.50kg
FL-100S-V	100w	309 x 312 x 53mm	5000K	15,939lm	120°	Black	2.72kg
FL-150S-V	150w	309 x 362 x 53mm	5000K	22,678lm	120°	Black	3.18kg
FL-200S-V	200w	309 x 413 x 53mm	5000K	30,896lm	120°	Black	3.76kg
FL-200A-V	200w	392 x 445 x 57mm	5000K	22,478lm	130/60° Asymmetrical	Black	5.40kg
FL-200S-T	200w	309 x 413 x 53mm	4000K	30,376lm	120°	Black	3.76kg
FL-300S-V	300w	411 x 437 x 61mm	5000K	47,764lm	90° Symmetrical	Black	5.45kg
FL-300A-V	300w	411 x 437 x 61mm	5000K	39,579lm	130/60° Asymmetrical	Black	5.45kg
FL-400S-V	400w	515 x 443 x 62mm	5000K	56,986lm	90° Symmetrical	Black	7.42kg
FL-400S-T	400w	515 x 443 x 62mm	4000K	56,029lm	90° Symmetrical	Black	7.42kg
FL-400A-V	400w	515 x 443 x 62mm	5000K	52,473lm	130/60° Asymmetrical	Black	7.42kg

LED Flood Light
High Power Series

Options:


Pole Mounted Head Frames



Mounting Poles



Cut-off Hood

Product Features

- 500w and 600w Options Available
- 5000K
- Full range power input 90~305VAC
- Aluminium die cast housing
- Tempered glass face
- Symmetrical or Asymmetrical Beam Options
- 637 x 462 x 134mm
- IP66 Housing
- IK08 Impact Rating


Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview

Model	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
FLA-SC500W-RV	500w	637 x 462 x 134mm	5000K	68,604lm	60° Symmetrical	Black	15kg
FLA-SC500W-AV	500w	637 x 462 x 134mm	5000K	64,158lm	150/80° Asymmetrical	Black	15kg
FL-600-RV	600w	637 x 462 x 134mm	5000K	85,132lm	30° Symmetrical	Black	16kg
FL-600-AV	600w	637 x 462 x 134mm	5000K	76,776lm	115/60° Asymmetrical	Black	16kg

LED Flood Light
High Power Series


Product Features

- 1000w or 1200w Options Available
- 5000K
- Full range power input 90~305VAC
- Aluminium die cast housing
- Tempered glass face
- Symmetrical or Asymmetrical Beam Options
- 637 x 1120 x 134mm
- IP66 Housing
- IK08 Impact Rating

Options:

-  Pole Mounted Head Frames
-  Mounting Poles
-  Cut-off Hood

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview

Model	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
FLA-SC1000W-RV	1000w	637 x 1120 x 134mm	5000K	137,208lm	60° Symmetrical	Black	33kg
FLA-SC1000W-AV	1000w	637 x 1120 x 134mm	5000K	128,316lm	150 x 80° Asymmetrical	Black	33kg
FL-1200S-V	1200w	637 x 1120 x 134mm	5000K	170,264lm	30° Symmetrical	Black	34kg
FL-1200A-V	1200w	637 x 1120 x 134mm	5000K	153,552lm	115 x 60° Asymmetrical	Black	34kg

SPECIALISED FLOOD LIGHTS



LED Flood Light

IK10 Series



Product Features

- 100w, 150w or 200w options
- 4000K
- Full range power input 90~305VAC
- Aluminium die cast housing
- Polycarbonate Face
- 90° Beam Angle
- IP66 Housing
- IK10 Impact Rating
- Weight: 4.0kg (100w), 5.2kg (150w), 6.5kg (200w)

Options:

Pole Mounted
Head Frames

Mounting Poles

**Looking for Poles
and Accessories?**

 Have a look at the
poles section towards
the back of the book


Vandal Resistance

IK10

Specification Overview



Model	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
FL-100W-PCT	100w	366 x 330 x 70mm	4000K	13,279lm	90°	Black	17.5kg
FL-150W-PCT	150w	366 x 408 x 70mm	4000K	19,992lm	90°	Black	5.2kg
FL-200W-PCT	200w	366 x 484 x 74mm	4000K	26,636lm	90°	Black	6.5kg

LED Flood Light

100w Sensor



Product Features

- 100w
- 3 colour adjustable (3000K/4000K/5000K)
- Built-in Microwave Sensor with 3-step dimming function (on-dim-off)
- Sensor settings are set using the optional remote control
- Retains last setting by remote control
- Aluminium die cast housing
- Tempered glass face
- 120° Beam Angle
- 394 x 394 x 56mm
- IP66 Housing
- IK08 Impact Rating
- Weight: 4.5kg

Options:

-  Remote Control
-  Pole Mounted Head Frames
-  Mounting Poles

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



via Remote



Specification Overview

Model	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
-------	-------	------------	-------------	--------	------------	-------------	--------

FLA-SC100W-3C-MR

100w

394 x 394 x 56mm

3000/4000/5000K

11,970~13,300lm

120°

Black

4.5kg

FLA-SC-MR-REMOTE

RF Remote Control for microwave motion settings

LED Flood Light
 100w V24 Green Eyewash


EYEWASH LIGHT

Product Features

- 100w
- Green LED's
- Suitable for Eye Wash Stations
- Full range power input 90~305VAC
- Aluminium die cast housing
- Tempered glass face
- 120° Symmetrical Beam Angle
- 309 x 312 x 53mm
- IP66 Housing
- IK08 Impact Rating
- Weight: 2.72kg

Options:



Pole Mounted Head Frames



Mounting Poles

Looking for Poles and Accessories?
 Have a look at the poles section towards the back of the book



Specification Overview



Model	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
FL-100S-GL	100w	309 x 312 x 53mm	Green	13,000lm	120°	Black	2.72kg

LED Flood Light
100w V24 Turtle Friendly


Product Features

- 100w
- Amber LED's
- Turtle and Wildlife Friendly
- Bug Free Lighting*
- Full range power input 90~305VAC
- Aluminium die cast housing
- Tempered glass face
- 120° Symmetrical Beam Angle
- 309 x 312 x 53mm
- IP66 Housing
- IK08 Impact Rating
- Weight: 2.72kg

Options:

Pole Mounted Head Frames

Mounting Poles
Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book




Specification Overview



Model	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
FL-100S-TL	100w	309 x 312 x 53mm	Amber	9,860lm	120°	Black	2.72kg

SPORTS FLOODLIGHTS



LED Flood Light
Stadium Series


Product Features

- Available in 200w, 300w, 400w, 600w, 800w, 1000w or 1200w
- 5000K
- Quality Driver
- Full range power input 90~305VAC
- Aluminium housing
- Polycarbonate lens face
- Choice of 15°, 30°, 40°x80°, 60° or 90°x135° Beam Angles
- IP66 Housing
- IK08 Impact Rating

Looking for Poles and Accessories?
 Have a look at the poles section towards the back of the book



Specification Overview



Model	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
ST-SF-200W	200w	351 x 395 x 125mm	5000K	31,375lm	See options	Black	10.5kg
ST-SF-300W	300w	470 x 395 x 125mm	5000K	46,388lm	See options	Black	12kg
ST-SF-400W	400w	351 x 568 x 125mm	5000K	61,375lm	See options	Black	15kg
ST-SF-600W	5000K	465 x 568 x 125mm	5000K	92,782lm	See options	Black	20kg
ST-SF-800W	800w	715 x 568 x 125mm	5000K	120,981lm	See options	Black	25kg
ST-SF-1000W	1000w	715 x 568 x 125mm	5000K	154,529lm	See options	Black	25kg
ST-SF-1200W	1200w	834 x 568 x 125mm	5000K	188,585lm	See options	Black	27kg

LED Flood Light

PLC G4 High Mast



Product Features

- 5000K
- Asymmetric lens
- Precision Lighting Control using patented optical lens and reflector technology
- Minimal LIGHT Spill and Superior Uniformity
- Optional Split dimming (50% or 100%), 0-10V, DMX or Dali Dimming
- Surge Protector
- Aluminium housing
- Corrosion resistant polyester powder coat finish
- IP66 Housing
- IK10 Impact Rating

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview



Model	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
ST-PLC-420W-__V	420w	675 x 417 x 151mm	5000K	64,260lm	15°, 30°, 60°, 45x90°	Dark Grey	13.9kg
ST-PLC-630W-__V	630w	836 x 417 x 151mm	5000K	96,390lm	15°, 30°, 60°, 45x90°	Dark Grey	16.8kg
ST-PLC-840W-__V	840w	675 x 721 x 151mm	5000K	128,520lm	15°, 30°, 60°, 45x90°	Dark Grey	23.5kg
ST-PLC-1060W-__V	1060w	836 x 721 x 151mm	5000K	162,180lm	15°, 30°, 60°, 45x90°	Dark Grey	28.8kg
ST-PLC-1260W-__V	1260w	836 x 721 x 151mm	5000K	192,780lm	15°, 30°, 60°, 45x90°	Dark Grey	28.8kg
ST-PLC-1500W-__V	1500w	987 x 755 x 153mm	5000K	225,000lm	15°, 30°, 60°, 45x90°	Dark Grey	33.6kg
ST-PLC-1600W-__V	1600w	987 x 755 x 153mm	5000K	240,000lm	15°, 30°, 60°, 45x90°	Dark Grey	33.6kg



Product Features

- 1200w and 1400w Options Available
- 5000K
- Quality Drivers
- Split dimming (50% or 100%), 0-10V or Dali Dimming optional
- 20kV Surge Protector
- Aluminium die cast housing
- Tempered glass face
- Asymmetric Lens providing low glare and minimal light spill to meet Australian Standards
- Corrosion resistant polyester powder coat finish
- IP66 Housing
- IK08 Impact Rating
- Weight: 32.25kg

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview

Model	Power	Dimensions	Colour Temp	Lumens	Beam Angle	Trim Colour	Weight
ST-HML1200G3RK-V	1200w	952 x 757 x 200mm	5000K	133,662lm	Asymmetric Narrow	Black	32.25kg
ST-HML1400G3RK-V	1400w	952 x 757 x 200mm	5000K	149,730lm	Asymmetric Narrow	Black	32.25kg



CANOPY LIGHTS



Canopy Light Series

Small Housing



Product Features

- 100w or 150w* Options
- CCT: 5000K
- 120° Beam Angle
- Large range input 180~295VAC
- Easy connect junction box on rear with large terminal block *
- Aluminium die cast housing
- Opal Polycarbonate Lens
- 455 x 455 x 110mm
- IP65 Housing
- IK10 Impact Rating

Options:


 Driver
Extension
Cable

* Driver must be mounted remote from the light in the 150w version, an extension cable is supplied with each light to enable this



Specification Overview



Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SCL-100W-VS	100w	180~295VAC	5000K	8882lm	120°	White	455x455x110mm
SCL-150W-VSS	150w	180~295VAC	5000K	13350lm	120°	White	455x455x110mm

Canopy Light Series
Large Housing


Product Features

- 100w or 150w or 200w Options
- CCT: 5000K
- Large range input 180~295VAC
- Easy connect junction box on rear with large terminal block*
- 120° Beam Angle
- Aluminium die cast housing
- Opal Polycarbonate Lens
- 580 x 580 x 120mm
- IP65 Housing
- IK10 Impact Rating
- Weight: 11.2kg

Options:


 Driver
Extension
Cable


Specification Overview



Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SCL-100W-VSL	100w	180~295VAC	5000K	10595lm	120°	White	580x580x120mm
SCL-150W-VS	150w	180~295VAC	5000K	14805lm	120°	White	580x580x120mm
SCL-200W-VS	200w	180~295VAC	5000K	18217lm	120°	White	580x580x120mm

STREETLIGHTS AND LANTERNS



MultiFit V3 LED Streetlight

30w 12~24V DC Input






Product Features

- 30w
- 3 Colour Adjustable (3000K/4000K/5000K)
- Black Housing
- Fits 50~60mm spigot size
- 12~24VDC Input Power
- Aluminium die cast housing
- Supports pole top (90° ±15°) or spigot mounting (0° ±15°)
- 150/80° Beam Angle
- IP65 Housing
- IK08 Impact Rating
- Weight: 4.8kg

Options:

 Ø36-40mm Spigot
 Replacement
 (black only)


Mounting Poles


 Outreach or
 Spigot Adaptors
Pole top
mountingSpigot
mounting
**Looking for Poles
and Accessories?**

 Have a look at the
 poles section towards
 the back of the book


Specification Overview


Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions	Spigot Size
SLM-030W-DC	30w	12~24VDC	3000K/ 4000K/ 5000K	4100lm 4298lm 4198lm	150/80°	Black	568x200x109mm	50~60mm




MultiFit V3 LED Streetlight
3CCT Series


Product Features

- Available in 30/60w, 100w, 150w and 200w
- 3 Colour Adjustable (3000K/4000K/5000K)
- Black or Silver Housing (available in some models)
- Fits 50~60mm spigot size
- Full range power input 90~305VAC
- 10KV surge protector
- Aluminium die cast housing
- Supports pole top (90° ±15°) or spigot mounting (0° ±15°)
- 150/80° Beam Angle
- IP65 Housing
- IK08 Impact Rating


Options:

-  Silver Housing (available in some models)
-  Ø36-40mm Spigot Replacement
-  PE Cell (n/a in -N model)
-  Mounting Poles
-  Outreach or Spigot Adaptors

Specification Overview



Looking for Poles and Accessories?
Have a look at the poles section towards the back of the book



Model	Power	Input	Colour Temp	Lumens	Trim Colour	Dimensions	Spigot Size
SLM-WS60-3C <small>Refer to specification page for model options</small>	30w/60w Watt Select	90~305VAC	3000K/4000K/5000K	4100 ~ 7749lm	Black or Silver	568x200x109mm	Ø50~60mm
SLM-100W-3C <small>Refer to specification page for model options</small>	100w	90~305VAC	3000K/4000K/5000K	13,074 ~ 14,087lm	Black or Silver	613x240x109mm	Ø50~60mm
SLM-150W-3C <small>Refer to specification page for model options</small>	150w	90~305VAC	3000K/4000K/5000K	17732 ~ 20,393lm	Black or Silver	683x260x109mm	Ø50~60mm
SLM-200W-3C <small>Refer to specification page for model options</small>	200w	90~305VAC	3000K/4000K/5000K	23,535lm ~ 26,752lm	Black	693x300x109mm	Ø50~60mm

Streetlight Accessories


Spigot Replacement – 40mm


Product Features

- Suitable for SLM-2C and SLM-3C Street Lights
- Fits Ø36~40mm pole spigot
- Available in Black or Silver


Specification
Dimensions

Model	SLM-SPIGOT-40	SLM-SPI-40-S
Colour	Black	Silver
Accepts Spigot	36~40mm OD	
Finish	Powder Coated	
Dimension	115mm x 157.5mm	
Weight	450g	
Warranty	5 Years	


Specification Overview

Model	Colour	Accepts Spigot	Dimension
SLM-SPIGOT-40	Black	Ø36~40mm	115 x 157.5mm
SLM-SPI-40-S	Silver	Ø36~40mm	115 x 157.5mm

LED Street Lantern

30w LumiOrb



Product Features

- 3w to 30w Adjustable
- Amber~5000K Adjustable Options
- Supplied with remote control for programming
- Turtle safe and bug free (amber setting)
- Aluminium die cast housing
- Polycarbonate Diffuser
- Fits Ø42mm spigot, optional spigot adaptors available
- Ø325 x 386mm
- 360° Beam Angle
- IP65 Housing
- IK08 Impact Rating
- Weight: 2.8kg


Options:



Spigot Adaptor Ø60mm or Ø76mm



Pillar Bracket



Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions	Spigot Size
PSL-LO30	30w	220~240VAC	Amber~5000K	2,400~2,670lm	360°	Silver	Ø325 x 386mm	Ø42mm
PSL-LO-A60S			Spigot Adaptor – fits Ø60 vertical spigot – Silver					
PSL-LO-A76S			Spigot Adaptor – fits Ø76 vertical spigot – Silver					
PSL-LO-PBS			Pillar Bracket with 42mm vertical spigot – Silver					

LED Street Lantern

30w Halo


Product Features


- 30w
- 4000K or 5000K Options Available
- Fits 60mm or 76mm spigot size (adaptor included)
- Aluminium die cast housing
- High transmittance, impact resistant polycarbonate lens
- 100° Beam Angle
- Ø520 x 317mm
- IP65 Housing
- IK08 Impact Rating
- Weight: 6kg


Options:


Mounting Poles

Spigot Adaptors

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book


Specification Overview


Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions	Spigot Size
PPL-52030-2-TR	30w	100~240VAC	4000K	2,230lm	120°	Black	Ø520x317mm	60mm or 76mm
PPL-52030-2-VR	30w	100~240VAC	5000K	2,460lm	120°	Black	Ø520x317mm	60mm or 76mm

Round Street Lantern

LUMA 55w 3CCT



Product Features

- 55w
- 3 Colour Adjustable (3000K/4000K/5000K)
- Black Housing
- Fits both 60mm and 76mm spigot size (adaptor included)
- Aluminium die cast housing with PC Lens
- 120° Beam Angle
- IP65 Housing
- IK08 Impact Rating
- Weight: 5.8kg

Options:


Mounting Poles

Spigot Adaptors

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview

Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions	Spigot Size
PSL-LUMA-3C	55w	100~277VAC	3000K/4000K/5000K	5,065lm	120°	Black	Ø430 X 526mm	Ø60mm or Ø76mm



Round Street Lantern

60w 3CCT


Product Features

- 60w
- 3 Colour Adjustable (3000K/4000K/5000K)
- Black Housing
- Fits both 60mm and 76mm spigot size (adaptor included)
- Aluminium die cast housing
- 120° Beam Angle
- IP65 Housing
- IK08 Impact Rating
- Weight: 5.8kg

Options:


Mounting Poles

Spigot Adaptors

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book


Specification Overview


Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions	Spigot Size
PSL-43060-3C-R	60w	100~277VAC	3000K/4000K/5000K	5,534lm	120°	Black	Ø430 X 526mm	Ø60mm or Ø76mm

LED Street Lantern
60w Square


Product Features

- 60w
- 4000K
- Fits 76mm spigot size
- Aluminium die cast housing
- 430 x 430 x 922mm
- 120° Beam Angle
- IP65 Housing
- IK08 Impact Rating
- Weight: 8.8kg


Options:


Mounting Poles

Spigot Adaptors

Looking for Poles and Accessories?

Have a look at the
poles section towards
the back of the book



Specification Overview



Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions	Spigot Size
PSL-43060-TS	60w	100~277VAC	4000K	6,003lm	120°	Black	430x430x922mm	76mm

LED Street Lantern

55w Urban


Product Features

- 55w
- 4000K
- Fits 76mm spigot size
- Aluminium die cast housing, aluminium lid and Steel Spigot and Arm for strength
- Toughened glass face
- Ø650 x 450mm
- 110° Beam Angle
- IP65 Housing
- IK08 Impact Rating
- Weight: 10kg

Options:


Mounting Poles

Spigot Adaptors

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book


Specification Overview


Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions	Spigot Size
PSL-65055-TR	55w	100~277VAC	4000K	4,406lm	110°	Black	Ø650x450mm	76mm

LED Street Lantern
50w Parachute


Product Features

- 50w
- 5000K
- Fits 60mm spigot size
- Aluminium die cast housing
- Polycarbonate face
- 527 x 142 x 551mm
- 120° Beam Angle
- IP65 Housing
- IK08 Impact Rating

Options:


Mounting Poles

Spigot Adaptors

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview



Model	Power	Input	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions	Spigot Size
PSL-PARA-50	50w	100~277VAC	5000K	6,500lm	120°	Black	527 x 142 x 551mm	60mm

SOLAR POWERED LIGHTING



Solar Sensor Light

Sensor Security – 1,000lm



Product Features

- 67w Halogen Equivalent
- 6000K
- Inbuilt PIR motion sensor
- 2 operation modes:
 - Mode 1 = Dimmed brightness (30%) until motion activated (100%)
 - Mode 2 = Light off (0%) until motion activated (100%)
- Separate solar panel with 3.5m lead
- Automatic night-time operation
- 120° Beam Angle
- IP65 Housing
- IK08 Impact Rating
- Weight: 2.2kg




Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SML-10CBA	67w Halogen	6000K	1,000lm	120°	Black	243 x 121 x 92mm

Solar Flood Light
MINI – 1,000lm


Product Features

- 67w Halogen Equivalent
- 6000K
- Dusk to Dawn Operation
- Inbuilt PIR Motion Sensor
- Flexible mounting options
- 4 mode settings
- Automatic night time operation
- 0-90° adjustable light head and solar panel
- Includes kit to remote mount solar panel (length: 2m)
- IP65 Housing
- IK06 Impact Rating
- Weight: 650g



Includes kit to remote mount the solar panel



Fully portable, includes table stand



Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SML-MINI	67w Halogen	4000K	1,000lm	120°	Dark Grey	190 x 146.5 x 26.5mm



S-tech
LED Lighting

Solar Flood Light

UniFlood – 2,000lm



70 Middleborough Road
Burwood East 3151



Product Features

- 130w Halogen Equivalent
- 6000K
- Dusk to Dawn Operation
- Inbuilt PIR Motion Sensor
- Universal mounting options
- Remote control for mode settings
- Automatic night time operation
- 0-180° Adjustable light head and solar panel
- Adjustable Beam Angle (60°, 90° or 120°)
- IP65 Housing
- IK08 Impact Rating
- Weight: 2.3kg

Universal Mounting Options



Wall

Ground

Pole

Flagpole

Ext. Arm

Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SFL-U20	130w Halogen	6000K	2,000lm	Adjustable 60°/90°/120°	Dark Grey	279.5 x 306 x 59.5mm



Solar Flood Light

SolarLED – 4,600lm



Product Features

- 92w Metal Halide Equivalent
- 6000K
- ON/OFF, modes and lighting time adjustable with the supplied remote control
- Automatic night time operation Smart power battery detection – LED brightness will be automatically reduced to prolong battery life
- Separate solar panel with 4m lead
- 120° Beam Angle
- IP65 Housing
- IK10 Impact Rating
- Weight: 2.5kg



Specification Overview



Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SFL-40WA	92w MH	6000K	4,600lm	120°	Black	168 x 104 x 42mm

Solar Flood Light
M Series – 6000lm



Product Features



- 120w Metal Halide Equivalent
- 6000K
- ON/OFF with remote either day or night
- Inbuilt Motion Sensor – 2 operation modes: 1) Dimmed brightness (30%) until motion activated, or 2) Light off (0%) until motion activated
- Sensor can be enabled or disabled
- Auto setting for dusk to dawn lighting*
- Remote control allows brightness, operation time and sensor mode settings
- Automatic night-time operation
- Separate solar panel with 5m lead
- 120° Beam Angle
- IP65 Housing
- IK08 Impact Rating



Options:



Pole Clamp Kit

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SFL-M60	120w MH	6000K	6,000lm	120°	Black	Light: 375 x 275 x 52mm Panel: 600 x 370 x 18mm

Solar Flood Light


9 Series – 9000lm



Product Features

- 180w Metal Halide Equivalent
- 6000K
- Inbuilt Motion Sensor – Dimmed brightness (30%) until motion activated
- Sensor can be enabled or disabled
- Auto setting for dusk-to-dawn lighting
- ECO power mode (50% brightness setting)
- Remote control allows operation time, dusk-to-dawn and sensor mode settings
- Automatic night-time operation
- Separate solar panel with 5m lead
- 120° Beam Angle
- IP65 Housing
- IK08 Impact Rating

Options:



Pole Clamp Kit

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SFL-9000	180w MH	6000K	9,000lm	120°	Black	Light: 388 x 320 x 50mm Panel: 670 x 443 x 22mm



Solar Flood Light


RGB – 5,000lm



Product Features

- 100w Metal Halide Equivalent
- RGB and White Options (3000~6000K)
- Automatic night-time operation
- Remote control allows brightness and lighting time settings
- Separate solar panel with 5m lead
- Match together with the RGB Solar Bollard to synchronise colours
- 120° Beam Angle
- IP65 Housing
- IK08 Impact Rating
- Weight: 5.5kg

Options:



Pole Clamp Kit


Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SFL-RGB60	100w MH	RGB + 3000~6000K	5,000lm	120°	Black	Light: 375 x 275 x 52mm Panel: 600 x 370 x 18mm

Solar Batten
Shed Batten Series

SOLARPOWERED
 Remote
 Control


Product Features

- 21w and 42w Fluorescent Equivalent models available
- 360mm or 600mm Batten Options
- Automatic night-time operation
- Built-in PIR motion sensor
- Supplied with remote control and wall switch
- Light can be used during the day or night
- Dedicated 5V USB charge port
- Cable Length: 5m (panel to light), 3m (light to wall switch)
- 120° Beam Angle
- IP65 Housing
- IK05 Impact Rating



Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SSBL-12W	21w Fluorescent	6000K	1,200lm	120°	White	Light: 360 x 65 x 80mm Panel: 350 x 170 x 17mm
SSBL-15W	44w Fluorescent	6000K	2,500lm	120°	White	Light: 600 x 60 x 85mm Panel: 550 x 170 x 17mm

Solar Batten
SWP Series


Product Features

- 40w and 80w Fluorescent Equivalent models available
- 6000K
- 2FT or 3FT Batten Options
- Automatic night-time operation
- Built-in microwave motion sensor
- Power saving mode (PSM) provides 30% reduced brightness until sensor detects motion
- Intelligent controller
- Cable Length: 5m
- 120° Beam Angle
- IP67 Housing
- IK10 Impact Rating



Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SWP-2FT-18CM	40w Fluorescent	6000K	2,250lm	120°	White	Light: 92x84x600mm Panel: 650 x 325 x 25mm
SWP-3FT-36CM	80w Fluorescent	6000K	4,500lm	120°	White	Light: 92x84x900mm Panel: 700 x 670 x 30mm

Solar Bunker Light

Ø275 – 1,500lm



Product Features

- 150w Incandescent Equivalent
- 4000K
- Dusk to Dawn Operation
- Inbuilt Microwave Motion Sensor
- Auto setting for dusk to dawn lighting*
- Remote control allows brightness, lighting time and sensor mode settings
- Automatic night-time operation
- Separate solar panel with 5m lead
- 120° Beam Angle
- IP66 Housing
- Weight: 3kg



Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SBH-M15	150w Incandescent	4000K	1,500lm	120°	Black	Light: Ø275 x 80mm Panel: 348 x 350 x 16mm

Solar Bollard Light

RGBW



Product Features

- 40w Incandescent Equivalent
- RGB and White (3000~6000K)
- Automatic night-time operation
- Remote Control Included
- Replaceable Battery Pack
- Flange mount or direct bury options
- Flange Mount Options: 600mm or 900mm
Direct Bury: 900mm (above ground)
- Aluminium Post
- IK10 Polycarbonate dome
- IP65, IK10 Rating
- Weight: 3.7kg

Flange Mount
600mmFlange Mount
900mmDirect Bury
900mm
(above ground)

Light & Battery


Vandal Resistance
IK10


Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Post Colour	Post Type	Dimensions (Overall)
SBL-0.6MB-RGBW	40W Incandescent	3000~6000K + RGB	400lm	360°	Black	Flange Mount	Ø260 x 600mm
SBL-1MB-RGBW	40W Incandescent	3000~6000K + RGB	400lm	360°	Black	Flange Mount	Ø260 x 900mm
SBL-1DBP-RGBW	40W Incandescent	3000~6000K + RGB	400lm	360°	Black	Direct Bury	Ø260 x 900mm (above ground)

Solar Bollard Light

Walkway


Product Features

- 30w Incandescent Equivalent
- 4000K
- 4 Mode Settings
- Built-in Microwave Motion Sensor
- Power saving mode (PSM) provides dimmed light until motion detected
- Multi-function Remote Control Included
- 900mm Overall Height
- Aluminium Housing
- Polycarbonate Lens
- IP65 Housing
- IK10 Impact Rating
- Weight: 6kg


Specification Overview


Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SBL-WS9-T	30w Incandescent	4000K	280lm	360°	Black	Ø275 x 900mm

Solar Street Light

Post Top – 4,000lm



SOLARPOWERED



Product Features

- 80w Metal Halide Equivalent
- 2 Colour Adjustable 3000K, 6000K (remote select)
- 4000K
- Inbuilt Motion Sensor – Dimmed brightness (30%) until motion activated
- Auto setting for dusk to dawn lighting*
- Remote control allows brightness, lighting time and sensor mode settings
- Automatic night time operation
- Fits Ø76mm vertical spigot
- Rotatable installation to allow for ultimate direction to achieve best charging results
- 120° Beam Angle
- IP65 Housing
- IK10 Impact Rating
- Weight: 12.2kg

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



DIMMABLE



Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SSL-PTL30	80w MH	3000K + 6000K	4,000lm	120°	Black	Ø580 x 435mm

Solar Pathway Light

3000lm




Product Features

- 60w Metal Halide Equivalent
- 2 Colour Adjustable (3000K/5700K)
- 4 Mode Settings
- Built-in PIR motion sensor (can be disabled for dusk-to-dawn operation)
- Power saving mode (PSM) provides dimmed light until motion detected (with sensor on)
- Rain sensor function
- Multi-function Remote Control Included
- Wall Mount or Spigot Mounting (fits 60mm)
- Aluminium and Polycarbonate Housing
- Type IV Polycarbonate Lens
- IP65 Housing
- IK08 Impact Rating
- Weight: 2.25kg


Options:


Mounting Poles



Outreach or Spigot Adaptors

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview

Model	Equivalent	Colour Temp	Lumens	Optics	Trim Colour	Dimensions
SPL-3000	60w MH	3000K/5700K	3000lm	T4	Dark Grey	350x258x94mm (excluding spigot)

Solar Street Light
G4 Series

SOLARPOWERED

Product Features

- 120w and 240w Halogen Equivalent Options
- 3 colour adjustable (3000K, 4000K, 5000K)
- Single Streetlight head or twin head options
- Automatic night-time operation
- Built-in PIR motion sensor
- Power saving mode (PSM) provides 30% brightness until the sensor detects motion
- Streetlight clamp fits Ø60~90mm post
- Solar Panel spigot available in Ø60mm, Ø76mm or Ø89mm
- Adjustable solar panel allows for ultimate angle and direction to achieve best charging results
- T2M Beam Angle
- IP66 Housing
- IK10 Impact Rating (Light), IK08 (Panel)

Options:

Ø60mm Spigot
Ø76mm Spigot
Ø89mm Spigot

4m Tri-Post
Mounting Pole
(single head only)

5m CHS Galv.
Mounting Pole

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SSL-G415S	120w Halogen	3000K/4000K/5000K	1,800lm	T2M	Dark Grey	Light: 568 x 200 x 109mm Panel: 424 x 403 x 24mm
SSL-G415T	240w Halogen	3000K/4000K/5000K	3,600lm	T2M	Dark Grey	Light: 568 x 200 x 109mm Panel: 803x 424 x 24mm
SSL-G4-S60	Solar Panel Spigot - Fits Ø60mm Vertical Spigot					
SSL-G4-S76	Solar Panel Spigot - Fits Ø76mm Vertical Spigot					
SSL-G4-S89	Solar Panel Spigot - Fits Ø89mm Vertical Spigot					

Solar Street Light

All-in-One Series




Product Features

- 100w, 160w and 200w Metal Halide Equivalent models available
- 4000K
- 3 Mode Settings
- Built-in Microwave Motion Sensor
- Power saving mode (PSM) provides dimmed light until motion detected
- Multi-function Remote Control Included
- Spigot Mounting (fits 60mm or 76mm)
- Aluminium Housing
- 155°/70° (T2M) Polycarbonate Lens
- IP65 Housing
- IK08 Impact Rating
- Weight: 20kg

Options:


Mounting Poles


 Outreach or
Spigot Adaptors

Looking for Poles and Accessories?

 Have a look at the
poles section towards
the back of the book


5627

Specification Overview

Model	Equivalent	Colour Temp	Lumens	Optics	Trim Colour	Dimensions
SSL-AIO-5	100w MH	4000K	5,100lm	T2M	Dark Grey	1102x340x420mm (with vertical spigot)
SSL-AIO-8	160w MH	4000K	8,160lm	T2M	Dark Grey	1102x340x420mm (with vertical spigot)
SSL-AIO-10	200w MH	4000K	10,200lm	T2M	Dark Grey	1102x340x420mm (with vertical spigot)




Product Features

- 90w and 180w Metal Halide Equivalent Options
- 5000K
- Inbuilt Motion Sensor
- Power saving mode (PSM) provides 30% reduced brightness until sensor detects motion
- Fits 60mm spigot size
- Supports pole top or spigot mount
- Automatic night-time operation
- MPPT intelligent controller
- Aluminium die cast housing
- Adjustable solar panel allows for ultimate angle and direction to achieve best charging results.
- 155/70° Beam Angle
- IP65 Housing
- IK08 Impact Rating

Options:



Mounting Poles



Outreach or Spigot Adaptors

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SSL-G330C2	90w MH	5000K	4,500lm	155/70°	Dark Grey	Light: 713 x 297 x 384mm Panel: 503 x 426 x 25mm
SSL-G360C2	180 MH	5000K	9,000lm	155/70°	Dark Grey	Light: 713 x 297 x 384mm Panel: 730 x 503 x 30mm



LED Solar Street Light

Separate Panel – 6,000lm



Product Features

- 120w Metal Halide Equivalent
- 5000K
- 100% operation, dusk to dawn
- Fits 60mm spigot size
- Supports pole top or spigot mount
- Automatic night-time operation
- MPPT intelligent controller
- Aluminium die cast housing
- Adjustable solar panel allows for ultimate angle and direction to achieve best charging results.
- 155/70° Beam Angle
- IP08 Housing
- IK10 Impact Rating
- Weight: 32kg

Options:

-  Pole top spigot adaptor
-  Mounting Pole

Looking for Poles and Accessories?

Have a look at the poles section towards the back of the book



Specification Overview

Model	Equivalent	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SSL-G340CF	120w MH	5000K	6,000lm	155/70°	Dark Grey	Light: 713 x 297 x 384mm Panel: 1300 x 660 x 30mm





POLES AND ACCESSORIES

Mounting Poles

Round Ø89mm – Direct Bury



Options:



Adaptor

Product Features

- Suitable for approved products only
- 5m High (above ground)
- Direct Bury – No rag bolt required
- Ø89mm x 4mm CHS
- Galvanised
- Suitable for Wind Region A or B only

Approved Products

Model	Description
SSL-AIO Series	All-In-One Solar Streetlight (SSL-AIO-5, -8, -10) (Requires SLM-PTA-10160-G Adaptor)
SSL-G330C2	4,500lm Split Panel G3 Solar Streetlight (Requires SLM-PTA-10160-G Adaptor)
SSL-G415S	1,800lm Single Head Solar Street Light (Requires SSL-G4-S89 Adaptor)
SSL-G415T	3,600lm Twin Head Solar Street Light (Requires SSL-G4-S89 Adaptor)
SPL-3000	3,000lm Solar Pathway Light (Requires SLM-PTA-10160 Adaptor)



Specification Overview

Model	Install Type	Pole Height (above ground)	Total Length	Finish	Vertical Spigot Size
FX-PI-6.5DB-89	Direct Bury	5.0m	6.5m	Galvanised	Ø89mm

Mounting Poles
Tri-Post Aluminium Poles


Product Features

- Suitable for approved products only (see following page)
- 3m or 4m High (above ground) Options
- Supplied in 3 pieces (requires assembly)
- Suitable for Wind Region A only
- Ø60mm Vertical Spigot
- Powder Coated Aluminium Construction
- Access Hatch included
- Optional Rag Bolt Kit available or can use M16 Chemset bolts to secure
- Weight: 12.5kg

Options:


Specification Overview



Model	Pole Diameter	Total Height	Door Size	Base Plate	Trim Colour	Vertical Spigot Size
FX-TRI-3.0-PC	Lower Ø120mm Middle Ø76mm Upper Ø60mm	3m	80x250mm	250x250x10mm 177mm centres	Black	Ø60mm
FX-TRI-4.0-PC	Lower Ø120mm Middle Ø76mm Upper Ø60mm	4m	80x250mm	250x250x10mm 177mm centres	Black	Ø60mm
RBK-TRI-4	Rag Bolt Foundation Kit – Including Template					

Mounting Poles
Tri-Post Aluminium Poles

Approved Products for use with Tri-Post Aluminium Poles

Model	Description
PPL-52030-2-VR	30w LED Halo Street Lantern
PSL-34060-3C-R	60w LED Round Street Lantern
PSL-43060-TS	60w LED Square Street Lantern (Requires SLM-PTA-6076 Adaptor)
PSL-LUMA-3C	55w LED Round Street Lantern
PSL-LO30	30w LumiOrb Sphere Lantern *Note: Light base is silver colour (Requires PSL-LO-A60S Adaptor)
SLM-WS60-3C / SLM-WS60-3C-N	30w/60w MultiFit LED Street Light
SSL-PTL30	30w Solar Post Top Lantern (Requires SLM-PTA-6076 Adaptor)
SPL-3000	3,000lm Solar Pathway Light

Mounting Poles
Octagonal – Base Plate

Options:

Caged Rag Bolt Assembly

Streetlight Outreaches

Floodlight Headframes

Adaptors

Product Features

- 3m~12m options available
- Ø60mm or 76mm Vertical Spigot Options
- Hot Dip Galvanised
- Powder Coated Finish Available
- Suitable for Wind Region A or B only



Specification Overview

Model	Install Type	Pole Height (above ground)	Finish	Vertical Spigot Size	Optional Caged Ragbolt Assembly
FX-PI-3.0TP-XX-YY	Base Plate	3m			RBA-PI-445
FX-PI-4.0TP-XX-YY	Base Plate	4m			RBA-PI-445
FX-PI-6.0TP-XX-YY	Base Plate	6m	Galvanised or Powder Coated	Ø60mm x 100mm or Ø76mm x 100mm	RBA-PI-645
FX-PI-8.0TP-XX-YY	Base Plate	8m			RBA-PI-845
FX-PI-10.0TP-XX-YY	Base Plate	10m			RBA-PI-1045
FX-PI-12.0TP-XX-YY	Base Plate	12m			RBA-PI-1245

Model Number: XX = **60** or **76** for vertical spigot size, YY = leave **Blank** for Galvanised or **-PC** for powder coated finish

Example: **FX-PI-3.0TP-60** is a galvanised pole with a 60mm vertical spigot, if powder coated it the model would be **FX-PI-3.0TP-60-PC**

Mounting Poles

Octagonal – Direct Bury



Product Features

- 4m or 6m options available
- Direct Bury – No rag bolt required
- Ø60mm or 76mm Vertical Spigot Options
- Hot Dip Galvanised
- Powder Coated Finish Available
- Suitable for Wind Region A or B only


Options:

 Streetlight
Outreaches

 Floodlight
Headframes


Adaptors



Specification Overview

Model	Install Type	Pole Height (above ground)	Total Length	Finish	Vertical Spigot Size
FX-PI-4.0DB-XXXX	Direct Bury	4.0m	5.1m	Galvanised	Ø60mm x 100mm or Ø76mm x 100mm
FX-PI-6.0DB-XXXX	Direct Bury	6.0m	7.6m	Powder Coated	

 Model Number: XX = **60** or **76** for vertical spigot size, ZZ = leave **Blank** for Galvanised or **-PC** for powder coated finish

Streetlight Accessories
Spigot Adaptor - Enlarge


SLM-SA-3460-B

SLM-SA-3460-S

SLM-SA-6076

Product Features

- Use to Enlarge the Spigot Size
- 36mm~40mm > 60mm or
50mm~60mm > 75mm Options
- Material: Galvanised steel and
Powder Coated

Other types available on application

Specification Overview



Model	Colour	Accepts Spigot	Increases to	Dimension
SLM-SA-3460-B	Black	Ø36~40mm OD	Ø60mm OD	Ø60 x 181mm
SLM-SA-3460-S	Silver	Ø36~40mm OD	Ø60mm OD	Ø60 x 181mm
SLM-SA-6076	Black	Ø50~60mm OD	Ø75mm OD	Ø75 x 216mm

Streetlight Accessories
Spigot Adaptor - Reducer


SLM-PTA-8060-S

SLM-PTA-10160-G

SLM-PTA-10176-G

Product Features

- Use to reduce the Spigot
- Options to fit 76~80mm and 80~93mm OD spigot size
- Options to Reduce to 60mm or 76mm OD
- Available in Galvanised Finish, or Powder Coated Black, Dark Grey or Silver options in some models
- Material: Galvanised Steel

Other types available on application



Specification Overview

Model	Finish	Accepts Spigot	Reduces to	Dimension
SLM-PTA-8060	P/C Black	Ø76~80mm OD	Ø60mm OD	Ø89 x 221mm
SLM-PTA-8060-G	P/C Dark Grey	Ø76~80mm OD	Ø60mm OD	Ø89 x 221mm
SLM-PTA-8060-S	P/C Silver	Ø76~80mm OD	Ø60mm OD	Ø89 x 221mm
SLM-PTA-10160-G	Galvanised	Ø80~93mm OD	Ø60mm OD	Ø101 x 200mm
SLM-PTA-10160-PC	P/C Black	Ø80~93mm OD	Ø60mm OD	Ø101 x 200mm
SLM-PTA-10176-G	Galvanised	Ø80~93mm OD	Ø75mm OD	Ø101 x 200mm
SLM-PTA-10176-PC	P/C Black	Ø80~93mm OD	Ø75mm OD	Ø101 x 200mm



Product Features


- Baseplate 74x134mm
- 60mm OD x 200mm Spigot
- Designed to carry a maximum horizontal load of 8kg
- Hot Dip Galvanised Steel



Specification

Model	SL-WP60-200-G	SL-WP60-200-PC
Colour	Silver (Galvanised)	Black
Spigot	60mm OD	
Housing	Hot Dipped Galvanised Steel	
Dimension (Outreach)	Ø60 x 200mm	
Dimension (Base)	74 x 134mm	
Maximum Load	8kg	
Weight	1.2kg	
Warranty	1 Year	

Dimensions



Specification Overview

Model	Colour	Dimension (base)	Dimension (Outreach)
SL-WP60-200-G	Silver	74 x 134mm	Ø60 x 200mm
SL-WP60-200-PC	Black	74 x 134mm	Ø60 x 200mm

Streetlight Accessories

Single or Double Outreach



SL-SSA60-300-PC



SL-SSA60-300-G

SL-DSA60-300-PC



SL-DSA60-300-G

Product Features

- Available in Single or Double Outreach
- Fits 76mm Post Top
- 60mm OD x 300mm Spigot
- Hot Dip Galvanised Steel
- Powder Coated options available

Other types available on application



Specification Overview

Model	Outreach Type	Finish	Accepts Spigot	Outreach
SL-SSA60-300-G	Single	Galvanised	Ø76mm OD	Ø60mm x 300mm (0° Tilt)
SL-SSA60-300-PC	Single	P/C Black	Ø76mm OD	Ø60mm x 300mm (0° Tilt)
SL-DSA60-300-G	Double	Galvanised	Ø76mm OD	Ø60mm x 300mm (0° Tilt)
SL-DSA60-300-PC	Double	P/C Black	Ø76mm OD	Ø60mm x 300mm (0° Tilt)

Floodlight Accessories
Pole Clamp Kits


Product Features

- Suitable for SFL-M40, SFL-M60, SFL-RGB60, SparX Series and V24 Commercial Floodlight Series (up-to 400w)
- Fits Ø60~90mm pole
- Suitable for round, square or rectangle posts




Specification

Kit Includes

Model	FL-PC	FL-PC-M40	FL-PC-M60	FL-PC-9000	
Suits Floodlight Models	SparX Series, V24 Commercial Series	SFL-M40	SFL-M60, SFL-RGB60	SFL-9000	FL-PC Pole Clamp to suit 240VAC flood Lights
Kit Includes	1 x Pole Clamp	2 x Pole Clamps 1 x Solar Panel Extension			FL-PC-M40 Pole Clamp Kit to suit SFL-M40 FL-PC-M60 Pole Clamp Kit to suit SFL-M60 FL-PC-9000 Pole Clamp Kit to suit SFL-9000
Colour	Black				
Fits Pole Size	Ø60~90mm OD				
Finish	Powder Coated				
Warranty	2 Years				

Specification Overview

Model	Suits Models	Kit Includes
FL-PC	FL-SPARX, FL-SPX-XL, V24 Commercial Series	1 x Pole Clamp
FL-PC-M40	SFL-M40	2 x Pole Clamps, 1 x Solar Panel Extension
FL-PC-M60	SFL-M60, SFL-RGB60	2 x Pole Clamps, 1 x Solar Panel Extension
FL-PC-9000	SFL-9000	2 x Pole Clamps, 1 x Solar Panel Extension

Floodlight Accessories
Extension Arm


Product Features


- Suitable for SFL-U20, SML-10CBA, SparX Series, V24 Commercial Floodlight Series (up-to 200w)
- 825mm Outreach
- Powder Coated Steel



Specification

Dimensions

Model	FL-EXT-1
Suits Floodlight Models	SFL-U20, SML-10CBA, FL-SPARX, FL-SPX-XL, V24 Commercial Flood Series (Max. 200w)
Kit Includes	1 x Extension Arm
Colour	Black
Base Size (WxH)	150mm x 115mm
Arm Length	825mm
Finish	Powder Coated Black
Warranty	2 Years



Specification Overview

Model	Colour	Suits Models	Arm Length	Base Size (WxH)
FL-EXT-1	Black	SFL-U20, SML-10CBA, SparX Series, V24 Commercial Floods (up-to 200w)	825mm	150 x 115mm

Floodlight Accessories
Headframes



Product Features

- Available for Single, Double and Triple Floodlights
- Fits 76mm OD pole spigot
- Available in Galvanised or PC finish
- Galvanised Steel




Specification Overview

Model	Headframe Type	Finish	Accepts Spigot	Dimensions
SL-HF-1F	Single	Galvanised	Ø76mm OD	300 x 90 x 195mm
SL-HF-1F-PC	Single	Black	Ø76mm OD	300 x 90 x 195mm
SL-HF-2F	Twin	Galvanised	Ø76mm OD	1000 x 90 x 195mm
SL-HF-2F-PC	Twin	Black	Ø76mm OD	1000 x 90 x 195mm
SL-HF-3F	Triple	Galvanised	Ø76mm OD	1500 x 90 x 195mm
SL-HF-3F-PC	Triple	Black	Ø76mm OD	1500 x 90 x 195mm



-tech
LED Lighting

Switch to Excellence



Head Office
1 Forum Avenue
Canning Vale WA 6155
Tel: 08 9330 8485

Adelaide Office / Warehouse
Everard Avenue
Keswick SA 5035
Tel: 08 8272 8495

S-Tech Holdings Pty Ltd
ABN: 25162575804

Melbourne Office / Warehouse
Geelong Road
Brooklyn VIC 3012
Tel: 03 8692 6682

Tel: 08 9330 8485
Email: sales@s-tech.com.au
www.s-tech.com.au

Sydney Office / Warehouse
1 Salmon Close
Cranebrook NSW 2749
Tel: 02 8076 2267