



4FT G2 LED Surface Mount Batten – EMERGENCY

Product Features





- Maintained Emergency Fitting
- 36w, 30w, 20w selectable
- 4FT (1200mm)
- 3 colours in one: 4000K, 5000K, 6000K (switch select)
- 120° Beam Angle
- Steel Base with PC Lens
- 1200 x 60 x 65mm
- IP20 Housing
- Weight: 1.6kg



3 Colour Adjustable



Options:

-  Standard Fitting
-  Dimmable Fitting
-  Microwave Sensor Fitting
-  Motion sensor and Emergency Combined

Specification Overview



Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
SMD-4FT-4C-E	36w/30w/20w	220~240VAC	4000-5000-6000K	4140~4533lm (36w)	120°	White	1200x60x65mm

Product Specification





4FT G2 LED Surface Mount Batten – EMERGENCY

Specification

Model	SMD-4FT-3C-E		
Colour Temperature (3CCT)	4000K	5000K	6000K
Lumen (lm) @ 36w setting	4140lm	4533lm	4322lm
Efficiency (lm/w)	>115 _{lm/w}	>125 _{lm/w}	>120 _{lm/w}
Light Source	LED		
CRI (%)	≥80		
Beam Angle	120°		
Power Requirement	220~240VAC		
Power Consumption	36w / 30w / 20w (selectable)		
Emergency Power	3.5w		
Emergency Run-Time	90 minutes		
Housing	Steel Base with PC Diffuser		
Lifespan	>54,000 hours		
Operation Temperature	-20°C~+45°C		
Product Dimension	1200 x 60 x 65mm		
Impact Rating	IK08		
Weight	1.6kg		
Protection Rating	IP20		
Warranty	3 Years		

Specifications are subject to change without notice



Options:



Standard Fitting
Model: SMD-4FT-4C



Dimmable Fitting
Model: SMD-4FT-3C-D



Microwave Sensor Fitting
Model: SMD-4FT-4C-MR



Motion sensor and
Emergency Combined
Model: SMD-4FT-3C-MR-E

Illuminance-Distance Curve

