



## 150w V19E Slimline LED Flood Light

### Product Features

- 150w
- Quality Driver
- Full range power input 90~305VAC
- Aluminium die cast housing
- Tempered glass face
- 120° Beam Angle
- 445 x 392 x 56mm
- IP66 Housing
- Weight: 5.2kg




### Specification Overview

Model	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Trim Colour	Dimensions
FLA-SC150W-V19E	150w	90~305VAC	5000K	19,507lm	120°	Black	445x392x56mm

# Product Specification




## 150w V19E Slimline LED Flood Light



### Specification

Model	FLA-SC150W-V19E
Colour Temperature (1CCT)	5000K
Lumen (lm)	19,507m
Efficiency (lm/w)	>128lm/w
Light Source	LED
CRI (%)	≥80
Beam Angle	120°
Power Requirement	90~305VAC
Power Consumption	151.5w
Dimmable	No
Housing	Diecast aluminium with toughened glass lens
Lifespan	>50,000 hours
Operation Temperature	-20°C~+60°C
Product Dimension	445 x 392 x 56mm
Impact Rating	IK08
Weight	5.2kg
Protection Rating	IP66
Warranty	5 Years



Specifications are subject to change without notice