



# **Product Features**

- **Dusk to Dawn Operation**
- Inbuilt PIR Motion Sensor
- Flexible mounting options
- 4 mode settings
- Automatic night time operation
- 0-90° adjustable light head and solar panel
- Includes kit to remote mount solar panel (length: 2m)
- **IP65 Housing**
- Weight: 650g







Includes kit to remote mount the solar panel

Fully portable, includes table stand












Specification overview							
del	Power	Power Requirement	Colour Temp	Lumens	Beam Angle	Housing Colour	Dimensions

4000K 1000lm SML-MINI 10w Solar 120° Dark Grev 190 x 146.5 x 26.5mm





## 10w MINI Solar Flood Light





#### **PIR Sensor**

Black sensor to eliminate false triggers by interference.

Max. detection: 5m



#### Mode Settings:

**M1** = 10% then 100% when motion detected (60s)

**M2** = 0% then 100% when motion detected (60s)

M3 = 30% brightness (6H) then off

M4 = 100% brghtness (2H) then off

### **Specification**

Model	SML-MINI			
Colour Temperature	4000K			
Lumen (lm)	1000lm			
Efficiency (lm/w)	>100lm/w			
Light Source	LED			
CRI (%)	≥80			
Beam Angle	120°			
Power Requirement	Solar Powered			
Battery	LifePO4, 3.7V 14.8WH			
Charging Time	~8 Hours (from 0-100%)			
Operation Time	Dusk to dawn*			
Housing	PC			
Remote Control	No			
Sensor	PIR (up-to 5m)			
Lifespan	>30,000 hours			
Operation Temperature	-10°C~+55°C			
Product Dimension	190 x 146.5 x 26.5mm			
Weight	650g			
Protection Rating	IP65			
Warranty	1 Years			

Specifications are subject to change without notice



<sup>\*</sup> S-Tech solar products are designed for dusk to dawn operation with added allowance for winter conditions, however you must be aware that in winter months it is possible that some nights the light will not last all night due to inclement weather conditions limiting charging time. Solar is not recommended for any locations classed as critical lighting areas where lighting is required all night.